



WORKBOOK
2023 BIKES





TURBO

LEVO

S-WORKS TURBO LEVO



GLOSS GOLD PEARL OVER CARBON / CARBON



GLOSS BLACK LIQUID METAL / SATIN BLACK CHROME FOIL

The all-new Levo delivers the unbelievable power to ride more trails through an unequalled combination of ride quality, usable power, and ride anywhere range. It's the distillation, application, and amplification of a 40-year obsession with creating the world's best riding mountain bikes. Since its introduction, Levo has set the bar every other e-MTB aims for, and the new Levo raises that bar again. It starts with our Turbo Full Power 2.1 motor and MasterMind Turbo Control Unit (TCU), which provide Levo with a smooth and seamless amplification of your efforts—4x you power that lets you choose where to ride, and when you want to do it. Levo also shatters limitations when it comes to range, amplifying your effort for up to five hours of trail time. Now you can ride farther, and explore more, than ever before. And the optimized chassis boasts 150mm of custom-tuned rear suspension and adjustable geometry that delivers a stable and natural ride like no other. Because at the end of the day, it's the ride that matters. Believe it. When nothing but the best will do, the top-shelf S-Works Levo is outfitted SRAM's premier Eagle AXS XX1 drivetrain, feature-packed FOX Factory suspension, and a super-light, super-tough Roval Traverse SL wheelset.

- Levo's fully integrated Turbo Full Power 2.1 motor, 700Wh battery, and advanced MasterMind Turbo Control Unit deliver category-leading 90 Nm of torque and 565 watts of power for up to five hours of ride time, empowering you to ride farther and faster than ever before.
- The MasterMind Turbo Control Unit is your information hub with customizable display fields, including the exact percentage of battery level, and it features our all-new MicroTune function to adjust power delivery in 10% increments, so you get exactly the support you need to experience precisely the ride you want.
- A dedicated mixed-wheel size design with a 27.5" wheel in the back and 29" up front delivers a nimble ride that carves circles around other full-power e-MTBs. A generous cockpit centers you on the bike, optimizing traction and corner control. The low bottom bracket, slack headtube angle and reduced fork offset keep things stable in the rough.
- Levo offers six distinct geometry settings, allowing you to easily dial-in its performance for any riding style and any terrain. Head tube angle can be adjusted between 63- and 65.5-degrees. Bottom bracket height can be fine-tuned up or down by 7mm.
- Levo's 150mm of rear travel is supple on small bumps, devours square-edged hits without a twitch, eats massive G-outs for breakfast, yet still offers amazing pedal response and delivers your power to the ground with total efficiency.
- The Levo's S-Sizing is based on what matters—rider size and style, not inseam. Six sizes, all with similar headtube lengths and standover, allow you to choose the size that best suits your individual style. Smaller S-Size numbers are going to be nimble and more flickable, while bigger S-Sizes deliver more stability and a roomier ride.

SPECS	Specifications subject to change without notice.
Frame	FACT 11m full carbon, 29" front wheel, 27.5" rear wheel, full internal cable routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel, geo adjust head tube, geo adjust horst pivot
Rear Shock	Fox Float X2 Factory, Kashima, 210x55mm
Fork	Fox 38 Factory, Grip 2 damper, 29", 160mm travel, kashima, 44mm offset
Stem	Deity, 35.0mm
Handlebars	Roval Traverse SL Carbon, riser bar, 6-degree upsweep, 8-degree backsweep, 30mm rise, 780mm, 35.0mm
Grips	Deity Grips
Front Brake	Magura MT7, 4 piston caliper, Loic lever blade
Rear Brake	Magura MT7, 4 piston caliper, Loic lever blade
Rear Derailleur	SRAM XX1 Eagle AXS
Shift Levers	SRAM Eagle AXS Rocker Paddle
Cassette	Sram XG-1299, 12-Speed, 10-52t
Chain	SRAM XX1 Eagle, 12-speed
Crankset	Praxis Carbon M30, custom offset, 160mm
Chainrings	SRAM X-Sync Eagle, 104 BCD, 32T, steel
Front Wheel	Roval Traverse SL 29
Rear Wheel	Roval Traverse SL 27.5, 148mm spacing, XD freehub body
Front Tire	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.6"
Rear Tire	Eliminator, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, 27.5x2.6"
Inner Tubes	Standard, Presta Valve
Saddle	Bridge, 155/143mm, Hollow Ti-rails
SeatPost	RockShox Reverb AXS, 30.9, 1X remote, (S1:100mm, S2: 125mm, S3: 150mm, S4-S6: 170mm)
Seat Binder	Alloy, 38.6mm
Motor	Specialized 2.1 Custom Rx Trail Tuned Motor
UI/Remote	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, over-the-air updates, ANT+/Bluetooth®, w/Handlebar remote
Battery	Specialized M3-700, Integrated battery, 700Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Wiring Harness	Custom Specialized wiring harness
SWAT	SWAT CC steerer tube integrated tool with chain tool and link

PART NO.	DESCRIPTION	COLOR	SIZE
95223-0202	LEVO SW CARBON NB	GLOSS BLACK LIQUID METAL / SATIN BLACK CHROME FOIL	S2
95223-0203			S3
95223-0204			S4
95223-0205			S5
95223-0206			S6
95223-0302	LEVO SW CARBON NB	GLOSS GOLD PEARL OVER CARBON / CARBON / GOLD PEARL OVER CARBON	S2
95223-0303			S3
95223-0304			S4
95223-0305			S5
95223-0306			S6

S-WORKS TURBO LEVO



Blue Ghost Gravity Fade / Black / Light Silver



Metallic White Silver / Chrome / Dream Silver

The all-new Levo delivers the unbelievable power to ride more trails through an unequalled combination of ride quality, usable power, and ride anywhere range. It's the distillation, application, and amplification of a 40-year obsession with creating the world's best riding mountain bikes. Since its introduction, Levo has set the bar every other e-MTB aims for, and the new Levo raises that bar again.

- Levo's fully integrated Turbo Full Power 2.2 motor, 700Wh battery, and advanced MasterMind Turbo Control Unit deliver category-leading 90 Nm of torque and 565 watts of power for up to five hours of ride time, empowering you to ride farther and faster than ever before.
- The MasterMind Turbo Control Unit is your information hub with customizable display fields, including the exact percentage of battery level, and it features our all-new MicroTune function to adjust power delivery in 10% increments, so you get exactly the support you need to experience precisely the ride you want.
- A dedicated mixed-wheel size design with a 27.5" wheel in the back and 29" up front delivers a nimble ride that carves circles around other full-power e-MTBs. A generous cockpit centers you on the bike, optimizing traction and corner control. The low bottom bracket, slack headtube angle and reduced fork offset keep things stable in the rough.
- Levo offers six distinct geometry settings, allowing you to easily dial-in its performance for any riding style and any terrain. Head tube angle can be adjusted between 63- and 65.5-degrees. Bottom bracket height can be fine-tuned up or down by 7mm.
- Levo's 150mm of rear travel is supple on small bumps, devours square-edged hits without a twitch, eats massive G-outs for breakfast, yet still offers amazing pedal response and delivers your power to the ground with total efficiency.
- The Levo's S-Sizing is based on what matters—rider size and style, not inseam. Six sizes, all with similar headtube lengths and standover, allow you to choose the size that best suits your individual style. Smaller S-Size numbers are going to be nimble and more flickable, while bigger S-Sizes deliver more stability and a roomier ride.

S-WORKS TURBO LEVO	S1	S2	S3	S4	S5	S6
Stack (mm)	605	617	626	635	644	653
Reach (mm)	412	432	452	477	502	532
Headtube Angle (°)	64.5	64.5	64.5	64.5	64.5	64.5
BB Height (mm)	352	350	350	350	350	350
BB Drop (mm)	25	27	27	27	27	27
Trail (mm)	130	130	130	130	130	130
Fork Length (full) (mm)	557	567	567	567	567	567
Fork Rake/Offset (mm)	44	44	44	44	44	44
Front Center (mm)	738	760	784	814	843	878
Chainstay Length (mm)	442	442	442	442	442	442
Wheelbase (mm)	1179	1200	1225	1255	1284	1318
Bike Standover Height (mm)	752	776	783	787	788	790
Seat Tube Length (mm)	380	390	405	425	445	465
Seat Tube Angle (degrees)	78	77.2	76.7	76.2	76.2	76.2

SPECS	Specifications subject to change without notice.
Frame	FACT 11m full carbon, 29" front wheel, 27.5" rear wheel, full internal cable routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel, geo adjust head tube, geo adjust horst pivot
Rear Shock	FOX FLOAT X2 Factory, LSC, LSR, 2-position lever, 55x210mm, Kashima
Fork	FOX FLOAT 38 Factory 29, Grip2 damper, 44mm offset, HSC, LSC, HSR, LSR, 110x15mm, 1.5" tapered steerer, 160mm travel, Kashima
Stem	Deity Copperhead, 35.0mm
Handlebars	Roval Traverse SL Carbon, riser bar, 6-degree upsweep, 8-degree backsweep, 30mm rise, 780mm, 35.0mm
Grips	Deity, Knuckleduster, Black
Front Brake	Front Brake Magura MT7, 4-piston caliper, hydraulic disc, 200mm rotor
Rear Brake	Magura MT7, 4-piston caliper, hydraulic disc, 200mm
Rear Derailleur	SRAM XX1 Eagle AXS
Shift Levers	SRAM Eagle AXS Rocker Paddle
Cassette	Sram XG-1299, 12-Speed, 10-52t
Chain	SRAM XX1 Eagle, 12-speed
Crankset	Praxis Carbon M30, custom offset, 160mm
Chainrings	SRAM X-Sync Eagle, 104 BCD, 34T, steel
Front Wheel	Traverse SL 29
Rear Wheel	Traverse SL 27.5
Front Tire	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.6"
Rear Tire	Eliminator, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, 27.5x2.6"
Inner Tubes	Standard, Presta Valve
Saddle	Bridge, 155/143mm, Hollow Ti-rails
SeatPost	RockShox Reverb AXS, 30.9, 1X remote, (S1:100mm, S2:125mm, S3:150mm, S4-S6:170mm)
Seat Binder	Alloy, 38.6mm
Motor	Specialized Turbo Full Power System 2.2 Motor
UI/Remote	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, over-the-air updates, ANT+/Bluetooth®, w/Handlebar remote
Battery	Specialized M3-700, Integrated battery, 700Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug
Wiring Harness	Custom Specialized wiring harness
SWAT	SWAT CC steerer tube integrated tool with chain tool and link

PART NO.	DESCRIPTION	COLOR	SIZE
95221-0702	LEVO SW CARBON NB	Blue Ghost Gravity Fade / Black / Light Silver	S2
95221-0703			S3
95221-0704			S4
95221-0705			S5
95221-0706			S6
95221-0802	LEVO SW CARBON NB	Metallic White Silver / Chrome / Dream Silver	S2
95221-0803			S3
95221-0804			S4
95221-0805			S5
95221-0806			S6

TURBO LEVO PRO



GLOSS RUSTED RED / SATIN REDWOOD

The all-new Levo delivers the unbelievable power to ride more trails through an unequalled combination of ride quality, usable power, and ride anywhere range. It's the distillation, application, and amplification of a 40-year obsession with creating the world's best riding mountain bikes. Since its introduction, Levo has set the bar every other e-MTB aims for, and the new Levo raises that bar again. It starts with our Turbo Full Power 2.1 motor and MasterMind Turbo Control Unit (TCU), which provide Levo with a smooth and seamless amplification of your efforts—4x your power that lets you choose where to ride, and when you want to do it. Levo also shatters limitations when it comes to range, amplifying your effort for up to five hours of trail time. Now you can ride farther, and explore more, than ever before. And the optimized chassis boasts 150mm of custom-tuned rear suspension and adjustable geometry that delivers a stable and natural ride like no other. Because at the end of the day, it's the ride that matters. Believe it. The heavy-hitting Levo Pro delivers unbelievable bang for the buck thanks to SRAM's robust X01 Eagle AXS 12-speed drivetrain, feature-packed FOX Factory suspension, and a hand-built Roval Traverse Carbon wheelset.

- Levo's fully integrated Turbo Full Power 2.1 motor, 700Wh battery, and advanced MasterMind Turbo Control Unit deliver category-leading 90 Nm of torque and 565 watts of power for up to five hours of ride time, empowering you to ride farther and faster than ever before.
- The MasterMind Turbo Control Unit is your information hub with customizable display fields, including the exact percentage of battery level, and it features our all-new MicroTune function to adjust power delivery in 10% increments, so you get exactly the support you need to experience precisely the ride you want.
- A dedicated mixed-wheel size design with a 27.5" wheel in the back and 29" up front delivers a nimble ride that carves circles around other full-power e-MTBs. A generous cockpit centers you on the bike, optimizing traction and corner control. The low bottom bracket, slack headtube angle and reduced fork offset keep things stable in the rough.
- Levo offers six distinct geometry settings, allowing you to easily dial-in its performance for any riding style and any terrain. Head tube angle can be adjusted between 63- and 65.5-degrees. Bottom bracket height can be fine-tuned up or down by 7mm.
- Levo's 150mm of rear travel is supple on small bumps, devours square-edged hits without a twitch, eats massive G-outs for breakfast, yet still offers amazing pedal response and delivers your power to the ground with total efficiency.
- The Levo's S-Sizing is based on what matters—rider size and style, not inseam. Six sizes, all with similar headtube lengths and standover, allow you to choose the size that best suits your individual style. Smaller S-Size numbers are going to be nimble and more flickable, while bigger S-Sizes deliver more stability and a roomier ride.

SPECS	Specifications subject to change without notice.
Frame	FACT 11m full carbon, 29" front wheel, 27.5" rear wheel, full internal cable routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel, geo adjust head tube, geo adjust horst pivot
Rear Shock	Fox Float X2 Factory, Kashima, 210x55mm
Fork	Fox 38 Factory, Grip 2 damper, 29", 160mm travel, kashima, 44mm offset
Stem	Deity, 35.0mm
Handlebars	Roval Traverse SL Carbon, riser bar, 6-degree upsweep, 8-degree backsweep, 30mm rise, 780mm, 35.0mm
Grips	Deity Grips
Front Brake	SRAM Code RSC, 4-piston caliper, hydraulic disc, S1-S3: 200mm, S4-S6: 220mm
Rear Brake	SRAM Code RSC, 4-piston caliper, hydraulic disc, 200mm
Rear Derailleur	SRAM X01 Eagle AXS
Shift Levers	SRAM Eagle AXS Rocker Paddle
Cassette	SRAM XG-1295 Eagle, 10-52t
Chain	SRAX X01 Eagle, 12-speed
Crankset	Praxis Carbon M30, custom offset, 160mm
Chainrings	SRAM X-Sync Eagle, 104 BCD, 32T, steel
Front Wheel	Roval Traverse Carbon 29
Rear Wheel	WH-TRAVERSE 29 27.5 CARBON 148:FS
Front Tire	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.6"
Rear Tire	Eliminator, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, 27.5x2.6"
Inner Tubes	Standard, Presta Valve
Saddle	Bridge, 155/143mm, Hollow Ti-rails
SeatPost	Bike Yoke Revive dropper post, 34.9mm diameter, S1: 125mm, S2/S3: 160mm, S4-6: 180mm
Seat Binder	Alloy, 38.6mm
Motor	Specialized 2.1 Custom Rx Trail Tuned Motor
UI/Remote	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, over-the-air updates, ANT+/Bluetooth®, w/Handlebar remote
Battery	Specialized M3-700, Integrated battery, 700Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Wiring Harness	Custom Specialized wiring harness
SWAT	SWAT CC steerer tube integrated tool with chain tool and link

PART NO.	DESCRIPTION	COLOR	SIZE
95223-1102	LEVO PRO CARBON NB	GLOSS RUSTED RED / SATIN REDWOOD	S2
95223-1103			S3
95223-1104			S4
95223-1105			S5
95223-1106			S6

TURBO LEVO PRO



Satin Redwood / Smoke / Black

The all-new Levo delivers the unbelievable power to ride more trails through an unequaled combination of ride quality, usable power, and ride anywhere range. It's the distillation, application, and amplification of a 40-year obsession with creating the world's best riding mountain bikes. Since its introduction, Levo has set the bar every other e-MTB aims for, and the new Levo raises that bar again.

- Levo's fully integrated Turbo Full Power 2.2 motor, 700Wh battery, and advanced MasterMind Turbo Control Unit deliver category-leading 90 Nm of torque and 565 watts of power for up to five hours of ride time, empowering you to ride farther and faster than ever before.
- The MasterMind Turbo Control Unit is your information hub with customizable display fields, including the exact percentage of battery level, and it features our all-new MicroTune function to adjust power delivery in 10% increments, so you get exactly the support you need to experience precisely the ride you want.
- A dedicated mixed-wheel size design with a 27.5" wheel in the back and 29" up front delivers a nimble ride that carves circles around other full-power e-MTBs. A generous cockpit centers you on the bike, optimizing traction and corner control. The low bottom bracket, slack headtube angle and reduced fork offset keep things stable in the rough.
- Levo offers six distinct geometry settings, allowing you to easily dial-in its performance for any riding style and any terrain. Head tube angle can be adjusted between 63- and 65.5-degrees. Bottom bracket height can be fine-tuned up or down by 7mm.
- Levo's 150mm of rear travel is supple on small bumps, devours square-edged hits without a twitch, eats massive G-outs for breakfast, yet still offers amazing pedal response and delivers your power to the ground with total efficiency.
- The Levo's S-Sizing is based on what matters—rider size and style, not inseam. Six sizes, all with similar headtube lengths and standover, allow you to choose the size that best suits your individual style. Smaller S-Size numbers are going to be nimble and more flickable, while bigger S-Sizes deliver more stability and a roomier ride.

TURBO LEVO PRO	S1	S2	S3	S4	S5	S6
Stack (mm)	605	617	626	635	644	653
Reach (mm)	412	432	452	477	502	532
Headtube Angle (°)	64.5	64.5	64.5	64.5	64.5	64.5
BB Height (mm)	352	350	350	350	350	350
BB Drop (mm)	25	27	27	27	27	27
Trail (mm)	130	130	130	130	130	130
Fork Length (full) (mm)	557	567	567	567	567	567
Fork Rake/Offset (mm)	44	44	44	44	44	44
Front Center (mm)	738	760	784	814	843	878
Chainstay Length (mm)	442	442	442	442	442	442
Wheelbase (mm)	1179	1200	1225	1255	1284	1318
Bike Standover Height (mm)	752	776	783	787	788	790
Seat Tube Length (mm)	380	390	405	425	445	465
Seat Tube Angle (degrees)	78	77.2	76.7	76.2	76.2	76.2

SPECS	Specifications subject to change without notice.
Frame	FACT 11m full carbon, 29" front wheel, 27.5" rear wheel, full internal cable routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel, geo adjust head tube, geo adjust horst pivot
Rear Shock	FOX FLOAT X2 Factory, LSC, LSR, 2-position lever, 55x210mm, Kashima
Fork	FOX FLOAT 38 Factory 29, Grip2 damper, 44mm offset, HSC, LSC, HSR, LSR, 110x15mm, 1.5" tapered steerer, 160mm travel, Kashima
Stem	Deity Copperhead, 35.0mm
Handlebars	Roval Traverse SL Carbon, riser bar, 6-degree upsweep, 8-degree backsweep, 30mm rise, 780mm, 35.0mm
Grips	Deity, Knuckleduster, Black
Front Brake	SRAM Code RSC, 4-piston caliper, hydraulic disc, S1-S3: 200mm, S4-S6: 220mm
Rear Brake	SRAM Code RSC, 4-piston caliper, hydraulic disc, 200mm
Rear Derailleur	Sram X01 Eagle, 12-speed
Shift Levers	SRAM X01 Eagle trigger, 12-speed, single click
Cassette	SRAM XG-1295 Eagle, 10-52t
Chain	SRAX X01 Eagle, 12-speed
Crankset	Praxis Carbon M30, custom offset, 160mm
Chainrings	SRAM X-Sync Eagle, 104 BCD, 34T, steel
Front Wheel	Traverse Carbon 29
Rear Wheel	Traverse Carbon 27.5
Front Tire	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.6"
Rear Tire	Eliminator, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, 27.5x2.6"
Inner Tubes	Standard, Presta Valve
Saddle	Bridge, 155/143mm, Hollow Ti-rails
SeatPost	FOX Transfer, 30.9, S1: 100mm, S2: 125mm, S3: 150mm, S4/S5: 175mm, S6: 200mm
Seat Binder	Alloy, 38.6mm
Motor	Specialized Turbo Full Power System 2.2 Motor
UI/Remote	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, over-the-air updates, ANT+/Bluetooth®, w/Handlebar remote
Battery	Specialized M3-700, Integrated battery, 700Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug
Wiring Harness	Custom Specialized wiring harness
SWAT	SWAT CC steerer tube integrated tool with chain tool and link

PART NO.	DESCRIPTION	COLOR	SIZE
95221-1102	LEVO PRO CARBON NB	Satin Redwood / Smoke / Black	S2
95221-1103			S3
95221-1104			S4
95221-1105			S5
95221-1106			S6

TURBO LEVO EXPERT



GLOSS / SATIN OBSIDIAN / GLOSS TAUPE



SATIN HARVEST GOLD / OBSIDIAN

The all-new Levo delivers the unbelievable power to ride more trails through an unequalled combination of ride quality, usable power, and ride anywhere range. It's the distillation, application, and amplification of a 40-year obsession with creating the world's best riding mountain bikes. Since its introduction, Levo has set the bar every other e-MTB aims for, and the new Levo raises that bar again. It starts with our Turbo Full Power 2.1 motor and MasterMind Turbo Control Unit (TCU), which provide Levo with a smooth and seamless amplification of your efforts—4x your power that lets you choose where to ride, and when you want to do it. Levo also shatters limitations when it comes to range, amplifying your effort for up to five hours of trail time. Now you can ride farther, and explore more, than ever before. And the optimized chassis boasts 150mm of custom-tuned rear suspension and adjustable geometry that delivers a stable and natural ride like no other. Because at the end of the day, it's the ride that matters. Believe it. Here're where the gloves come off—the Levo Expert brings it with SRAM's expansive GX Eagle 12-speed drivetrain, dialed-in FOX Performance Elite suspension, and a high-performing Roval Traverse wheelset.

- Levo's fully integrated Turbo Full Power 2.1 motor, 700Wh battery, and advanced MasterMind Turbo Control Unit deliver category-leading 90 Nm of torque and 565 watts of power for up to five hours of ride time, empowering you to ride farther and faster than ever before.
- The MasterMind Turbo Control Unit is your information hub with customizable display fields, including the exact percentage of battery level, and it features our all-new MicroTune function to adjust power delivery in 10% increments, so you get exactly the support you need to experience precisely the ride you want.
- A dedicated mixed-wheel size design with a 27.5" wheel in the back and 29" up front delivers a nimble ride that carves circles around other full-power e-MTBs. A generous cockpit centers you on the bike, optimizing traction and corner control. The low bottom bracket, slack headtube angle and reduced fork offset keep things stable in the rough.
- Levo offers six distinct geometry settings, allowing you to easily dial-in its performance for any riding style and any terrain. Head tube angle can be adjusted between 63- and 65.5-degrees. Bottom bracket height can be fine-tuned up or down by 7mm.
- Levo's 150mm of rear travel is supple on small bumps, devours square-edged hits without a twitch, eats massive G-outs for breakfast, yet still offers amazing pedal response and delivers your power to the ground with total efficiency.
- The Levo's S-Sizing is based on what matters—rider size and style, not inseam. Six sizes, all with similar headtube lengths and standover, allow you to choose the size that best suits your individual style. Smaller S-Size numbers are going to be nimble and more flickable, while bigger S-Sizes deliver more stability and a roomier ride.

SPECS	Specifications subject to change without notice.
Frame	FACT 11m full carbon, 29" front wheel, 27.5" rear wheel, full internal cable routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel, geo adjust head tube, geo adjust horst pivot
Rear Shock	S2-S6: Fox Float X2 Performance Elite series, 210x55mm, S1: Fox Float DPS Performance Elite series, 210x52.5mm
Fork	Fox 38 Performance Elite, Grip 2 damper, 29", 160mm travel, 44mm offset
Stem	Alloy Trail Stem, 35mm bar bore
Handlebars	Specialized Trail, 7050 alloy, 8-degree backsweep, 6-degree upsweep, 30mm rise, 800mm, 35mm clamp
Grips	Deity Grips
Front Brake	SRAM Code RS, 4-piston caliper, hydraulic disc, S/M: 200mm, L/XL: 220mm
Rear Brake	SRAM Code RS, 4-piston caliper, hydraulic disc, 200mm
Rear Derailleur	SRAM GX Eagle AXS, w/ battery cover
Shift Levers	SRAM GX Eagle AXS Controller
Cassette	SRAM XG-1275, 12-speed, 10-52t
Chain	SRAM GX Eagle, 12-speed
Crankset	Praxis forged M30, custom offset, 160mm
Chainrings	SRAM X-Sync Eagle, 104 BCD, 32T, steel
Front Wheel	Traverse 29
Rear Wheel	Traverse 27.5
Front Tire	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.6"
Rear Tire	Eliminator, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, 27.5x2.6"
Inner Tubes	Standard, Presta Valve
Saddle	Bridge Comp, Hollow Cr-mo rails, 155/143mm
SeatPost	OneUp, Dropper Post-V2, MMX lever, 34.9 (S1:120mm, S2/S3:150mm, S4: 180mm, S5/S6: 210mm)
Seat Binder	Alloy, 38.6mm
Motor	Specialized 2.1 Custom Rx Trail Tuned Motor
UI/Remote	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, over-the-air updates, ANT+/Bluetooth®, w/Handlebar remote
Battery	Specialized M3-700, Integrated battery, 700Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Wiring Harness	Custom Specialized wiring harness
SWAT	SWAT CC steerer tube integrated tool with chain tool and link

PART NO.	DESCRIPTION	COLOR	SIZE
95223-3201	LEVO EXPERT CARBON NB	GLOSS / SATIN OBSIDIAN / GLOSS TAUPE	S1
95223-3202			S2
95223-3203			S3
95223-3204			S4
95223-3205			S5
95223-3206			S6
95223-3301	LEVO EXPERT CARBON NB	SATIN HARVEST GOLD / OBSIDIAN	S1
95223-3302			S2
95223-3303			S3
95223-3304			S4
95223-3305			S5
95223-3306			S6

TURBO LEVO EXPERT



Carbon / Smoke / Black



Maroon / Black

The all-new Levo delivers the unbelievable power to ride more trails through an unequalled combination of ride quality, usable power, and ride anywhere range. It's the distillation, application, and amplification of a 40-year obsession with creating the world's best riding mountain bikes. Since its introduction, Levo has set the bar every other e-MTB aims for, and the new Levo raises that bar again.

- Levo's fully integrated Turbo Full Power 2.2 motor, 700Wh battery, and advanced MasterMind Turbo Control Unit deliver category-leading 90 Nm of torque and 565 watts of power for up to five hours of ride time, empowering you to ride farther and faster than ever before.
- The MasterMind Turbo Control Unit is your information hub with customizable display fields, including the exact percentage of battery level, and it features our all-new MicroTune function to adjust power delivery in 10% increments, so you get exactly the support you need to experience precisely the ride you want.
- A dedicated mixed-wheel size design with a 27.5" wheel in the back and 29" up front delivers a nimble ride that carves circles around other full-power e-MTBs. A generous cockpit centers you on the bike, optimizing traction and corner control. The low bottom bracket, slack headtube angle and reduced fork offset keep things stable in the rough.
- Levo offers six distinct geometry settings, allowing you to easily dial-in its performance for any riding style and any terrain. Head tube angle can be adjusted between 63- and 65.5-degrees. Bottom bracket height can be fine-tuned up or down by 7mm.
- Levo's 150mm of rear travel is supple on small bumps, devours square-edged hits without a twitch, eats massive G-outs for breakfast, yet still offers amazing pedal response and delivers your power to the ground with total efficiency.
- The Levo's S-Sizing is based on what matters—rider size and style, not inseam. Six sizes, all with similar headtube lengths and standover, allow you to choose the size that best suits your individual style. Smaller S-Size numbers are going to be nimble and more flickable, while bigger S-Sizes deliver more stability and a roomier ride.

TURBO LEVO EXPERT	S1	S2	S3	S4	S5	S6
Stack (mm)	605	617	626	635	644	653
Reach (mm)	412	432	452	477	502	532
Headtube Angle (°)	64.5	64.5	64.5	64.5	64.5	64.5
BB Height (mm)	352	350	350	350	350	350
BB Drop (mm)	25	27	27	27	27	27
Trail (mm)	130	130	130	130	130	130
Fork Length (full) (mm)	557	567	567	567	567	567
Fork Rake/Offset (mm)	44	44	44	44	44	44
Front Center (mm)	738	760	784	814	843	878
Chainstay Length (mm)	442	442	442	442	442	442
Wheelbase (mm)	1179	1200	1225	1255	1284	1318
Bike Standover Height (mm)	752	776	783	787	788	790
Seat Tube Length (mm)	380	390	405	425	445	465
Seat Tube Angle (degrees)	78	77.2	76.7	76.2	76.2	76.2

SPECS	Specifications subject to change without notice.
Frame	FACT 11m full carbon, 29" front wheel, 27.5" rear wheel, full internal cable routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel, geo adjust head tube, geo adjust horst pivot
Rear Shock	FOX FLOAT X2 Performance Elite, LSC, LSR, 2-position lever, 55x210mm
Fork	FOX FLOAT 38 Performance Elite 29, Grip2 damper, 44mm offset, HSC, LSC, HSR, LSR, 110x15mm, 1.5" tapered steerer, 160mm travel
Stem	Alloy Trail Stem, 35mm bar bore
Handlebars	Specialized Trail, 7050 alloy, 8-degree backsweep, 6-degree upsweep, 30mm rise, 800mm, 35mm clamp
Grips	Deity, Knuckleduster, Black
Front Brake	SRAM Code RS, 4-piston caliper, hydraulic disc, S/M: 200mm, L/XL: 220mm
Rear Brake	SRAM Code RS, 4-piston caliper, hydraulic disc, 200mm
Rear Derailleur	Sram XO1 Eagle, 12-speed
Shift Levers	SRAM XO1 Eagle trigger, 12-speed, single click
Cassette	SRAM XG-1275, 12-speed, 10-52t
Chain	SRAM GX Eagle, 12-speed
Crankset	Praxis forged M30, custom offset, 160mm
Chainrings	SRAM X-Sync Eagle, 104 BCD, 32T, steel
Front Wheel	Traverse 29
Rear Wheel	Traverse 27.5
Front Tire	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.6"
Rear Tire	Eliminator, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, 27.5x2.6"
Inner Tubes	Standard, Presta Valve
Saddle	Bridge Comp, Hollow Cr-mo rails, 155/143mm
SeatPost	X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SLR LE lever, 34.9, S1: 100mm, S2: 125mm, S3: 150mm, S4/S5: 175mm, S6: 190mm
Seat Binder	Alloy, 38.6mm
Motor	Specialized Turbo Full Power System 2.2 Motor
UI/Remote	Specialized MasterMind TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®, w/Handlebar remote
Battery	Specialized M3-700, Integrated battery, 700Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug
Wiring Harness	Custom Specialized wiring harness
SWAT	SWAT CC steerer tube integrated tool with chain tool and link

PART NO.	DESCRIPTION	COLOR	SIZE
96421-3201	LEVO EXPERT CARBON NB	Carbon / Smoke / Black	S1
96421-3202			S2
96421-3203			S3
96421-3204			S4
96421-3205			S5
96421-3206			S6
96421-3301	LEVO EXPERT CARBON NB	Maroon / Black	S1
96421-3302			S2
96421-3303			S3
96421-3304			S4
96421-3305			S5
96421-3306			S6

TURBO LEVO COMP



Satin Black / Light Silver / Gloss Black



Satin White Sage / Deep Lake

The all-new Levo delivers the unbelievable power to ride more trails through an unequalled combination of ride quality, usable power, and ride anywhere range. It's the distillation, application, and amplification of a 40-year obsession with creating the world's best riding mountain bikes. Since its introduction, Levo has set the bar every other e-MTB aims for, and the new Levo raises that bar again.

- Levo's fully integrated Turbo Full Power 2.1 motor, 700Wh battery, and advanced MasterMind Turbo Control Unit deliver category-leading 90 Nm of torque and 565 watts of power for up to five hours of ride time, empowering you to ride farther and faster than ever before.
- The MasterMind Turbo Control Unit is your information hub with customizable display fields, including the exact percentage of battery level, and it features our all-new MicroTune function to adjust power delivery in 10% increments, so you get exactly the support you need to experience precisely the ride you want.
- A dedicated mixed-wheel size design with a 27.5" wheel in the back and 29" front delivers a nimble ride that carves circles around other full-power e-MTBs. A generous cockpit centers you on the bike, optimizing traction and corner control. The low bottom bracket, slack headtube angle and reduced fork offset keep things stable in the rough.
- Levo offers six distinct geometry settings, allowing you to easily dial-in its performance for any riding style and any terrain. Head tube angle can be adjusted between 63- and 65.5-degrees. Bottom bracket height can be fine-tuned up or down by 7mm.
- Levo's 150mm of rear travel is supple on small bumps, devours square-edged hits without a twitch, eats massive G-outs for breakfast, yet still offers amazing pedal response and delivers your power to the ground with total efficiency.
- The Levo's S-Sizing is based on what matters—rider size and style, not inseam. Six sizes, all with similar headtube lengths and standover, allow you to choose the size that best suits your individual style. Smaller S-Size numbers are going to be nimble and more flickable, while bigger S-Sizes deliver more stability and a roomier ride.

TURBO LEVO COMP	S1	S2	S3	S4	S5	S6
Stack (mm)	605	617	626	635	644	653
Reach (mm)	412	432	452	477	502	532
Headtube Length (mm)	105	105	115	125	135	145
Headtube Angle (°)	64.5	64.5	64.5	64.5	64.5	64.5
BB Height (mm)	352	350	350	350	350	350
BB Drop (mm)	25	27	27	27	27	27
Trail (mm)	130	130	130	130	130	130
Fork Length (full) (mm)	557	567	567	567	567	567
Fork Rake/Offset (mm)	44	44	44	44	44	44
Front Center (mm)	738	760	784	814	843	878
Chainstay Length (mm)	442	442	442	442	442	442
Wheelbase (mm)	1179	1200	1225	1255	1284	1318
Bike Standover Height (mm)	752	776	783	787	788	790
Seat Tube Length (mm)	380	390	405	425	445	465
Seat Tube Angle (°)	78	77.2	76.7	76.2	76.2	76.2
Max Seatpost Insertion (mm)	210	220	240	255	275	295
Min Seatpost Insertion (mm)	80	80	80	80	80	80
Crank Length (mm)	160	160	160	160	160	160
Handlebar Width (mm)	780	780	780	780	780	780
Stem Length (mm)	40	40	40	40	50	50
Saddle Width (mm)	155	155	143	143	143	143
Seatpost Length (mm)	100	125	150	170	170	190

SPECS	Specifications subject to change without notice.
Frame	FACT 11m full carbon, 29" front wheel, 27.5" rear wheel, full internal cable routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel, geo adjust head tube, geo adjust horst pivot
Rear Shock	FOX FLOAT X Performance, LSR, 2-position lever, 55x210mm
Fork	Fox 36 Rhythm, 29", 44mm offset, Grip damper, S1: 150mm, S2-S6: 160mm travel
Stem	Alloy Trail Stem, 35mm bar bore
Handlebars	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 30mm rise, 780mm width
Front Brake	SRAM Code RS, 4-piston caliper, hydraulic disc, S/M: 200mm, L/XL: 220mm
Rear Brake	SRAM Code RS, 4-piston caliper, hydraulic disc, 200mm
Rear Derailleur	SRAM GX Eagle, 12-speed
Shift Levers	SRAM GX Eagle, 12-speed
Cassette	SRAM XG-1275, 12-speed, 10-52t
Chain	SRAM NX Eagle, 12-speed
Crankset	Praxis forged M30, custom offset, 160mm
Chainrings	SRAM X-Sync Eagle, 104 BCD, 32T, steel
Rims	Specialized 29, hookless alloy, 30mm inner width, tubeless ready
Front Hub	Alloy, sealed cartridge bearings, 15x110mm thru-axle, 28h
Rear Hub	Alloy, sealed cartridge bearings, 148mmx12mm thru-axle, 28h
Spokes	DT Swiss Industry
Front Tire	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.6"
Rear Tire	Eliminator, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, 27.5x2.6"
Inner Tubes	Standard, Presta Valve
Saddle	Bridge Comp, Hollow Cr-mo rails, 155/143mm
SeatPost	X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SLR LE lever, 34.9, S1: 100mm, S2: 125mm, S3: 150mm, S4/S5: 175mm, S6: 190mm
Seat Binder	Alloy, 38.6mm
Motor	Specialized 2.1 Custom Rx Trail Tuned Motor
UI/Remote	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, over-the-air updates, ANT+/Bluetooth®, w/Handlebar remote
Battery	Specialized M3-700, Integrated battery, 700Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Wiring Harness	Custom Specialized wiring harness
SWAT	SWAT CC steerer tube integrated tool with chain tool and link

PART NO.	DESCRIPTION	COLOR	SIZE
96422-5101	LEVO COMP CARBON NB	Satin Black / Light Silver / Gloss Black	S1
96422-5102			S2
96422-5103			S3
96422-5104			S4
96422-5105			S5
96422-5106			S6
95223-5301	LEVO COMP CARBON NB	Satin White Sage / Deep Lake	S1
95223-5302			S2
95223-5303			S3
95223-5304			S4
95223-5305			S5
95223-5306			S6

TURBO LEVO COMP



Satin Black / Light Silver / Gloss Black

The all-new Levo delivers the unbelievable power to ride more trails through an unequaled combination of ride quality, usable power, and ride anywhere range. It's the distillation, application, and amplification of a 40-year obsession with creating the world's best riding mountain bikes. Since its introduction, Levo has set the bar every other e-MTB aims for, and the new Levo raises that bar again.

- Levo's fully integrated Turbo Full Power 2.2 motor, 700Wh battery, and advanced MasterMind Turbo Control Unit deliver category-leading 90 Nm of torque and 565 watts of power for up to five hours of ride time, empowering you to ride farther and faster than ever before.
- The MasterMind Turbo Control Unit is your information hub with customizable display fields, including the exact percentage of battery level, and it features our all-new MicroTune function to adjust power delivery in 10% increments, so you get exactly the support you need to experience precisely the ride you want.
- A dedicated mixed-wheel size design with a 27.5" wheel in the back and 29" up front delivers a nimble ride that carves circles around other full-power e-MTBs. A generous cockpit centers you on the bike, optimizing traction and corner control. The low bottom bracket, slack headtube angle and reduced fork offset keep things stable in the rough.
- Levo offers six distinct geometry settings, allowing you to easily dial-in its performance for any riding style and any terrain. Head tube angle can be adjusted between 63- and 65.5-degrees. Bottom bracket height can be fine-tuned up or down by 7mm.
- Levo's 150mm of rear travel is supple on small bumps, devours square-edged hits without a twitch, eats massive G-outs for breakfast, yet still offers amazing pedal response and delivers your power to the ground with total efficiency.
- The Levo's S-Sizing is based on what matters—rider size and style, not inseam. Six sizes, all with similar headtube lengths and standover, allow you to choose the size that best suits your individual style. Smaller S-Size numbers are going to be nimble and more flickable, while bigger S-Sizes deliver more stability and a roomier ride.

TURBO LEVO COMP	S1	S2	S3	S4	S5	S6
Stack (mm)	605	617	626	635	644	653
Reach (mm)	412	432	452	477	502	532
Headtube Angle (°)	64.5	64.5	64.5	64.5	64.5	64.5
BB Height (mm)	352	350	350	350	350	350
BB Drop (mm)	25	27	27	27	27	27
Trail (mm)	130	130	130	130	130	130
Fork Length (full) (mm)	557	567	567	567	567	567
Fork Rake/Offset (mm)	44	44	44	44	44	44
Front Center (mm)	738	760	784	814	843	878
Chainstay Length (mm)	442	442	442	442	442	442
Wheelbase (mm)	1179	1200	1225	1255	1284	1318
Bike Standover Height (mm)	752	776	783	787	788	790
Seat Tube Length (mm)	380	390	405	425	445	465
Seat Tube Angle (degrees)	78	77.2	76.7	76.2	76.2	76.2

SPECS	Specifications subject to change without notice.
Frame	FACT 11m full carbon, 29" front wheel, 27.5" rear wheel, full internal cable routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel, geo adjust head tube, geo adjust horst pivot
Rear Shock	FOX FLOAT X Performance, LSR, 2-position lever, 55x210mm
Fork	FOX FLOAT 36 RHYTHM 29, GRIP damper, 44mm offset, 2-position sweep adjust, 15x110mm, 1.5" tapered steerer, 160mm travel
Stem	Alloy Trail Stem, 35mm bar bore
Handlebars	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 30mm rise, 780mm width
Front Brake	SRAM Code RS, 4-piston caliper, hydraulic disc, S1-S3: 200mm, S4-S6: 220mm
Rear Brake	SRAM Code RS, 4-piston caliper, hydraulic disc, 200mm
Rear Derailleur	SRAM GX Eagle, 12-speed
Shift Levers	SRAM GX Eagle, 12-speed
Cassette	SRAM XG-1275, 12-speed, 10-52t
Chain	SRAM NX Eagle, 12-speed
Crankset	Praxis forged M30, custom offset, 160mm
Chainrings	SRAM X-Sync Eagle, 104 BCD, 32T, steel
Rims	Specialized 29, hookless alloy, 30mm inner width, tubeless ready
Front Hub	Alloy, sealed cartridge bearings, 15x110mm thru-axle, 28h
Rear Hub	Alloy, sealed cartridge bearings, 148mmx12mm thru-axle, 28h
Spokes	DT Swiss Industry
Front Tire	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.6"
Rear Tire	Eliminator, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, 27.5x2.6"
Inner Tubes	Standard, Presta Valve
Saddle	Bridge Comp, Hollow Cr-mo rails, 155/143mm
SeatPost	X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SLR LE lever, 34.9, S1: 100mm, S2: 125mm, S3: 150mm, S4/S5: 175mm, S6: 190mm
Seat Binder	Alloy, 38.6mm
Motor	Specialized Turbo Full Power System 2.2 Motor
UI/Remote	Specialized MasterMind TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®, w/Handlebar remote
Battery	Specialized M3-700, Integrated battery, 700Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug
Wiring Harness	Custom Specialized wiring harness
SWAT	SWAT CC steerer tube integrated tool with chain tool and link

PART NO.	DESCRIPTION	COLOR	SIZE
96422-5101	LEVO COMP CARBON NB	Satin Black / Light Silver / Gloss Black	S1
96422-5102			S2
96422-5103			S3
96422-5104			S4
96422-5105			S5
96422-5106			S6

TURBO LEVO CARBON



SMOKE / BLACK

The all-new Levo delivers the unbelievable power to ride more trails through an unequalled combination of ride quality, usable power, and ride anywhere range. It's the distillation, application, and amplification of a 40-year obsession with creating the world's best riding mountain bikes. Since its introduction, Levo has set the bar every other e-MTB aims for, and the new Levo raises that bar again.

- Levo's fully integrated Turbo Full Power 2.2 motor, 700Wh battery, and Turbo Connect Unit deliver category-leading 90 Nm of torque and 565 watts of power for up to five hours of ride time, empowering you to ride farther and faster than ever before.
- The Levo's Turbo Connect Unit (or "TCU") is more than an "On-Off" button—it's the brains of the bike. The TCU shows your battery level and power-assist mode. It also communicates, via ANT+/Bluetooth®, with our optional handlebar display to display even more information about your day's ride.
- A dedicated mixed-wheel size design with a 27.5" wheel in the back and 29" up front delivers a nimble ride that carves circles around other full-power e-MTBs. A generous cockpit centers you on the bike, optimizing traction and corner control. The low bottom bracket, slack headtube angle and reduced fork offset keep things stable in the rough.
- Levo offers two distinct geometry settings, allowing you to easily dial-in its performance for any riding style and any terrain. Bottom bracket height can be fine-tuned up or down by 7mm.
- Levo's 150mm of rear travel is supple on small bumps, devours square-edged hits without a twitch, eats massive G-outs for breakfast, yet still offers amazing pedal response and delivers your power to the ground with total efficiency.
- The Levo's S-Sizing is based on what matters—rider size and style, not inseam. Six sizes, all with similar headtube lengths and standover, allow you to choose the size that best suits your individual style. Smaller S-Size numbers are going to be nimble and more flickable, while bigger S-Sizes deliver more stability and a roomier ride.

TURBO LEVO	S1	S2	S3	S4	S5	S6
Stack (mm)	605	617	626	635	644	653
Reach (mm)	412	432	452	477	502	532
Headtube Length (mm)	105	105	115	125	135	145
Headtube Angle (°)	64.5	64.5	64.5	64.5	64.5	64.5
BB Height (mm)	352	350	350	350	350	350
BB Drop (mm)	25	27	27	27	27	27
Trail (mm)	130	130	130	130	130	130
Fork Length (full) (mm)	557	567	567	567	567	567
Fork Rake/Offset (mm)	44	44	44	44	44	44
Front Center (mm)	738	760	784	814	843	878
Chainstay Length (mm)	442	442	442	442	442	442
Wheelbase (mm)	1179	1200	1225	1255	1284	1318
Bike Standover Height (mm)	752	776	783	787	788	790
Seat Tube Length (mm)	380	390	405	425	445	465
Seat Tube Angle (°)	78	77.2	76.7	76.2	76.2	76.2
Max Seatpost Insertion (mm)	210	220	240	255	275	295
Min Seatpost Insertion (mm)	80	80	80	80	80	80
Crank Length (mm)	160	160	160	160	160	160
Stem Length (mm)	40	40	40	40	50	50

SPECS	Specifications subject to change without notice.
Frame	FACT 11m full carbon, 29" front wheel, 27.5" rear wheel, full internal cable routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel, geo adjust head tube, geo adjust horst pivot
Rear Shock	RockShox Deluxe Select R, rebound adjust, S1: 52.5x210mm, S2-S6: 55x210mm
Fork	SRAM 35 Silver 29, Turnkey damper, S1: 150mm travel, S2-S6: 160mm travel
Stem	Alloy Trail Stem, 35mm bar bore
Handlebars	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 30mm rise, 780mm width
Front Brake	SRAM Guide RE, S1-S3: 200mm, S4-S6: 220mm
Rear Brake	SRAM Guide RE, 200mm
Rear Derailleur	SRAM SX Eagle, 12-speed
Shift Levers	SRAM SL SX Eagle, 12-speed
Cassette	SRAM NX Eagle PG-1230, 12-speed, 11-50t
Chain	SRAM NX Eagle, 12-speed
Crankset	Praxis forged M30, custom offset, 160mm
Chainrings	SRAM X-Sync Eagle, 104 BCD, 34T, steel
Rims	Specialized 29, hookless alloy, 30mm inner width, tubeless ready
Front Hub	Specialized alloy front hub disc, sealed cartridge bearings, 6-bolt, 15x110mm thru-axle, 32h
Rear Hub	Alloy, sealed cartridge bearings, 12x148mm thru-axle, 32h
Spokes	DT Swiss Industry
Front Tire	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.6"
Rear Tire	Eliminator, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, 27.5x2.6"
Inner Tubes	Standard, Presta Valve
Saddle	Body Geometry Bridge Saddle, steel rails
SeatPost	TranzX dropper, 34.9mm, S1: 100mm, S2: 125mm, S3: 150mm, S4-S5: 170mm, S6- 200mm
Seat Binder	Alloy, 38.6mm
Motor	Specialized 2.2, Custom Rx Trail Tuned Motor
UI/Remote	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®, w/Handlebar remote
Battery	Specialized M3-700A, Integrated battery, 700Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Wiring Harness	Custom Specialized wiring harness

PART NO.	DESCRIPTION	COLOR	SIZE
95223-7801	LEVO CARBON NB	SMOKE / BLACK	S1
95223-7802			S2
95223-7803			S3
95223-7804			S4
95223-7805			S5
95223-7806			S6

TURBO LEVO COMP ALLOY



Black / Dove Grey / Black



Sage Green / Cool Grey / Black



Satin Midnight Shadow / Harvest Gold Metallic

The all-new Levo delivers the unbelievable power to ride more trails through an unequalled combination of ride quality, usable power, and ride anywhere range. It's the distillation, application, and amplification of a 40-year obsession with creating the world's best riding mountain bikes. Since its introduction, Levo has set the bar every other e-MTB aims for, and the new Levo raises that bar again.

- Levo's fully integrated Turbo Full Power 2.1 motor, 700Wh battery, and Turbo Connect Unit deliver category-leading 90 Nm of torque and 565 watts of power for up to five hours of ride time, empowering you to ride farther and faster than ever before.
- The Levo's Turbo Connect Unit (or "TCU") is more than an "On-Off" button—it's the brains of the bike. The TCU shows your battery level and power-assist mode. It also communicates, via ANT+/Bluetooth®, with our optional handlebar display to display even more information about your day's ride.
- A dedicated mixed-wheel size design with a 27.5" wheel in the back and 29" up front delivers a nimble ride that carves circles around other full-power e-MTBs. A generous cockpit centers you on the bike, optimizing traction and corner control. The low bottom bracket, slack headtube angle and reduced fork offset keep things stable in the rough.
- Levo offers six distinct geometry settings, allowing you to easily dial-in its performance for any riding style and any terrain. Head tube angle can be adjusted between 63- and 65.5-degrees. Bottom bracket height can be fine-tuned up or down by 7mm.
- Levo's 150mm of rear travel is supple on small bumps, devours square-edged hits without a twitch, eats massive G-outs for breakfast, yet still offers amazing pedal response and delivers your power to the ground with total efficiency.
- The Levo's S-Sizing is based on what matters—rider size and style, not inseam. Six sizes, all with similar headtube lengths and standover, allow you to choose the size that best suits your individual style. Smaller S-Size numbers are going to be nimble and more flickable, while bigger S-Sizes deliver more stability and a roomier ride.

TURBO LEVO COMP ALLOY	S1	S2	S3	S4	S5	S6
Stack (mm)	605	617	626	635	644	653
Reach (mm)	412	432	452	477	502	532
Headtube Length (mm)	105	105	115	125	135	145
Headtube Angle (°)	64.5	64.5	64.5	64.5	64.5	64.5
BB Height (mm)	352	350	350	350	350	350
BB Drop (mm)	25	27	27	27	27	27
Trail (mm)	130	130	130	130	130	130
Fork Length (full) (mm)	557	567	567	567	567	567
Fork Rake/Offset (mm)	44	44	44	44	44	44
Front Center (mm)	738	760	784	814	843	878
Chainstay Length (mm)	442	442	442	442	442	442
Wheelbase (mm)	1179	1200	1225	1255	1284	1318
Bike Standover Height (mm)	752	776	783	787	788	790
Seat Tube Length (mm)	380	390	405	425	445	465
Seat Tube Angle (°)	78	77.2	76.7	76.2	76.2	76.2
Max Seatpost Insertion (mm)	210	220	240	255	275	295
Min Seatpost Insertion (mm)	80	80	80	80	80	80
Crank Length (mm)	160	160	160	160	160	160
Handlebar Width (mm)	780	780	780	780	780	780
Stem Length (mm)	40	40	40	40	50	50
Saddle Width (mm)	155	155	143	143	143	143
Seatpost Length (mm)	100	125	150	170	170	190

SPECS	Specifications subject to change without notice.
Frame	Specialized M5 premium alloy, headset adjust, BB height adjust, S-Sizing, internal cable routing, 150mm travel, 148mm spacing
Rear Shock	FOX FLOAT X Performance, LSR, 2-position lever, 55x210mm
Fork	Fox Rhythm 36, S1: 150mm travel, S2-S6: 160mm travel
Stem	Alloy Trail Stem, 35mm bar bore
Handlebars	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 30mm rise, 780mm width
Front Brake	SRAM Code R, 4-piston caliper, hydraulic disc, S1-S3: 200mm, S4-S6: 220mm
Rear Brake	SRAM Code R, 4-piston caliper, hydraulic disc, 200mm
Rear Derailleur	SRAM GX Eagle, 12-speed
Shift Levers	SRAM GX Eagle, 12-speed
Cassette	SRAM XG-1275, 12-speed, 10-52t
Chain	SRAM NX Eagle, 12-speed
Crankset	Praxis forged M30, custom offset, 160mm
Chainrings	SRAM X-Sync Eagle, 104 BCD, 34t, steel
Rims	Specialized 29, hookless alloy, 30mm inner width, tubeless ready
Front Hub	Alloy, sealed cartridge bearings, 15x110mm thru-axle, 28h
Rear Hub	Alloy, sealed cartridge bearings, 148mmx12mm thru-axle, 28h
Spokes	DT Swiss Industry
Front Tire	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.6"
Rear Tire	Eliminator, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, 27.5x2.6"
Inner Tubes	Standard, Presta Valve
Saddle	Bridge Comp, Hollow Cr-mo rails, 155/143mm
SeatPost	X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SLR LE lever, 34.9, S1: 100mm, S2: 125mm, S3: 150mm, S4/S5: 175mm, S6: 190mm
Seat Binder	Alloy, 38.6mm
Motor	Specialized 2.1 Custom Rx Trail Tuned Motor
UI/Remote	Mastermind TCU2
Battery	Specialized M3-700, Integrated battery, 700Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Wiring Harness	Custom Specialized wiring harness

PART NO.	DESCRIPTION	COLOR	SIZE
95222-5401	LEVO COMP ALLOY NB	Black / Dove Grey / Black	S1
95222-5402			S2
95222-5403			S3
95222-5404			S4
95222-5405			S5
95222-5406			S6
95222-5701	LEVO COMP ALLOY NB	Sage Green / Cool Grey / Black	S1
95222-5702			S2
95222-5703			S3
95222-5704			S4
95222-5705			S5
95222-5706			S6
95223-5101	LEVO COMP ALLOY NB	Satin Midnight Shadow / Harvest Gold Metallic	S1
95223-5102			S2
95223-5103			S3
95223-5104			S4
95223-5105			S5
95223-5106			S6

TURBO LEVO COMP ALLOY



Black / Dove Grey / Black



Cobalt / Light Silver



Flo Red / Black



Sage Green / Cool Grey / Black

The all-new Levo delivers the unbelievable power to ride more trails through an unequalled combination of ride quality, usable power, and ride anywhere range. It's the distillation, application, and amplification of a 40-year obsession with creating the world's best riding mountain bikes. Since its introduction, Levo has set the bar every other e-MTB aims for, and the new Levo raises that bar again.

- Levo's fully integrated Turbo Full Power 2.2 motor, 700Wh battery, and Turbo Connect Unit deliver category-leading 90 Nm of torque and 565 watts of power for up to five hours of ride time, empowering you to ride farther and faster than ever before.
- The Levo's Turbo Connect Unit (or "TCU") is more than an "On-Off" button—it's the brains of the bike. The TCU shows your battery level and power-assist mode. It also communicates, via ANT+/Bluetooth®, with our optional handlebar display to display even more information about your day's ride.
- A dedicated mixed-wheel size design with a 27.5" wheel in the back and 29" up front delivers a nimble ride that carves circles around other full-power e-MTBs. A generous cockpit centers you on the bike, optimizing traction and corner control. The low bottom bracket, slack headtube angle and reduced fork offset keep things stable in the rough.
- Levo offers six distinct geometry settings, allowing you to easily dial-in its performance for any riding style and any terrain. Head tube angle can be adjusted between 63- and 65.5-degrees. Bottom bracket height can be fine-tuned up or down by 7mm.
- Levo's 150mm of rear travel is supple on small bumps, devours square-edged hits without a twitch, eats massive G-outs for breakfast, yet still offers amazing pedal response and delivers your power to the ground with total efficiency.
- The Levo's S-Sizing is based on what matters—rider size and style, not inseam. Six sizes, all with similar headtube lengths and standover, allow you to choose the size that best suits your individual style. Smaller S-Size numbers are going to be nimble and more flickable, while bigger S-Sizes deliver more stability and a roomier ride.

SPECS	Specifications subject to change without notice.
Frame	FSR Alloy Frame, 29" front wheel, 27.5" rear wheel
Rear Shock	FOX Float DPS
Fork	FOX Rhythm 36
Stem	Alloy Trail Stem, 35mm bar bore
Handlebars	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 30mm rise, 780mm width
Grips	Specialized Trail Grips
Front Brake	SRAM Code R, 4-piston caliper, hydraulic disc, 200mm
Rear Brake	SRAM Code R, 4-piston caliper, hydraulic disc, 200mm
Rear Derailleur	SRAM GX Eagle, 12-speed
Shift Levers	SRAM GX Eagle, 12-speed
Cassette	SRAM XG-1275, 12-speed, 10-52t
Chain	SRAM NX Eagle, 12-speed
Crankset	Praxis forged M30, custom offset, 160mm
Chainrings	SRAM Eagle, 104 BCD, 34T, steel
Rims	Specialized 29, hookless alloy, 30mm inner width, tubeless ready
Front Hub	Alloy, sealed cartridge bearings, 15x110mm thru-axle, 28h
Spokes	DT Swiss Industry
Inner Tubes	Standard, Presta Valve
Saddle	Bridge Comp, Hollow Cr-mo rails, 155/143mm
SeatPost	X-Fusion Manic
Seat Binder	Alloy, 38.6
Motor	Specialized Turbo Full Power System 2.2 Motor
UI/Remote	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®, w/Handlebar remote
Battery	Specialized M3-700, Integrated battery, 700Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug

TURBO LEVO COMP ALLOY	S1	S2	S3	S4	S5	S6
Stack (mm)	605	617	626	635	644	653
Reach (mm)	412	432	452	477	502	532
Headtube Length (mm)	105	105	115	125	135	145
Headtube Angle (°)	64.5	64.5	64.5	64.5	64.5	64.5
BB Height (mm)	352	350	350	350	350	350
BB Drop (mm)	25	27	27	27	27	27
Trail (mm)	130	130	130	130	130	130
Fork Length (full) (mm)	557	567	567	567	567	567
Fork Rake/Offset (mm)	44	44	44	44	44	44
Front Center (mm)	738	760	784	814	843	878
Chainstay Length (mm)	442	442	442	442	442	442
Wheelbase (mm)	1179	1200	1225	1255	1284	1318
Bike Standover Height (mm)	752	776	783	787	788	790
Seat Tube Length (mm)	380	390	405	425	445	465
Seat Tube Angle (°)	78	77.2	76.7	76.2	76.2	76.2
Max Seatpost Insertion (mm)	210	220	240	255	275	295
Min Seatpost Insertion (mm)	80	80	80	80	80	80
Crank Length (mm)	160	160	160	160	160	160
Handlebar Width (mm)	780	780	780	780	780	780
Stem Length (mm)	40	40	50	50	50	50
Saddle Width (mm)	155	155	143	143	143	143
Seatpost Length (mm)	100	125	150	170	170	190

PART NO.	DESCRIPTION	COLOR	SIZE
95222-5401	LEVO COMP ALLOY NB	Black / Dove Grey / Black	S1
95222-5402			S2
95222-5403			S3
95222-5404			S4
95222-5405			S5
95222-5406			S6
95222-5501	LEVO COMP ALLOY NB	Cobalt / Light Silver	S1
95222-5502			S2
95222-5503			S3
95222-5504			S4
95222-5505			S5
95222-5506			S6
95222-5601	LEVO COMP ALLOY NB	Flo Red / Black	S1
95222-5602			S2
95222-5603			S3
95222-5604			S4
95222-5605			S5
95222-5606			S6
95222-5701	LEVO COMP ALLOY NB	Sage Green / Cool Grey / Blk	S1
95222-5702			S2
95222-5703			S3
95222-5704			S4
95222-5705			S5
95222-5706			S6

TURBO LEVO ALLOY



Black / Light Silver / Black



Gloss Limestone / Black



Satin Dark Moss Green / Harvest Gold

The all-new Levo delivers the unbelievable power to ride more trails through an unequalled combination of ride quality, usable power, and ride anywhere range. It's the distillation, application, and amplification of a 40-year obsession with creating the world's best riding mountain bikes. Since its introduction, Levo has set the bar every other e-MTB aims for, and the new Levo raises that bar again.

- Levo's fully integrated Turbo Full Power 2.1 motor, 500Wh battery, and Turbo Connect Unit deliver category-leading 90 Nm of torque and 565 watts of power for up to five hours of ride time, empowering you to ride farther and faster than ever before.
- The Levo's Turbo Connect Unit (or "TCU") is more than an "On-Off" button—it's the brains of the bike. The TCU shows your battery level and power-assist mode. It also communicates, via ANT+/Bluetooth®, with our optional handlebar display to display even more information about your day's ride.
- A dedicated mixed-wheel size design with a 27.5" wheel in the back and 29" up front delivers a nimble ride that carves circles around other full-power e-MTBs. A generous cockpit centers you on the bike, optimizing traction and corner control. The low bottom bracket, slack headtube angle and reduced fork offset keep things stable in the rough.
- Levo offers two distinct geometry settings, allowing you to easily dial-in its performance for any riding style and any terrain. Bottom bracket height can be fine-tuned up or down by 7mm.
- Levo's 150mm of rear travel is supple on small bumps, devours square-edged hits without a twitch, eats massive G-outs for breakfast, yet still offers amazing pedal response and delivers your power to the ground with total efficiency.
- The Levo's S-Sizing is based on what matters—rider size and style, not inseam. Six sizes, all with similar headtube lengths and standover, allow you to choose the size that best suits your individual style. Smaller S-Size numbers are going to be nimble and more flickable, while bigger S-Sizes deliver more stability and a roomier ride.

TURBO LEVO ALLOY	S1	S2	S3	S4	S5	S6
Stack (mm)	605	617	626	635	644	653
Reach (mm)	412	432	452	477	502	532
Headtube Length (mm)	105	105	115	125	135	145
Headtube Angle (°)	64.5	64.5	64.5	64.5	64.5	64.5
BB Height (mm)	352	350	350	350	350	350
BB Drop (mm)	25	27	27	27	27	27
Trail (mm)	130	130	130	130	130	130
Fork Length (full) (mm)	557	567	567	567	567	567
Fork Rake/Offset (mm)	44	44	44	44	44	44
Front Center (mm)	738	760	784	814	843	878
Chainstay Length (mm)	442	442	442	442	442	442
Wheelbase (mm)	1179	1200	1225	1255	1284	1318
Bike Standover Height (mm)	752	776	783	787	788	790
Seat Tube Length (mm)	380	390	405	425	445	465
Seat Tube Angle (°)	78	77.2	76.7	76.2	76.2	76.2
Max Seatpost Insertion (mm)	210	220	240	255	275	295
Min Seatpost Insertion (mm)	80	80	80	80	80	80
Crank Length (mm)	160	160	160	160	160	160
Handlebar Width (mm)	780	780	780	780	780	780
Stem Length (mm)	40	40	40	40	50	50
Saddle Width (mm)	155	155	143	143	143	143
Seatpost Length (mm)	100	125	150	170	170	200

SPECS	Specifications subject to change without notice.
Frame	Specialized M5 premium alloy, 150mm travel, 29" wheel front, 27.5" rear, BB height adjust, S-Sizing, internal cable routing, 148mm spacing
Rear Shock	RockShox Deluxe Select R, rebound adjust, S1: 52.5x210mm, S2-S6: 55x210mm
Fork	RockShox 35 Silver, 35mm stanchion, Turnkey damper, S1: 150mm travel, S2-S6: 160mm travel
Stem	Alloy Trail Stem, 35mm bar bore
Handlebars	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 30mm rise, 780mm width
Front Brake	SRAM Guide RE, S1-S3: 200mm, S4-S6: 220mm
Rear Brake	SRAM Guide RE, 200mm
Rear Derailleur	SRAM SX Eagle, 12-speed
Shift Levers	SRAM SX Eagle, 12-speed
Cassette	SRAM NX Eagle PG-1230, 12-speed, 11-50t
Chain	SRAM NX Eagle, 12-speed
Crankset	Praxis forged M30, custom offset, 160mm
Chainrings	SRAM X-Sync Eagle, 104 BCD, 34t, steel
Rims	Specialized 29, hookless alloy, 30mm inner width, tubeless ready
Front Hub	Specialized alloy front hub disc, sealed cartridge bearings, 6-bolt, 15x110mm thru-axle, 32h
Rear Hub	Alloy, sealed cartridge bearings, 12x148mm thru-axle, 32h
Spokes	DT Swiss Industry
Front Tire	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.6"
Rear Tire	Eliminator, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, 27.5x2.6"
Inner Tubes	Standard, Presta Valve
Saddle	Body Geometry Bridge Saddle, steel rails
SeatPost	TranzX dropper, 34.9mm, S1: 100mm, S2: 125mm, S3: 150mm, S4-S5: 170mm, S6- 200mm
Seat Binder	Alloy, 38.6mm
Motor	Specialized 2.1 Custom Rx Trail Tuned Motor
UI/Remote	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®, w/Handlebar remote
Battery	Specialized M3-700, Integrated battery 700WH, SBC-B22
Charger	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Wiring Harness	Custom Specialized wiring harness

PART NO.	DESCRIPTION	COLOR	SIZE
95222-7301	LEVO ALLOY NB	Black / Light Silver / Black	S1
95222-7302			S2
95222-7303			S3
95222-7304			S4
95222-7305			S5
95222-7306			S6
95223-7301	LEVO ALLOY NB	Gloss Limestone / Black	S1
95223-7302			S2
95223-7303			S3
95223-7304			S4
95223-7305			S5
95223-7306			S6
95223-7201	LEVO ALLOY NB	Satin Dark Moss Green /Harvest Gold	S1
95223-7202			S2
95223-7203			S3
95223-7204			S4
95223-7205			S5
95223-7206			S6

TURBO LEVO ALLOY



Black / Light Silver / Black



Ice Blue / Black



Oasis / Black

The all-new Levo delivers the unbelievable power to ride more trails through an unequaled combination of ride quality, usable power, and ride anywhere range. It's the distillation, application, and amplification of a 40-year obsession with creating the world's best riding mountain bikes. Since its introduction, Levo has set the bar every other e-MTB aims for, and the new Levo raises that bar again.

- Levo's fully integrated Turbo Full Power 2.2 motor, 500Wh battery, and Turbo Connect Unit deliver category-leading 90 Nm of torque and 565 watts of power for up to five hours of ride time, empowering you to ride farther and faster than ever before.
- The Levo's Turbo Connect Unit (or "TCU") is more than an "On-Off" button—it's the brains of the bike. The TCU shows your battery level and power-assist mode. It also communicates, via ANT+/Bluetooth®, with our optional handlebar display to display even more information about your day's ride.
- A dedicated mixed-wheel size design with a 27.5" wheel in the back and 29" up front delivers a nimble ride that carves circles around other full-power e-MTBs. A generous cockpit centers you on the bike, optimizing traction and corner control. The low bottom bracket, slack headtube angle and reduced fork offset keep things stable in the rough.
- Levo offers two distinct geometry settings, allowing you to easily dial-in its performance for any riding style and any terrain. Bottom bracket height can be fine-tuned up or down by 7mm.
- Levo's 150mm of rear travel is supple on small bumps, devours square-edged hits without a twitch, eats massive G-outs for breakfast, yet still offers amazing pedal response and delivers your power to the ground with total efficiency.
- The Levo's S-Sizing is based on what matters—rider size and style, not inseam. Six sizes, all with similar headtube lengths and standover, allow you to choose the size that best suits your individual style. Smaller S-Size numbers are going to be nimble and more flickable, while bigger S-Sizes deliver more stability and a roomier ride.

SPECS	Specifications subject to change without notice.
Frame	FSR Alloy Frame, 29" front wheel, 27.5" rear wheel
Rear Shock	RockShox Deluxe
Fork	RockShox 35 Silver
Stem	Alloy Trail Stem, 35mm bar bore
Handlebars	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 30mm rise, 780mm width
Grips	Specialized Trail Grips
Front Brake	SRAM G2
Rear Brake	SRAM G2
Rear Derailleur	SRAM SX Eagle, 12-speed
Shift Levers	SRAM SX Eagle, 12-speed
Cassette	SRAM NX Eagle PG-1230, 12-speed, 11-50t
Chain	SRAM NX Eagle, 12-speed
Crankset	Praxis forged M30, custom offset, 160mm
Chainrings	SRAM Eagle, 104 BCD, 34T, steel
Rims	Specialized 29, hookless alloy, 30mm inner width, tubeless ready
Front Hub	Alloy, sealed cartridge bearings, 15x110mm thru-axle, 28h
Rear Hub	Alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
Spokes	DT Swiss Industry
Inner Tubes	Standard, Presta Valve
Saddle	Body Geometry Bridge Saddle, steel rails
SeatPost	TranzX dropper, 34.9mm
Seat Binder	Alloy, 38.6
Motor	Specialized Turbo Full Power System 2.2 Motor
UI/Remote	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®, w/Handlebar remote
Battery	Specialized M3-500, Integrated battery, 500Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug

TURBO LEVO ALLOY	S1	S2	S3	S4	S5	S6
Stack (mm)	605	617	626	635	644	653
Reach (mm)	412	432	452	477	502	532
Headtube Length (mm)	105	105	115	125	135	145
Headtube Angle (°)	64.5	64.5	64.5	64.5	64.5	64.5
BB Height (mm)	352	350	350	350	350	350
BB Drop (mm)	25	27	27	27	27	27
Trail (mm)	130	130	130	130	130	130
Fork Length (full) (mm)	557	567	567	567	567	567
Fork Rake/Offset (mm)	44	44	44	44	44	44
Front Center (mm)	738	760	784	814	843	878
Chainstay Length (mm)	442	442	442	442	442	442
Wheelbase (mm)	1179	1200	1225	1255	1284	1318
Bike Standover Height (mm)	752	776	783	787	788	790
Seat Tube Length (mm)	380	390	405	425	445	465
Seat Tube Angle (°)	78	77.2	76.7	76.2	76.2	76.2
Max Seatpost Insertion (mm)	210	220	240	255	275	295
Min Seatpost Insertion (mm)	80	80	80	80	80	80
Crank Length (mm)	160	160	160	160	160	160
Handlebar Width (mm)	780	780	780	780	780	780
Stem Length (mm)	40	40	50	50	50	50
Saddle Width (mm)	155	155	143	143	143	143
Seatpost Length (mm)	100	125	150	170	170	200

PART NO.	DESCRIPTION	COLOR	SIZE
95222-7301	LEVO ALLOY NB	Black / Light Silver / Black	S1
95222-7302			S2
95222-7303			S3
95222-7304			S4
95222-7305			S5
95222-7306			S6
95222-7401	LEVO ALLOY NB	Ice Blue / Black	S1
95222-7402			S2
95222-7403			S3
95222-7404			S4
95222-7405			S5
95222-7406			S6
95222-7501	LEVO ALLOY NB	Oasis / Black	S1
95222-7502			S2
95222-7503			S3
95222-7504			S4
95222-7505			S5
95222-7506			S6

LEVO SL

S-WORKS TURBO LEVO SL



Carbon / Bronze Foil / Gloss Carbon

Turbo Levo SL is a new, lightweight breed of eMTB that harnesses the quick and lively ride of our Stumpjumper...and adds just enough power to introduce a whole new dimension of kick ass. The top-shelf S-Works Turbo Levo SL features a carbon chassis mated to FOX Factory-level suspension and SRAM's premier Eagle XX1 AXS drivetrain.

- The Turbo Levo SL looks like a Stumpjumper and, out on the trail, feels like one too. That's no mistake. We aimed to build a Stumpjumper with a bit more boost to it and that's exactly what you get—a Sidearm chassis with just the right amount of front-to-rear stiffness and 150mm of smooth, custom-tuned FOX rear suspension. To top it all off, we constructed this Turbo Levo SL chassis entirely from our light-yet-strong FACT 11m carbon.
- The lightweight SL 1.1 motor doubles your effort with as much as 240 watts of silent and powerful assistance to your pedals. The motor's responsive torque curve delivers power perfectly in-tune with your normal riding cadence and leaves no resistance when you're riding without power assistance.
- Worried about running out of power? No problem. Turbo Levo SL eats up big miles and long days. And if you're looking for even more miles, our included range extender boosts your range by another 50 percent. On top of all that, our Mission Control App can handle battery management automatically, ensuring your battery will last as long as you need it to.
- Assist up to 20 mph / 32 km/h

S-WORKS TURBO LEVO SL	S	M	L	XL
Stack (mm)	606	606	633	647
Reach (mm)	415	435	455	480
Head-Tube Length (mm)	95	95	125	140
Head-Tube Angle (°)	66	66	66	66
B-B Height (mm)	348	348	348	348
B-B Drop (mm)	27	27	27	27
Trail (mm)	111	111	111	111
Fork Length (full) (mm)	560	560	560	560
Fork Rake/Offset (mm)	51	51	51	51
Front-Center (mm)	729	749	781	812
Chain-Stay Length (mm)	437	437	437	437
Wheelbase (mm)	1165	1185	1217	1248
Top-Tube Length (horizontal) (mm)	574	597	629	663
Bike Stand-Over Height (mm)	787	790	807	814
Seat-Tube Length (mm)	390	410	455	505
Seat-Tube Angle (°)	75.3	75	74.6	74.2
Crank Length (mm)	165	165	170	170
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	35	35	50	50
Saddle Width (mm)	155	143	143	143
Seatpost Length (mm)	125	150	170	170

SPECS	Specifications subject to change without notice.
FRAME	FACT 11m full carbon, 29 Trail Geometry, Integrated down tube battery, enclosed internal cable, Command Post routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel
REAR SHOCK	Fox Float DPX2 Factory, 3- position adjustment, 52.5x210mm, Rx Trail Tune
FORK	Fox Float 36 Factory, Grip2 damper, 150mm, 51mm rake, HSC, LSC, HSR, LSR, Kabolt axle
STEM	Deity Copperhead, 35.0mm
HANDLEBARS	Specialized Trail, FACT Carbon, 6-degree upsweep, 8-degree backsweep, 27mm rise, 780mm, 35mm
GRIPS	Deity, Knuckleduster, Black
FRONT BRAKE	Magura MT7 with custom Loic lever blade, 203mm rotor
REAR BRAKE	Magura MT7 with custom Loic lever blade, 203mm rotor
REAR DERAILLEUR	SRAM XX1 Eagle AXS
SHIFT LEVERS	SRAM AXS Eagle Controller
CHAIN	SRAM XX1 Eagle
CRANKSET	Praxis, carbon M30, custom offset
CHAINRINGS	SRAM X-Sync Eagle, 94 BCD, 30T
RIMS	Roval Traverse SL 29, hookless carbon, 30mm inner width, 2Bliss Ready, hand-built, 28h
FRONT HUB	Roval Traverse SL, sealed cartridge bearings, 15mm thru-axle, 110mm spacing
REAR HUB	Roval Traverse SL, DT Swiss Star Ratchet, 54t engagement, SRAM XD driver body, 12mm thru-axle, 148mm spacing
SPOKES	DT Competition Race
FRONT TIRE	Butcher, GRID TRAIL casing, GRIPTON® compound, 29x2.3"
REAR TIRE	Eliminator, GRID TRAIL casing, GRIPTON® compound, 2Bliss Ready, 29x2.3"
SADDLE	Bridge, 155/143mm, Hollow Ti-rails
SEATPOST	RockShox Reverb AXS, 30.9mm, S: 125, M:150, L/XL: 170mm
MOTOR	Specialized SL 1.1, custom lightweight motor
UI/REMOTE	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth*
BATTERY	Specialized SL1-320, fully integrated, 320Wh
CHARGER	Custom charger, 48V System w/ SL system charger plug
WIRING HARNESS	Custom Specialized wiring harness w/ chargeport

PART NO.	DESCRIPTION	COLOR	SIZE
96821-0002	LEVO SL SW CARBON	Carbon / Bronze Foil / Gloss Carbon	S
96821-0003			M
96821-0004			L
96821-0005			XL

TURBO LEVO SL EXPERT CARBON



Cast Battleship / Black



Satin Redwood / White Mountains

Turbo Levo SL is a new, lightweight breed of eMTB that harnesses the quick and lively ride of our Stumpjumper...and adds just enough power to introduce a whole new dimension of kick ass. The Turbo Levo SL Expert Carbon features a full carbon frame paired to full FOX suspension and a SRAM Eagle X01 drivetrain.

- The Turbo Levo SL looks like a Stumpjumper and, out on the trail, feels like one too. That's no mistake. We aimed to build a Stumpjumper with a bit more boost to it and that's exactly what you get—a Sidearm chassis with just the right amount of front-to-rear stiffness and 150mm of smooth, custom-tuned FOX rear suspension. To top it all off, we constructed this Turbo Levo SL chassis entirely from our light-yet-strong FACT 11m carbon.
- The lightweight SL 1.1 motor doubles your effort with as much as 240 watts of silent and powerful assistance to your pedals. The motor's responsive torque curve delivers power perfectly in-tune with your normal riding cadence and leaves no resistance when you're riding without power assistance.
- Worried about running out of power? No problem. Turbo Levo SL eats up big miles and long days. And if you're looking for even more miles, our optional range extender boosts your range by another 50 percent. On top of all that, our Mission Control App can handle battery management automatically, ensuring your battery will last as long as you need it to.
- Assist up to 20 mph / 32 km/h

TURBO LEVO SL EXPERT CARBON

	S	M	L	XL
Stack (mm)	606	606	633	647
Reach (mm)	415	435	455	480
Head-Tube Length (mm)	95	95	125	140
Head-Tube Angle (°)	66	66	66	66
B-B Height (mm)	348	348	348	348
B-B Drop (mm)	27	27	27	27
Trail (mm)	111	111	111	111
Fork Length (full) (mm)	560	560	560	560
Fork Rake/Offset (mm)	51	51	51	51
Front-Center (mm)	729	749	781	812
Chain-Stay Length (mm)	437	437	437	437
Wheelbase (mm)	1165	1185	1217	1248
Top-Tube Length (horizontal) (mm)	574	597	629	663
Bike Stand-Over Height (mm)	787	790	807	814
Seat-Tube Length (mm)	390	410	455	505
Seat-Tube Angle (°)	75.3	75	74.6	74.2
Crank Length (mm)	165	165	170	170
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	40	40	50	50
Saddle Width (mm)	155	143	143	143
Seatpost Length (mm)	125	150	150	170

SPECS	Specifications subject to change without notice.
Frame	FACT 11m full carbon, 29 Trail Geometry, Integrated down tube battery, enclosed internal cable, Command Post routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel
Rear Shock	Fox Float DPX2 Performance Elite, 3- position adjustment, 52.5x210mm, Rx Trail Tune
Fork	Fox Float 36, Performance Elite, Grip2 damper, 150mm, 51mm rake, HSC, LSC, HSR, LSR, Kabolt axle
Stem	Alloy Trail Stem, 35mm bar bore
Handlebars	Specialized Trail, 7050 alloy, 8-degree backsweep, 6-degree upsweep, 30mm rise, 800mm, 35mm clamp
Grips	Deity, Knuckleduster, Black
Front Brake	SRAM Code RS, 4-piston caliper, hydraulic disc, 200mm
Rear Brake	SRAM Code RS, 4-piston caliper, hydraulic disc, 200mm
Rear Derailleur	Sram X01 Eagle, 12-speed
Shift Levers	SRAM X01 Eagle, trigger, 12-speed
Cassette	SRAM XG-1275, 12-speed, 10-52t
Chain	SRAM GX Eagle, 12-speed
Crankset	Praxis, forged M30, custom offset
Chainrings	SRAM X-Sync Eagle, 94 BCD, 30T
Rims	Roval Traverse 29 Alloy, 30mm inner width, hand-built, 2Bliss Ready
Front Hub	Roval, sealed cartridge bearings, 15x110mm spacing, 28h
Rear Hub	Roval DT Swiss 360, 3-pawl design, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h
Spokes	DT Swiss Competition Race
Front Tire	Butcher, GRID TRAIL casing, GRIPTON® compound, 29x2.3"
Rear Tire	Eliminator, GRID TRAIL casing, GRIPTON® compound, 2Bliss Ready, 29x2.3"
Inner Tubes	Standard, Presta valve
Saddle	Bridge Comp, Hollow Cr-mo rails, 155/143mm
SeatPost	X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SRL LE lever, 34.9mm, S: 125mm, M/L: 150mm, XL: 170mm
Seat Binder	Specialized bolt-type, alloy, 38.6mm
Motor	Specialized SL 1.1, custom lightweight motor
UI/Remote	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®, w/Handlebar remote
Battery	Specialized SL1-320, fully integrated, 320Wh
Charger	Custom charger, 48V System w/ SL system charger plug
Wiring Harness	Custom Specialized wiring harness w/ chargeport

PART NO.	DESCRIPTION	COLOR	SIZE
96821-3002	LEVO SL EXPERT CARBON	Cast Battleship / Black	S
96821-3003			M
96821-3004			L
96821-3005			XL
96821-3102	LEVO SL EXPERT CARBON	Satin Redwood / White Mountains	S
96821-3103			M
96821-3104			L
96821-3105			XL

TURBO LEVO SL COMP CARBON



Tarmac Black / Gunmetal



Green Tint / Black

Turbo Levo SL is a new, lightweight breed of eMTB that harnesses the quick and lively ride of our Stumpjumper...and adds just enough power to introduce a whole new dimension of kick ass. The Turbo Levo SL Comp Carbon features a full carbon frame, full FOX suspension and a SRAM Eagle NX drivetrain.

- The Turbo Levo SL looks like a Stumpjumper and, out on the trail, feels like one too. That's no mistake. We aimed to build a Stumpjumper with a bit more boost to it and that's exactly what you get—a Sidearm chassis with just the right amount of front-to-rear stiffness and 150mm of smooth, custom-tuned FOX rear suspension. To top it all off, we constructed this Turbo Levo SL chassis entirely from our light-yet-strong FACT 11m carbon.
- The lightweight SL 1.1 motor doubles your effort with as much as 240 watts of silent and powerful assistance to your pedals. The motor's responsive torque curve delivers power perfectly in-tune with your normal riding cadence and leaves no resistance when you're riding without power assistance.
- Worried about running out of power? No problem. Turbo Levo SL eats up big miles and long days. And if you're looking for even more miles, our optional range extender boosts your range by another 50 percent. On top of all that, our Mission Control App can handle battery management automatically, ensuring your battery will last as long as you need it to.
- Assist up to 20 mph / 32 km/h

TURBO LEVO SL COMP CARBON

	S	M	L	XL
Stack (mm)	606	606	633	647
Reach (mm)	415	435	455	480
Head-Tube Length (mm)	95	95	125	140
Head-Tube Angle (°)	66	66	66	66
B-B Height (mm)	348	348	348	348
B-B Drop (mm)	27	27	27	27
Trail (mm)	111	111	111	111
Fork Length (full) (mm)	560	560	560	560
Fork Rake/Offset (mm)	51	51	51	51
Front-Center (mm)	729	749	781	812
Chain-Stay Length (mm)	437	437	437	437
Wheelbase (mm)	1165	1185	1217	1248
Top-Tube Length (horizontal) (mm)	574	597	629	663
Bike Stand-Over Height (mm)	787	790	807	814
Seat-Tube Length (mm)	390	410	455	505
Seat-Tube Angle (°)	75.3	75	74.6	74.2
Crank Length (mm)	165	165	170	170
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	45	45	45	45
Saddle Width (mm)	155	143	143	143
Seatpost Length (mm)	125	150	150	170

SPECS	Specifications subject to change without notice.
Frame	FACT 11m full carbon, 29 Trail Geometry, Integrated down tube battery, enclosed internal cable, Command Post routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel
Rear Shock	FOX Float DPS Performance, 3-position adjustment, 52.5x210mm, Rx Trail Tune
Fork	Fox Float 34 Rhythm, Grip damper, 150mm, Sweep-Adj, 51mm rake, Kabolt Axle
Stem	Specialized Trail, 3D-forged alloy, 4-bolt, 6-degree rise
Handlebars	Specialized Trail, 6061 alloy, 8-degree backsweep, 6-degree upsweep, 27mm rise, 31.8mm clamp, S 720mm, M-XL 750mm.
Front Brake	SRAM Guide RE, 4-piston caliper, hydraulic disc, 200mm
Rear Brake	SRAM Guide RE, metallic pads
Rear Derailleur	SRAM NX Eagle, 12-speed
Shift Levers	SRAM NX Eagle, trigger, 12-speed
Cassette	SRAM CS PG1230 EAGLE 11-50T
Chain	SRAM NX Eagle, 12-speed
Crankset	Praxis, forged M30, custom offset
Chainrings	SRAM X-Sync Eagle, 94 BCD, 30T
Rims	Specialized 29, hookless alloy, 30mm inner width, tubeless ready
Front Hub	Specialized, sealed cartridge bearings, 15x110mm spacing, 28h
Rear Hub	Specialized, sealed cartridge bearings, 12x148mm thru-axle, 28H
Spokes	DT Swiss Industry
Front Tire	Butcher, GRID TRAIL casing, GRIPTON® compound, 29x2.3"
Rear Tire	Eliminator, GRID TRAIL casing, GRIPTON® compound, 2Bliss Ready, 29x2.3"
Inner Tubes	Standard, Presta valve
Saddle	Bridge Comp, Hollow Cr-mo rails, 155/143mm
SeatPost	X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SRL LE lever, 34.9mm, S: 125mm, M/L: 150mm, XL: 170mm
Seat Binder	Specialized bolt-tube, alloy, 38.6mm
Motor	Specialized SL 1.1, custom lightweight motor
UI/Remote	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®, w/Handlebar remote
Battery	Specialized SL1-320, fully integrated, 320Wh
Charger	Custom charger, 48V System w/ SL system charger plug
Wiring Harness	Custom Specialized wiring harness w/ chargeport

PART NO.	DESCRIPTION	COLOR	SIZE
96821-5302	LEVO SL COMP CARBON	Green Tint / Black	S
96821-5303			M
96821-5304			L
96821-5305			XL
96820-5402	LEVO SL COMP CARBON	Tarmac Black / Gunmetal	S
96820-5403			M
96820-5404			L
96820-5405			XL

TURBO LEVO SL COMP



Dusty Turquoise / Black



Rocket Red / Black

Turbo Levo SL is a new, lightweight breed of eMTB that harnesses the quick and lively ride of our Stumpjumper...and adds just enough power to introduce a whole new dimension of kick ass. Thanks to a clever component selection, the Turbo Levo SL Comp brings all of that rad down to an equally-rad price point.

- The Turbo Levo SL looks like a Stumpjumper and, out on the trail, feels like one too. That's no mistake. We aimed to build a Stumpjumper with a bit more boost to it and that's exactly what you get—similar Sidearm chassis with great, balanced stiffness and 150mm of smooth, custom-tuned suspension. The Turbo Levo SL Comp's chassis is constructed entirely from our light-yet-strong M5 premium aluminum.
- The lightweight SL 1.1 motor doubles your effort with as much as 240 watts of silent and powerful assistance to your pedals. The motor's responsive torque curve delivers power perfectly in-tune with your normal riding cadence and leaves no resistance when you're riding without power assistance.
- Worried about running out of power? No problem. Turbo Levo SL eats up big miles and long days. And if you're looking for even more miles, our optional range extender boosts your range by another 50 percent. On top of all that, our Mission Control App can handle battery management automatically, ensuring your battery will last as long as you need it to.
- Assist up to 20 mph / 32 km/h

TURBO LEVO SL COMP	XS	S	M	L	XL
Stack (mm)	579	606	606	633	647
Reach (mm)	395	415	435	455	481
Head Tube Length (mm)	95	95	95	125	140
Head Tube Angle (°)	66	66	66	66	66
BB Height (mm)	347	347	347	347	347
BB Drop (mm)	27	27	27	27	27
Trail (mm)	110	110	110	110	100
Fork Length, Full (mm)	560	560	560	560	560
Fork Rake/Offset (mm)	51	51	51	51	51
Front Center (mm)	709	729	749	781	813
Chainstay Length (mm)	437	437	437	437	437
Wheelbase (mm)	1145	1165	1185	1217	1249
Top Tube Length, Horizontal (mm)	551	573	595	628	664
Bike Standover Height (mm)	767	771	774	789	789
Seat Tube Length (mm)	380	390	410	455	505
Seat Tube Angle (°)	75.6	75.4	75.2	74.7	74.2
Crank Length (mm)	165	165	165	170	170
Handlebar Width (mm)	750	780	780	780	780
Stem Length (mm)	45	45	45	45	45
Saddle Width (mm)	143	155	143	143	143
Seatpost Length (mm)	315.5	361.5	425.5	425.5	470.5

SPECS	Specifications subject to change without notice.
Frame	Specialized M5 Premium Aluminum, 29 Trail Geometry, integrated down tube battery, enclosed internal cable, Command Post routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel
Rear Shock	FOX Float DPS Performance, 3-position adjustment, 52.5x210mm, Rx Trail Tune
Fork	Fox Float 34 Rhythm, Grip damper, 160mm, Sweep-Adj, 51mm rake, Kabolt Axle
Stem	Specialized Trail, 3D-forged alloy, 4-bolt, 6-degree rise
Handlebars	Specialized Trail, 6061 alloy, 8-degree backsweep, 6-degree upsweep, 27mm rise, 31.8mm clamp, S 720mm, M-XL 750mm,
Front Brake	SRAM Guide RE, 4-piston caliper, hydraulic disc, 200mm
Rear Brake	SRAM Guide RE, metallic pads
Rear Derailleur	SRAM NX Eagle, 12-speed
Shift Levers	SRAM NX Eagle, trigger, 12-speed
Cassette	SRAM CS PG1230 EAGLE 11-50T
Chain	SRAM NX Eagle, 12-speed
Crankset	Praxis, forged M30, custom offset
Chainrings	SRAM X-Sync Eagle, 94 BCD, 30T
Rims	Specialized 29, hookless alloy, 30mm inner width, tubeless ready
Front Hub	Specialized, sealed cartridge bearings, 15x110mm spacing, 28h
Rear Hub	Specialized, sealed cartridge bearings, 12x148mm thru-axle, 32h
Spokes	DT Swiss Industry
Front Tire	Butcher, GRID TRAIL casing, GRIPTON® compound, 29x2.3"
Rear Tire	Eliminator, GRID TRAIL casing, GRIPTON® compound, 2Bliss Ready, 29x2.3"
Inner Tubes	Standard, Presta valve
Saddle	Bridge Comp, Hollow Cr-mo rails, 155/143mm
SeatPost	X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SRL LE lever, 34.9mm, S: 125mm, M/L: 150mm, XL: 170mm
Seat Binder	Specialized bolt-type, alloy, 38.6mm
Motor	Specialized SL 1.1, custom lightweight motor
UI/Remote	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®, w/Handlebar remote
Battery	Specialized SL1-320, fully integrated, 320Wh
Charger	Custom charger, 48V System w/ SL system charger plug
Wiring Harness	Custom Specialized wiring harness w/ chargeport
SWAT	Specialized Z-Cage, Swat CC Multi Tool in steerer tube without Chaintool

PART NO.	DESCRIPTION	COLOR	SIZE
96820-5001	LEVO SL COMP	Dusty Turquoise / Black	XS
96820-5002			S
96820-5003			M
96820-5004			L
96820-5005			XL
96820-5101	LEVO SL COMP	Rocket Red / Black	XS
96820-5102			S
96820-5103			M
96820-5104			L
96820-5105			XL

S-WORKS TURBO LEVO SL FRAMESET



Carbon / Bronze Foil / Gloss Carbon

Turbo Levo SL is a new, lightweight breed of eMTB that harnesses the quick and lively ride of our Stumpjumper...and adds just enough power to introduce a whole new dimension of kick ass. The top-shelf S-Works Turbo Levo SL Frameset features a carbon chassis mated to FOX Factory-level suspension.

- The Turbo Levo SL looks like a Stumpjumper and, out on the trail, feels like one too. That's no mistake. We aimed to build a Stumpjumper with a bit more boost to it and that's exactly what you get—a Sidearm chassis with just the right amount of front-to-rear stiffness and 150mm of smooth, custom-tuned FOX rear suspension. To top it all off, we constructed this Turbo Levo SL chassis entirely from our light-yet-strong FACT 11m carbon.
- The lightweight SL 1.1 motor doubles your effort with as much as 240 watts of silent and powerful assistance to your pedals. The motor's responsive torque curve delivers power perfectly in-tune with your normal riding cadence and leaves no resistance when you're riding without power assistance.
- Worried about running out of power? No problem. Turbo Levo SL eats up big miles and long days. And if you're looking for even more miles, our included range extender boosts your range by another 50 percent. On top of all that, our Mission Control App can handle battery management automatically, ensuring your battery will last as long as you need it to.

SPECS	Specifications subject to change without notice.
Frame	FACT 11m full carbon, 29 Trail Geometry, Integrated down tube battery, enclosed internal cable, Command Post routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel
Rear Shock	Fox Float DPX2 Factory, 3- position adjustment, 52.5x210mm, Rx Trail Tune
Crankset	Praxis, carbon M30, custom offset
Chainrings	SRAM X-Sync Eagle, 94 BCD, 30T
Seat Binder	Specialized Ti-bolt-type, alloy, 38.6mm
Motor	Specialized SL 1.1, custom lightweight motor
UI/Remote	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®, w/Handlebar remote
Battery	Specialized SL1-320, fully integrated, 320Wh
Charger	Custom charger, 48V System w/ SL system charger plug
Wiring Harness	Custom Specialized wiring harness w/ chargeport

S-WORKS TURBO LEVO SL FRAMESET

	S	M	L	XL
Stack (mm)	606	606	633	647
Reach (mm)	415	435	455	480
Head-Tube Length (mm)	95	95	125	140
Head-Tube Angle (°)	66	66	66	66
B-B Height (mm)	348	348	348	348
B-B Drop (mm)	27	27	27	27
Trail (mm)	111	111	111	111
Fork Length (full) (mm)	560	560	560	560
Fork Rake/Offset (mm)	51	51	51	51
Front-Center (mm)	729	749	781	812
Chain-Stay Length (mm)	437	437	437	437
Wheelbase (mm)	1165	1185	1217	1248
Top-Tube Length (horizontal) (mm)	574	597	629	663
Bike Stand-Over Height (mm)	787	790	807	814
Seat-Tube Length (mm)	390	410	455	505
Seat-Tube Angle (°)	75.3	75	74.6	74.2
Crank Length (mm)	165	165	170	170

PART NO.	DESCRIPTION	COLOR	SIZE
76821-0002	LEVO SL SW CARBON FRMSET	Carbon / Bronze Foil / Gloss Carbon	S
76821-0003			M
76821-0004			L
76821-0005			XL

KENEVO

TURBO KENEVO EXPERT



GLOSS RUSTED RED / REDWOOD



SATIN OBSIDIAN / TAUPE

Sorry, chairlifts and shuttle vehicles. The Kenevo Expert just made you obsolete. This is the bike that lets you summit the longest, nastiest climbs with energy to spare so that you can bomb down the longest, nastiest descents. The Kenevo Expert is, hands down, the most capable eMTB in existence, thanks to its 180mm of RockShox front and rear suspension and an all-new Sidearm-style frame that boosts your control. Add in a class-leading 700 watt-hour battery and you've got a bike that has no limits. The new Kenevo gains a stiffer, lower-slung Sidearm-style chassis and more aggressive geometry. And like the new Enduro, the Kenevo features an axle path and suspension that give you the smoothest, fastest ride over the roughest possible terrain. It all adds up to a bike that provides you with a whole new level of confidence and control on the toughest trails. The Kenevo's Specialized 2.1 motor amplifies your pedaling input by a mind blowing 410%. And as for range, our 700-watt hour battery provides you with plenty of range. What's more, our Mission Control App can handle battery management automatically, ensuring your battery will last as long as you need it to. More power. More miles per ride. More awesome.

- The completely redesigned alloy Kenevo frame features an M5 alloy front- and rear-end, an asymmetrical Sidearm design, and a new axle path and leverage curve that give the bike insane levels of control in the most challenging trails.
- Yes, that a dual-crown fork up front. When we launched the original Kenevo we started seeing riders strapping dual-crown forks on their Levos—it was that rowdy of a bike. So when we set out to design this latest Kenevo, we decided to equip our Expert model with a 180mm-travel RockShox Boxxer. Absolute steering precision and downhill control. Bring it on.
- The custom Specialized 2.1 motor represents the pinnacle of e-bike motor technology. The new motor is more efficient, 15% smaller, and 11% lighter than its predecessor. It has many other features that no other e-bike can touch, like instant engagement, fantastic heat management, a double freewheel design that disengages the gear box when you hit top speed, and silent, smooth, and consistent output—even at max power.
- This Turbo's new Specialized M2-series battery features a 700Wh capacity. That incredibly powerful battery is seamlessly integrated inside the frame and is easily removed in seconds, with a single hex wrench.
- The MasterMind Turbo Control Unit is your information hub with customizable display fields, including the exact percentage of battery level, and it features our all-new MicroTune function to adjust power delivery in 10% increments, so you get exactly the support you need to experience precisely the ride you want.

SPECS	Specifications subject to change without notice.
Frame	Specialized M5 Premium Aluminum, 27.5 Trail Geometry, integrated down tube battery, enclosed internal cable, Command Post routing, 148mm spacing, fully sealed cartridge bearings, 180mm of travel
Rear Shock	Rockshox Super Deluxe Coil, 230x62.5mm, S2:450lb, S3:500lb, S4:550lb, S5:600lb
Fork	RockShox Boxxer Select RC, 27.5, DebonAir, 20x110mm Boost™, 35mm chassis, 180mm of travel
Stem	Descendant 35mm Direct Mount Stem, 50mm length
Handlebars	Specialized Trail, 7050 alloy, 8-degree backsweep, 6-degree upsweep, 30mm rise, 800mm, 35mm clamp
Grips	Deity Grips
Front Brake	SRAM Code RS, 4-piston caliper, hydraulic disc, 200mm
Rear Brake	SRAM Code RS, 4-piston caliper, hydraulic disc, 220mm
Rear Derailleur	SRAM GX Eagle AXS, w/ battery cover
Shift Levers	SRAM GX Eagle AXS Controller
Cassette	SRAM XG-1275, 12-speed, 10-52t
Chain	SRAM GX Eagle, 12-speed
Crankset	Praxis forged M30, custom offset, 160mm
Chainrings	SRAM X-Sync Eagle, 104BCD, 32T, steel
Rims	Roval 27.5" Alloy DH, 28mm internal width, 32h, tubeless ready
Front Hub	Alloy, sealed cartridge bearings, 20x110mm, 28h
Rear Hub	DT Swiss 370, 6-bolt, 12x148mm thru-axle, 32h
Spokes	DT Swiss Industry
Front Tire	Butcher Grid Gravity 2Bliss Ready T9, 27.5 x 2.6"
Rear Tire	Butcher Grid Gravity 2Bliss Ready T9, 27.5 x 2.6"
Inner Tubes	Presta, 40mm valve
Saddle	Bridge, 155/143mm, Hollow Ti-rails
SeatPost	OneUp, Dropper Post-V2, MMX lever, 34.9 (S1:120mm, S2/S3:150mm, S4: 180mm, S5/S6: 210mm)
Seat Binder	Alloy, 38.6mm
Motor	Specialized 2.1 Custom Rx Trail Tuned Motor
UI/Remote	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, over-the-air updates, ANT+/Bluetooth®, w/Handlebar remote
Battery	Specialized M2-700, integrated battery w/rock guard, 700Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Wiring Harness	Custom Specialized harness
SWAT	Specialized Z-Cage, Swat CC Multi Tool in steerer tube without Chaintool

PART NO.	DESCRIPTION	COLOR	SIZE
98023-3502	KENEVO EXPERT 6FATTIE NB	GLOSS RUSTED RED / REDWOOD	S2
98023-3503			S3
98023-3504			S4
98023-3505			S5
98023-3402	KENEVO EXPERT 6FATTIE NB	SATIN OBSIDIAN / TAUPE	S2
98023-3403			S3
98023-3404			S4
98023-3405			S5

KENEVO EXPERT



SATIN DOPPIO / SAND



SATIN OLIVE GREEN / OAK GREEN

Sorry, chairlifts and shuttle vehicles. The Kenevo Expert just made you obsolete. This is the bike that lets you summit the longest, nastiest climbs with energy to spare so that you can bomb down the longest, nastiest descents. The Kenevo Expert is, hands down, the most capable eMTB in existence, thanks to its 180mm of RockShox front and rear suspension and an all-new Sidearm-style frame that boosts your control. Add in a class-leading 700 watt-hour battery and you've got a bike that has no limits.

- The completely redesigned alloy Kenevo frame features an M5 alloy front- and rear-end, an asymmetrical Sidearm design, and a new axle path and leverage curve that give the bike insane levels of control in the most challenging trails.
- Yes, that a dual-crown fork up front. When we launched the original Kenevo we started seeing riders strapping dual-crown forks on their Levos—it was that rowdy of a bike. So when we set out to design this latest Kenevo, we decided to equip our Expert model with a 180mm-travel RockShox Boxxer. Absolute steering precision and downhill control. Bring it on.
- The custom Specialized 2.2 motor represents the pinnacle of e-bike motor technology. The new motor is more efficient, 15% smaller, and 11% lighter than its predecessor. It has many other features that no other e-bike can touch, like instant engagement, fantastic heat management, a double freewheel design that disengages the gear box when you hit top speed, and silent, smooth, and consistent output—even at max power.
- This Turbo's new Specialized M2-series battery features a 700Wh capacity. That incredibly powerful battery is seamlessly integrated inside the frame and is easily removed in seconds, with a single hex wrench.
- The MasterMind Turbo Control Unit is your information hub with customizable display fields, including the exact percentage of battery level, and it features our all-new MicroTune function to adjust power delivery in 10% increments, so you get exactly the support you need to experience precisely the ride you want.

KENEVO EXPERT	S2	S3	S4	S5
Stack (mm)	602	611	620	629
Reach (mm)	450	475	500	525
Head Tube Length (mm)	105	115	125	135
Head Tube Angle (°)	64.5	64.5	64.5	64.5
BB Height (mm)	351	351	351	351
BB Drop (mm)	8	8	8	8
Trail (mm)	125	125	125	125
Fork Length, Full (mm)	572	572	572	572
Fork Rake/Offset (mm)	46	46	46	46
Front Center (mm)	780	809	838	868
Chainstay Length (mm)	454	454	454	454
Wheelbase (mm)	1234	1263	1292	1322
Top Tube Length, Horizontal (mm)	578	605	632	659
Bike Standover Height (mm)	799	799	799	799
Seat Tube Length (mm)	400	420	440	465
Seat Tube Angle (°)	78	78	78	78
Crank Length (mm)	160	160	160	160
Handlebar Width (mm)	800	800	800	800
Stem Length (mm)	50	50	50	50
Saddle Width (mm)	155	143	143	143
Seatpost Length (mm)	120	150	180	210

SPECS	Specifications subject to change without notice.
Frame	Specialized M5 Premium Aluminum, 27.5 Trail Geometry, integrated down tube battery, enclosed internal cable, Command Post routing, 148mm spacing, fully sealed cartridge bearings, 180mm of travel
Rear Shock	RockShox Super Deluxe Select Plus, 230 x 62.5mm
Fork	RockShox Boxxer Select RC, 27.5, DebonAir, 20x110mm Boost™, 35mm chassis, 180mm of travel
Stem	Descendant 35mm Direct Mount Stem, 50mm length
Handlebars	Specialized Trail, 7050 alloy, 8-degree backsweep, 6-degree upsweep, 30mm rise, 800mm, 35mm clamp
Grips	Deity, Knuckleduster, Black
Front Brake	SRAM Code RS, 4-piston caliper, hydraulic disc, 220mm
Rear Brake	SRAM Code RS, 4-piston caliper, hydraulic disc, 220mm
Rear Derailleur	Sram X01 Eagle, 12-speed
Shift Levers	SRAM X01 Eagle trigger, 12-speed, single click
Cassette	SRAM XG-1275, 12-speed, 10-52t
Chain	SRAM GX Eagle, 12-speed
Crankset	Praxis Carbon M30, custom offset, 160mm
Chainrings	SRAM X-Sync Eagle, 104BCD, 32T, steel
Rims	Roval 27.5" Alloy DH, 28mm internal width, 32h, tubeless ready
Front Hub	Alloy, sealed cartridge bearings, 20x110mm, 28h
Rear Hub	DT Swiss 370, 6-bolt, 12x148mm thru-axle, 32h
Spokes	DT Swiss Industry
Front Tire	Butcher Grid Gravity 2Bliss Ready T9, 27.5 x 2.6"
Rear Tire	Butcher Grid Gravity 2Bliss Ready T9, 27.5 x 2.6"
Inner Tubes	Presta, 40mm valve
Saddle	Bridge, 155/143mm, Hollow Ti-rails
SeatPost	OneUp, Dropper Post-V2, MMX lever, 34.9 (S1:120mm, S2/S3:150mm, S4: 180mm, S5/S6: 210mm)
Seat Binder	Alloy, 38.6mm
Motor	Specialized Turbo Full Power System 2.2 Motor
UI/Remote	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, over-the-air updates, ANT+/Bluetooth®, w/Handlebar remote
Battery	Specialized M2-700, integrated battery w/rock guard, 700Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug
Wiring Harness	Custom Specialized harness
SWAT	Specialized Z-Cage, Swat CC Multi Tool in steerer tube without Chaintool

PART NO.	DESCRIPTION	COLOR	SIZE
98022-3202	KENEVO EXPERT 6FATTIE NB	SATIN DOPPIO / SAND	S2
98022-3203			S3
98022-3204			S4
98022-3205			S5
98022-3302	KENEVO EXPERT 6FATTIE NB	SATIN OLIVE GREEN / OAK GREEN	S2
98022-3303			S3
98022-3304			S4
98022-3305			S5

TURBO KENEVO COMP



GLOSS DARK MOSS GREEN / OAK GREEN



SATIN HARVEST GOLD / OBSIDIAN

The Kenevo is the most capable eMTB you can find—complete with 180mm of front and rear suspension, the smoothest and most powerful motor available, and more miles per charge than ever before. Our Kenevo Comp model pairs all that technology with a smart mix of components that'll withstand the most demanding conditions and riders. The new Kenevo gains a stiffer, lower-slung Sidearm-style chassis and more aggressive geometry. And like the new Enduro, the Kenevo features an axle path and suspension that give you the smoothest, fastest ride over the roughest possible terrain. It all adds up to a bike that provides you with a whole new level of confidence and control on the toughest trails. The Kenevo's Specialized 2.1 motor amplifies your pedaling input by a mind blowing 410%. And as for range, our 500-watt hour battery provides you with plenty of range. What's more, our Mission Control App can handle battery management automatically, ensuring your battery will last as long as you need it to. More power. More miles per ride. More awesome.

- The completely redesigned alloy Kenevo frame features an M5 alloy front- and rear-end, an asymmetrical Sidearm design, and a new axle path and leverage curve that give the bike insane levels of control in the most challenging trails.
- FOX DHX Performance Series shock offers 180mm of plush suspension as well as adjustable low-speed compression and rebound damping, to help you dial in the ride to your style and terrain.
- FOX 38 Rhythm fork provides 180mm of smooth, controlled front suspension. Features include a proven FOX GRIP damper and EVOL air spring. Simple, reliable and absolutely capable of swallowing any rock or root that comes your way.
- The custom Specialized 2.1 motor represents the pinnacle of e-bike motor technology. The new motor is more efficient, 15% smaller, and 11% lighter than its predecessor. It has many other features that no other e-bike can touch, like instant engagement, fantastic heat management, a double freewheel design that disengages the gear box when you hit top speed, and silent, smooth, and consistent output—even at max power.
- This Turbo's new Specialized M2-series battery features a 500Wh capacity. That powerful battery is seamlessly integrated inside the frame and is easily removed in seconds, with a single hex wrench.

SPECS	Specifications subject to change without notice.
Frame	Specialized M5 Premium Aluminum, 27.5 Trail Geometry, integrated down tube battery, enclosed internal cable, Command Post routing, 148mm spacing, fully sealed cartridge bearings, 180mm of travel
Rear Shock	2023_22, DHX, P-S, Cr, 2pos, Specialized, Kenevo, 230, 62.5, 450/500/550/600bs/in, CL, RM, Rezi LMB3, Standard Logo, N/M
Fork	2023, 38, A, FLOAT, 27.5in, Rhythm, 180, Grip, Sweep-Adj, Matte Blk, Std/Matte Blk Logo, 15QRx110, 1.5 T, 58HT, 37mm Rake, N/M OE
Stem	Alloy Trail Stem, 35mm bar bore
Handlebars	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 30mm rise, 780mm width
Front Brake	Shimano SLX M7120, 4-piston caliper, hydraulic disc, 203 mm
Rear Brake	Shimano SLX M7120, 4-piston caliper, hydraulic disc, 180mm
Rear Derailleur	Shimano Deore XT RD-M8130, 11-speed
Shift Levers	Shimano Deore XT M8130, 11-speed
Cassette	Shimano 11-50
Chain	Shimano 11-speed
Crankset	Praxis forged M30, custom offset, 160mm
Chainrings	32T
Rims	Roval 27.5" Alloy DH, 28mm internal width, 32h, tubeless ready
Front Hub	Shimano MT400, centerlock
Rear Hub	Shimano MT400-B, Centerlock, 12x148 Boost, 32h
Spokes	DT Swiss Industry
Front Tire	Butcher Grid Gravity 2Bliss Ready T9, 27.5 x 2.6"
Rear Tire	Butcher Grid Gravity 2Bliss Ready T9, 27.5 x 2.6"
Inner Tubes	Presta, 40mm valve
Saddle	Bridge Comp, Hollow Cr-mo rails, 155/143mm
SeatPost	X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SRL LE lever, 34.9mm, S: 125mm, M/L: 150mm, XL: 170mm
Seat Binder	Alloy, 38.6mm
Motor	Specialized 2.1 Custom Rx Trail Tuned Motor
UI/Remote	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®, w/Handlebar remote
Battery	Specialized M2-500, integrated battery w/rock guard, 500Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Wiring Harness	Custom Specialized harness
SWAT	Specialized Z-Cage, Swat CC Multi Tool in steerer tube without Chaintool

PART NO.	DESCRIPTION	COLOR	SIZE
98023-5202	KENEVO COMP 6FATTIE NB	GLOSS DARK MOSS GREEN / OAK GREEN	S2
98023-5203			S3
98023-5204			S4
98023-5205			S5
98023-5302	KENEVO COMP 6FATTIE NB	SATIN HARVEST GOLD / OBSIDIAN	S2
98023-5303			S3
98023-5304			S4
98023-5305			S5

KENEVO COMP



GLOSS LAGOON BLUE / BLACK



SATIN FOREST GREEN / PINE GREEN

The Kenevo is the most capable eMTB you can find—complete with 180mm of front and rear suspension, the smoothest and most powerful motor available, and more miles per charge than ever before. Our Kenevo Comp model pairs all that technology with a smart mix of components that'll withstand the most demanding conditions and riders.

- The completely redesigned alloy Kenevo frame features an M5 alloy front- and rear-end, an asymmetrical Sidearm design, and a new axle path and leverage curve that give the bike insane levels of control in the most challenging trails.
- Fox Float X Performance Series shock offers 180mm of plush suspension as well as adjustable low-speed compression and rebound damping, to help you dial in the ride to your style and terrain.
- Marzocchi Bomber Z1 air-sprung fork provides 180mm of smooth, controlled front suspension. Features include a proven FOX GRIP damper and EVOL air spring. Simple, reliable and absolutely capable of swallowing any rock or root that comes your way.
- The custom Specialized 2.2 motor represents the pinnacle of e-bike motor technology. The new motor is more efficient, 15% smaller, and 11% lighter than its predecessor. It has many other features that no other e-bike can touch, like instant engagement, fantastic heat management, a double freewheel design that disengages the gear box when you hit top speed, and silent, smooth, and consistent output—even at max power.
- This Turbo's new Specialized M2-series battery features a 500Wh capacity. That powerful battery is seamlessly integrated inside the frame and is easily removed in seconds, with a single hex wrench.

KENEVO COMP	S2	S3	S4	S5
Stack (mm)	602	611	620	629
Reach (mm)	450	475	500	525
Head Tube Length (mm)	105	115	125	135
Head Tube Angle (°)	64.5	64.5	64.5	64.5
BB Height (mm)	351	351	351	351
BB Drop (mm)	8	8	8	8
Trail (mm)	125	125	125	125
Fork Length, Full (mm)	572	572	572	572
Fork Rake/Offset (mm)	44	44	44	44
Front Center (mm)	780	809	838	868
Chainstay Length (mm)	454	454	454	454
Wheelbase (mm)	1234	1263	1292	1322
Top Tube Length, Horizontal (mm)	578	605	632	659
Bike Standover Height (mm)	799	799	799	799
Seat Tube Length (mm)	400	420	440	465
Seat Tube Angle (°)	78	78	78	78
Crank Length (mm)	160	160	160	160
Handlebar Width (mm)	800	800	800	800
Stem Length (mm)	40	50	50	50
Saddle Width (mm)	155	143	143	143
Seatpost Length (mm)	125	150	150	150

SPECS	Specifications subject to change without notice.
Frame	Specialized M5 Premium Aluminum, 27.5 Trail Geometry, integrated down tube battery, enclosed internal cable, Command Post routing, 148mm spacing, fully sealed cartridge bearings, 180mm of travel
Rear Shock	Fox Float X Performance Series, 230x62.5mm
Fork	2021, Bomber Z1, 27.5in, Marzocchi, 180, Grip, Sweep-Adj, Matte Blk, Neutral/Matte Blk Logo, Kabolt 110, BLK, 1.5 T, 44mm Rake, N/M OE.
Stem	Alloy Trail Stem, 35mm bar bore
Handlebars	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 30mm rise, 780mm width
Front Brake	SRAM Code R, 4-piston caliper, hydraulic disc, 220mm
Rear Brake	SRAM Code R, 4-piston caliper, hydraulic disc, 200mm
Rear Derailleur	SRAM GX Eagle, 12-speed
Shift Levers	SRAM GX Eagle, trigger, 12-speed, single click
Cassette	SRAM NX Eagle PG-1230, 12-speed, 11-50t
Chain	SRAM NX Eagle, 12-speed
Crankset	Praxis forged M30, custom offset, 160mm
Chainrings	SRAM X-Sync Eagle, 104BCD, 32T, steel
Rims	Roval 27.5" Alloy DH, 28mm internal width, 32h, tubeless ready
Front Hub	Alloy, sealed cartridge bearings, 15x110mm thru-axle, 28h
Rear Hub	Alloy, sealed cartridge bearings, 12x148mm thru-axle, 32h
Spokes	DT Swiss Industry
Front Tire	Butcher Grid Gravity 2Bliss Ready T9, 27.5 x 2.6"
Rear Tire	Butcher Grid Gravity 2Bliss Ready T9, 27.5 x 2.6"
Inner Tubes	Presta, 40mm valve
Saddle	Bridge Comp, Hollow Cr-mo rails, 155/143mm
SeatPost	X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SRL LE lever, 34.9mm, S: 125mm, M/L: 150mm, XL: 170mm
Seat Binder	Alloy, 38.6mm
Motor	Specialized Turbo Full Power System 2.2 Motor
UI/Remote	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®, w/Handlebar remote
Battery	Specialized M2-500, integrated battery w/rock guard, 500Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug
Wiring Harness	Custom Specialized harness
SWAT	Specialized Z-Cage, Swat CC Multi Tool in steerer tube without Chaintool

PART NO.	DESCRIPTION	COLOR	SIZE
98022-5202	KENEVO COMP 6FATTIE NB	GLOSS LAGOON BLUE / BLACK	S2
98022-5203			S3
98022-5204			S4
98022-5205			S5
98022-5302	KENEVO COMP 6FATTIE NB	SATIN FOREST GREEN / PINE GREEN	S2
98022-5303			S3
98022-5304			S4
98022-5305			S5

KENEVO SL

S-WORKS TURBO KENEVO SL



Gloss Carbon / Black / Satin Brushed Dream Silver / white



Gloss Oak Green Metallic / Satin Black

Power up to trail riding's next level and dominate any and all trail monsters—the Turbo Kenevo Super Light melds the legendary handling and all-around big trail prowess of the Enduro with our Super Light electric support to deliver indomitable capability, light weight, and power to conquer more and bigger trails.

- The Turbo Kenevo Super Light motor/controller system is a full integration of the bike's 250-watt motor and 320Wh battery with a radically advanced and seamlessly integrated controller. The result is massive power delivered, up to 25kph, to get you to the top of your favorite descent with just half of the effort, and much faster, giving even more of the quality ride you yearn for, and more of it than ever before possible.
- Our next-generation Mastermind TCU is your information hub, with customizable display fields including the exact percentage of battery level, and features our all-new, bar-mounted MicroTune function to adjust power delivery in 10% increments, so you get exactly the support you need to experience precisely the ride you want.
- 29" wheels front and rear deliver a nimble ride that carves circles around other full-power e-MTBs. A generous cockpit centers you on the bike, optimizing traction and corner control. The low bottom bracket, slack headtube angle and reduced fork offset keep things stable in the rough.
- The Turbo Kenevo Super Light geometry can be fine-tuned for wherever and however you ride. Six distinct geometry settings allow easy adjustment to hone performance in any terrain. Head angle can be adjusted between 62.5 and 64.5 degrees. Bottom bracket height can be fine-tuned up or down by 7mm. We've never made a more adjustable, adaptable trail bike.
- The Turbo Kenevo Super Light's 170mm of Enduro-inspired travel is supple on small bumps, devours square-edged hits without a twitch, eats massive G-outs for breakfast, yet still offers amazing pedal response and delivers your power to the ground with total efficiency.
- The Turbo Kenevo Super Light's S-Sizing is based on what matters—rider size and style, not inseam. Four sizes, all with similar headtube lengths and standover, allow you to choose the size that best suits your individual style. Smaller S-Size numbers are going to be nimble and more flickable, while bigger S-Sizes deliver more stability and a roomier ride.

S-WORKS TURBO KENEVO SL	S2	S3	S4	S5
Stack (mm)	618	626	635	644
Reach (mm)	435	460	485	510
Headtube Length (mm)	105	115	125	135
Headtube Angle (°)	63.5	63.5	63.5	63.5
BB Height (mm)	350	350	350	350
BB Drop (mm)	25	25	25	25
Trail (mm)	136	136	136	136
Fork Length (full) (mm)	579	579	579	579
Fork Rake/Offset (mm)	46	46	46	46
Front Center (mm)	782	812	841	871
Chainstay Length (mm)	447	447.3	447	447
Wheelbase (mm)	1228	1258	1287	1316
Bike Standover Height (mm)	779	779	792	802
Seat Tube Length (mm)	400	420	440	465
Seat Tube Angle (°)	76	76	76	76
Max Seatpost Insertion (mm)	0	0	0	0
Min Seatpost Insertion (mm)	80	80	80	80
Crank Length (mm)	165	165	170	170
Handlebar Width (mm)	800	800	800	800
Stem Length (mm)	35	50	50	50
Saddle Width (mm)	155	143	143	143
Seatpost Length (mm)	125	150	170	170

SPECS	Specifications subject to change without notice.
Frame	FACT 11m full carbon, 29", full internal cable routing, 148mm spacing, fully sealed cartridge bearings, 170mm rear travel, geo adjust head tube, geo adjust horst pivot
Rear Shock	FOX FLOAT X2 Factory, LSC, LSR, 2-position lever, 62.5x230mm, Kashima
Fork	FOX FLOAT 38 Factory 29, Grip2 damper, 44mm offset, HSC, LSC, HSR, LSR, 110x15mm, 1.5" tapered steerer, 170mm travel, Kashima
Stem	Deity Copperhead, 35.0mm
Handlebars	Royal Traverse SL Carbon, riser bar, 6-degree upsweep, 8-degree backsweep, 30mm rise, 800mm, 35.0mm
Grips	Deity, Knuckleduster, Black
Front Brake	SRAM Code RSC, 4-piston caliper, hydraulic disc, 220mm
Rear Brake	SRAM Code RSC, 4-piston caliper, hydraulic disc, 200mm
Rear Derailleur	SRAM XX1 Eagle AXS
Shift Levers	SRAM Eagle AXS Rocker Paddle
Cassette	SRAM XG-1299 Eagle, 10-52t
Chain	SRAM XX1, 12 speed
Crankset	Praxis Carbon M30, custom offset
Chainrings	SRAM X-Sync Eagle, 94 BCD, 32t, alloy
Front Wheel	Traverse SL 29
Rear Wheel	Traverse SL 29
Front Tire	Butcher Grid Trail T9 29x2.6"
Rear Tire	Eliminator Grid Trail T7 29x2.6"
Inner Tubes	Standard, Presta valve
Saddle	Bridge, 155/143mm, Hollow Ti-rails
SeatPost	RockShox Reverb AXS, 30.9mm, S: 125, M:150, L/XL: 170mm
Seat Binder	Alloy, 38.6mm
Motor	Specialized SL 1.1, custom lightweight motor
UI/Remote	Specialized MasterMind TCU, ANT+/Bluetooth®, w/Handlebar remote
Battery	Specialized SL1-320, fully integrated, 320Wh
Charger	Custom charger, 48V System w/ SL system charger plug
Wiring Harness	Custom Specialized wiring harness
SWAT	SWAT CC, integrated tool and chain tool with spare link in steerer tube

PART NO.	DESCRIPTION	COLOR	SIZE
98021-0102	KENEVO SL SW CARBON 29	Gloss Carbon / Black / Satin Brushed Dream Silver / white	S2
98021-0103			S3
98021-0104			S4
98021-0105			S5
98021-0002	KENEVO SL SW CARBON 29	Gloss Oak Green Metallic / Satin Black	S2
98021-0003			S3
98021-0004			S4
98021-0005			S5

TURBO KENEVO SL EXPERT



Gloss Brassy Yellow / Black



Gloss Cool Grey / Carbon / Dove Grey / Black

Power up to trail riding's next level and dominate any and all trail monsters—the Turbo Kenevo Super Light melds the legendary handling and all-around big trail prowess of the Enduro with our Super Light electric support to deliver indomitable capability, light weight, and power to conquer more and bigger trails.

- The Turbo Kenevo Super Light motor/controller system is a full integration of the bike's 240-watt motor and 320Wh battery with a radically advanced and seamlessly integrated controller. The result is massive power delivered, up to 25kph, to get you to the top of your favorite descent with just half of the effort, and much faster, giving even more of the quality ride you yearn for, and more of it than ever before possible.
- Our next-generation Mastermind TCU is your information hub, with customizable display fields including the exact percentage of battery level, and features our all-new, bar-mounted MicroTune function to adjust power delivery in 10% increments, so you get exactly the support you need to experience precisely the ride you want.
- 29" wheels front and rear deliver a nimble ride that carves circles around other full-power e-MTBs. A generous cockpit centers you on the bike, optimizing traction and corner control. The low bottom bracket, slack headtube angle and reduced fork offset keep things stable in the rough.
- The Turbo Kenevo Super Light geometry can be fine-tuned for wherever and however you ride. Six distinct geometry settings allow easy adjustment to hone performance in any terrain. Head angle can be adjusted between 62.5 and 64.5 degrees. Bottom bracket height can be fine-tuned up or down by 7mm. We've never made a more adjustable, adaptable trail bike.
- The Turbo Kenevo Super Light's 170mm of Enduro-inspired travel is supple on small bumps, devours square-edged hits without a twitch, eats massive G-outs for breakfast, yet still offers amazing pedal response and delivers your power to the ground with total efficiency.
- The Turbo Kenevo Super Light's S-Sizing is based on what matters—rider size and style, not inseam. Four sizes, all with similar headtube lengths and standover, allow you to choose the size that best suits your individual style. Smaller S-Size numbers are going to be nimble and more flickable, while bigger S-Sizes deliver more stability and a roomier ride.

TURBO KENEVO SL EXPERT	S2	S3	S4	S5
Stack (mm)	618	626	635	644
Reach (mm)	435	460	485	510
Headtube Length (mm)	105	115	125	135
Headtube Angle (°)	63.5	63.5	63.5	63.5
BB Height (mm)	350	350	350	350
BB Drop (mm)	25	25	25	25
Trail (mm)	136	136	136	136
Fork Length (full) (mm)	579	579	579	579
Fork Rake/Offset (mm)	46	46	46	46
Front Center (mm)	782	812	841	871
Chainstay Length (mm)	447	447.3	447	447
Wheelbase (mm)	1228	1258	1287	1316
Bike Standover Height (mm)	779	779	792	802
Seat Tube Length (mm)	400	420	440	465
Seat Tube Angle (°)	76	76	76	76
Max Seatpost Insertion (mm)	0	0	0	0
Min Seatpost Insertion (mm)	80	80	80	80
Crank Length (mm)	165	165	170	170
Handlebar Width (mm)	800	800	800	800
Stem Length (mm)	40	50	50	50
Saddle Width (mm)	155	143	143	143
Seatpost Length (mm)	125	150	170	170

SPECS	Specifications subject to change without notice.
Frame	FACT 11m full carbon, 29", full internal cable routing, 148mm spacing, fully sealed cartridge bearings, 170mm rear travel, geo adjust head tube, geo adjust horst pivot
Rear Shock	FOX FLOAT X2 Performance, 2-position lever, 62.5x230mm
Fork	FOX FLOAT 38 Performance Elite 29, Grip2 damper, 44mm offset, HSC, LSC, HSR, LSR, 110x15mm, 1.5" tapered steerer, 170mm travel
Stem	Alloy Trail Stem, 35mm bar bore
Handlebars	Specialized Trail, 7050 alloy, 8-degree backsweep, 6-degree upsweep, 30mm rise, 800mm, 35mm clamp
Grips	Deity, Knuckleduster, Black
Front Brake	SRAM Code RS, 4-piston caliper, hydraulic disc, 220mm
Rear Brake	SRAM Code RS, 4-piston caliper, hydraulic disc, 200mm
Rear Derailleur	Sram X01 Eagle, 12-speed
Shift Levers	SRAM X01 Eagle, trigger, 12-speed
Cassette	SRAM XG-1295 Eagle, 10-52t
Chain	SRAM GX Eagle, 12-speed
Crankset	Praxis, forged M30, custom offset
Chainrings	SRAM X-Sync Eagle, 94 BCD, 32t, alloy
Front Wheel	Traverse 29
Rear Wheel	Traverse 29
Rims	Roval Traverse 29 Alloy, 30mm inner width, hand-built, 2Bliss Ready
Front Hub	Roval, sealed cartridge bearings, 15x110mm spacing, 28h
Rear Hub	Roval DT Swiss 370, Ratchet LN, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h
Spokes	DT Swiss Competition Race
Front Tire	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Rear Tire	Eliminator, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, 29x2.6"
Inner Tubes	Standard, Presta valve
Saddle	Bridge Comp, Hollow Cr-mo rails, 155/143mm
SeatPost	X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SLR LE lever, 34.9mm, S2: 125mm, S3/S4: 150mm, S5: 170mm
Seat Binder	Alloy, 38.6mm
Motor	Specialized SL 1.1, custom lightweight motor
UI/Remote	Specialized MasterMind TCU, ANT+/Bluetooth®, w/Handlebar remote
Battery	Specialized SL1-320, fully integrated, 320Wh
Charger	Custom charger, 48V System w/ SL system charger plug
Wiring Harness	Custom Specialized wiring harness
SWAT	SWAT CC, integrated tool and chain tool with spare link in steerer tube

PART NO.	DESCRIPTION	COLOR	SIZE
98021-3602	KENEVO SL EXPERT CARBON 29	Gloss Brassy Yellow / Black	S2
98021-3603			S3
98021-3604			S4
98021-3605			S5
98021-3702	KENEVO SL EXPERT CARBON 29	Gloss Cool Grey / Carbon / Dove Grey / Black	S2
98021-3703			S3
98021-3704			S4
98021-3705			S5

TURBO KENEVO SL COMP



Gloss Blaze / Black



Gloss Smoke / Dream Silver

Power up to trail riding's next level and dominate any and all trail monsters—the Turbo Kenevo Super Light melds the legendary handling and all-around big trail prowess of the Enduro with our Super Light electric support to deliver indomitable capability, light weight, and power to conquer more and bigger trails.

- The Turbo Kenevo Super Light motor/controller system is a full integration of the bike's 250-watt motor and 320Wh battery with a radically advanced and seamlessly integrated controller. The result is massive power delivered, up to 25kph, to get you to the top of your favorite descent with just half of the effort, and much faster, giving even more of the quality ride you yearn for, and more of it than ever before possible.
- Our next-generation TCU2 is your information hub, with customizable display fields including the exact percentage of battery level, and features our all-new, bar-mounted MicroTune function to adjust power delivery in 10% increments, so you get exactly the support you need to experience precisely the ride you want.
- 29" wheels front and rear deliver a nimble ride that carves circles around other full-power e-MTBs. A generous cockpit centers you on the bike, optimizing traction and corner control. The low bottom bracket, slack headtube angle and reduced fork offset keep things stable in the rough.
- The Turbo Kenevo Super Light geometry can be fine-tuned for wherever and however you ride. Six distinct geometry settings allow easy adjustment to hone performance in any terrain. Head angle can be adjusted between 63 and 65.5 degrees. Bottom bracket height can be fine-tuned up or down by 7mm. We've never made a more adjustable, adaptable trail bike.
- The Turbo Kenevo Super Light's 170mm of Enduro-inspired travel is supple on small bumps, devours square-edged hits without a twitch, eats massive G-outs for breakfast, yet still offers amazing pedal response and delivers your power to the ground with total efficiency.
- The Turbo Kenevo Super Light's S-Sizing is based on what matters—rider size and style, not inseam. Six sizes, all with similar headtube lengths and standover, allow you to choose the size that best suits your individual style. Smaller S-Size numbers are going to be nimble and more flickable, while bigger S-Sizes deliver more stability and a roomier ride.

TURBO KENEVO SL COMP	S2	S3	S4	S5
Stack (mm)	618	626	635	644
Reach (mm)	435	460	485	510
Headtube Length (mm)	105	115	125	135
Headtube Angle (°)	63.5	63.5	63.5	63.5
BB Height (mm)	350	350	350	350
BB Drop (mm)	25	25	25	25
Trail (mm)	136	136	136	136
Fork Length (full) (mm)	579	579	579	579
Fork Rake/Offset (mm)	46	46	46	46
Front Center (mm)	782	812	841	871
Chainstay Length (mm)	447	447.3	447	447
Wheelbase (mm)	1228	1258	1287	1316
Bike Standover Height (mm)	779	779	792	802
Seat Tube Length (mm)	400	420	440	465
Seat Tube Angle (°)	76	76	76	76
Max Seatpost Insertion (mm)	0	0	0	0
Min Seatpost Insertion (mm)	80	80	80	80
Crank Length (mm)	165	165	170	170
Handlebar Width (mm)	800	800	800	800
Stem Length (mm)	40	50000013884000138840	500000138840	500000138841
Saddle Width (mm)	155	143	143	143
Seatpost Length (mm)	125	150	170	170

SPECS	Specifications subject to change without notice.
Frame	FACT 11m full carbon, 29", full internal cable routing, 148mm spacing, fully sealed cartridge bearings, 170mm rear travel, geo adjust head tube, geo adjust horst pivot
Rear Shock	FOX FLOAT X Performance, LSR, 2-position lever, 62.5x230mm
Fork	FOX FLOAT 36 RHYTHM 29, GRIP damper, 44mm offset, 2-position sweep adjust, 15x110mm, 1.5" tapered steerer, 170mm travel
Stem	Alloy Trail Stem, 35mm bar bore
Handlebars	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 30mm rise, 780mm width
Front Brake	SRAM Code R, 4-piston caliper, hydraulic disc, 220mm
Rear Brake	SRAM Code R, 4-piston caliper, hydraulic disc, 200mm
Rear Derailleur	SRAM GX Eagle, 12-speed
Shift Levers	SRAM GX Eagle, 12-speed
Cassette	SRAM XG-1275, 12-speed, 10-52t
Chain	SRAM NX Eagle, 12-speed
Crankset	Praxis, forged M30, custom offset
Chainrings	SRAM X-Sync Eagle, 94 BCD, 32t, alloy
Rims	Specialized 29, hookless alloy, 30mm inner width, tubeless ready
Front Hub	Alloy, sealed cartridge bearings, 15x110mm thru-axle, 28h
Rear Hub	Alloy, sealed cartridge bearings, 148mmx12mm thru-axle, 28h
Spokes	DT Swiss Industry
Front Tire	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Rear Tire	Eliminator, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, 29x2.6"
Inner Tubes	Standard, Presta valve
Saddle	Bridge Comp, Hollow Cr-mo rails, 155/143mm
SeatPost	X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SLR LE lever, 34.9mm, S2: 125mm, S3/S4: 150mm, S5: 170mm
Seat Binder	Alloy, 38.6mm
Motor	Specialized SL 1.1, custom lightweight motor
UI/Remote	Specialized MasterMind TCU, ANT+ / Bluetooth®, w/Handlebar remote
Battery	Specialized SL1-320, fully integrated, 320Wh
Charger	Custom charger, 48V System w/ SL system charger plug
Wiring Harness	Custom Specialized wiring harness
SWAT	SWAT CC, integrated tool and chain tool with spare link in steerer tube

PART NO.	DESCRIPTION	COLOR	SIZE
98021-5502	KENEVO SL COMP CARBON 29	Gloss Blaze / Black	S2
98021-5503			S3
98021-5504			S4
98021-5505			S5
98021-5602	KENEVO SL COMP CARBON 29	Gloss Smoke / Dream Silver	S2
98021-5603			S3
98021-5604			S4
98021-5605			S5

S-WORKS TURBO KENEVO SL FRAMESET



Gloss Carbon / Black /Satin Brushed Dream Silver / white

Power up to trail riding's next level and dominate any and all trail monsters—the Turbo Kenevo Super Light melds the legendary handling and all-around big trail prowess of the Enduro with our Super Light electric support to deliver indomitable capability, light weight, and power to conquer more and bigger trails.

- The Turbo Kenevo Super Light motor/controller system is a full integration of the bike's 250-watt motor and 320Wh battery with a radically advanced and seamlessly integrated controller. The result is massive power delivered, up to 25kph, to get you to the top of your favorite descent with just half of the effort, and much faster, giving even more of the quality ride you yearn for, and more of it than ever before possible.
- Our next-generation TCU2 is your information hub, with customizable display fields including the exact percentage of battery level, and features our all-new, bar-mounted MicroTune function to adjust power delivery in 10% increments, so you get exactly the support you need to experience precisely the ride you want.
- 29" wheels front and rear deliver a nimble ride that carves circles around other full-power e-MTBs. A generous cockpit centers you on the bike, optimizing traction and corner control. The low bottom bracket, slack headtube angle and reduced fork offset keep things stable in the rough.
- The Turbo Kenevo Super Light geometry can be fine-tuned for wherever and however you ride. Six distinct geometry settings allow easy adjustment to hone performance in any terrain. Head angle can be adjusted between 63 and 65.5 degrees. Bottom bracket height can be fine-tuned up or down by 7mm. We've never made a more adjustable, adaptable trail bike.
- The Turbo Kenevo Super Light's 170mm of Enduro-inspired travel is supple on small bumps, devours square-edged hits without a twitch, eats massive G-outs for breakfast, yet still offers amazing pedal response and delivers your power to the ground with total efficiency.
- The Turbo Kenevo Super Light's 170mm of Enduro-inspired travel is supple on small bumps, devours square-edged hits without a twitch, eats massive G-outs for breakfast, yet still offers amazing pedal response and delivers your power to the ground with total efficiency.

SPECS	Specifications subject to change without notice.
Frame	FACT 11m full carbon, 29", full internal cable routing, 148mm spacing, fully sealed cartridge bearings, 170mm rear travel, geo adjust head tube, geo adjust horst pivot
Rear Shock	FOX FLOAT X2 Factory, LSC, LSR, 2-position lever, 62.5x230mm, Kashima
Crankset	Praxis Carbon M30, custom offset
Chainrings	SRAM X-Sync Eagle, 94 BCD, 32t, alloy
Seat Binder	Alloy, 38.6mm
Motor	Specialized SL 1.1, custom lightweight motor
UI/Remote	Specialized MasterMind TCU, ANT+/Bluetooth®, w/Handlebar remote
Battery	Specialized SL1-320, fully integrated, 320Wh
Charger	Custom charger, 48V System w/ SL system charger plug
Wiring Harness	Custom Specialized wiring harness

S-WORKS TURBO KENEVO SL FRAMESET

	S2	S3	S4	S5
Stack (mm)	618	626	635	644
Reach (mm)	435	460	485	510
Headtube Length (mm)	105	115	125	135
Headtube Angle (°)	63.5	63.5	63.5	63.5
BB Height (mm)	350	350	350	350
BB Drop (mm)	25	25	25	25
Trail (mm)	136	136	136	136
Fork Length (full) (mm)	579	579	579	579
Fork Rake/Offset (mm)	46	46	46	46
Front Center (mm)	782	812	841	871
Chainstay Length (mm)	447	447.3	447	447
Wheelbase (mm)	1228	1258	1287	1316
Bike Standover Height (mm)	779	779	792	802
Seat Tube Length (mm)	400	420	440	465
Seat Tube Angle (°)	76	76	76	76
Max Seatpost Insertion (mm)	0	0	0	0
Min Seatpost Insertion (mm)	80	80	80	80
Crank Length (mm)	165	165	170	170

PART NO.	DESCRIPTION	COLOR	SIZE
78021-0002	KENEVO SL SW CARBON FRMSET	Gloss Carbon / Black /Satin Brushed Dream Silver / white	S2
78021-0003			S3
78021-0004			S4
78021-0005			S5

CREO SL

S-WORKS TURBO CREO SL



Red Tint/Spectraflair/Silver/Black/Chrome

We have a long history of developing the world's highest performing road bikes. Tarmac, Venge, Roubaix, Allez, Diverge—each one dominates their respective category, featuring the best technologies in the industry. And while that's a tough palmarès to follow, the Turbo Creo SL redefines e-road bike performance. It's lightweight, smooth, capable, and lively—all with the power to flatten mountains, laugh at headwinds, and go farther than you ever thought possible. It's you, only faster.

- The Creo SL is the lightest e-bike in its class—literally kilograms lighter than the competition. Not only does the lightweight and stiff FACT 11r carbon frame inspire dancing on the pedals and diving into corners, but it also reduces overall system weight and increases the range.
- The lightweight SL 1.1 motor doubles your effort with as much as 240 watts of silent and powerful assistance to amplify your ride. The motor's responsive torque curve delivers power perfectly in-tune with your normal riding cadence and leaves no resistance when riding unassisted.
- Battery anxiety? Not on the Creo SL. With up to 80 miles of range from the internal battery, the Creo SL eats up big miles and long days. Our optional range extender provides up to 40 additional miles of mountain-flattening power.
- By connecting with our Mission Control App, you're able to tune the SL 1.1 motor to your riding style, record rides, and monitor the battery. The app can handle battery management automatically too, ensuring the battery will last as long as you need it to. The motor even has a built-in power meter that transmits to any ANT+ head unit. Don't want to connect? No worries—the Specialized MasterMind TCU on the top tube gives you all the control you need to ride.
- With the Future Shock 2.0, you'll feel a reduction in fatigue and an increase in speed, no matter the terrain. The 2.0 iteration gives you more control via a knob atop the stem. This knob adjusts compression from fully-open to stiff, while hydraulically-damped internals control rebound. The new Smooth Boot, top cap, and Future Stem also enhance the aesthetic, so you get a clean transition from head tube to stem.
- We've learned there can be more difference between two male cyclists than between a male and female. Gender alone doesn't provide enough data to specialize. It means that separating bikes as male or female is arbitrary and outdated. With this in mind, we've developed a geometry that's best-fit for all riders—one that's comfortable, snappy, and handles like a dream.

S-WORKS TURBO CREO SL	XS	S	M	L	XL	XXL
Stack (mm)	573	575	592	615	643	675
Reach (mm)	363	373	379	384	391	399
Head-Tube Length (mm)	145.5	145.5	163.5	185.5	217	250
Head-Tube Angle (degrees)	71.5	72	72.5	73	73	73
B-B Height (mm)	264.5	264.5	267	267	269.5	269.5
B-B Drop (mm)	80.5	80.5	78	78	75.5	75.5
Trail (mm)	68	60	56	53	53	52
Fork Length (full) (mm)	390	390	390	390	390	390
Fork Rake/Offset (mm)	50	50	50	50	50	50
Front-Center (mm)	586	592	598	605	621	636
Chain-Stay Length (mm)	426	426	426	427	427	428
Wheelbase (mm)	999	1005	1012	1020	1036	1052
Top-Tube Length (horizontal) (mm)	527	539	548	566	581	605
Bike Stand-Over Height (mm)	728	731	759	782	810	840
Seat-Tube Length (mm)	415	447.5	477.5	502.5	527.5	557.5
Seat-Tube Angle (degrees)	74	74	74	73.5	73.5	73
Crank Length (mm)	170	172.5	175	165	172.5	175
Handlebar Width (mm)	400	420	440	380	420	440
Stem Length (mm)	90	100	110	80	100	110
Saddle Width (mm)	155	143	143	155	143	143
Seatpost Length (mm)	330	330	380	330	380	380

SPECS	Specifications subject to change without notice.
SEAT BINDER	Specialized Alloy, 30.8mm
SADDLE	Body Geometry S-Works Power, carbon fiber rails, carbon fiber base
WIRING HARNESS	Custom Specialized wiring harness w/ chargeport
CHARGER	Custom charger, 48V System w/ SL system charger plug
FRAME	FACT 11r carbon, Open Road Geometry, front/rear thru-axles, fully integrated down tube battery, internal cable routing, fender/rack mounts, Boost™ 12x148mm
FORK	Future Shock 2.0 w/ Smooth Boot, Boost™ 12x110mm thru-axle, flat-mount disc
CRANKSET	Praxis Carbon Crank Arms
INNER TUBES	Presta, 48mm valve
FRONT WHEEL	Roval Terra CLX, 30mm inner width carbon rim, 32mm depth, Roval AFD hub, 24h, DT Swiss Aerolite spokes
REAR WHEEL	Roval Terra CLX, 30mm inner width carbon rim, 32mm depth, Roval AFD hub, 24h, DT Swiss Aerolite spokes
SEATPOST	Roval Terra Carbon Seat Post, 20mm Offset
HANDLEBARS	S-Works Carbon Hover Drop 125mm, Reach 75mm, w/Di2 hole
STEM	S-Works Future Stem w/ Integrated Computer mount
FRONT TIRE	S-Works Turbo 700x30 Rapid Air 2BR
REAR TIRE	S-Works Turbo 700x30 Rapid Air 2BR
FRONT BRAKE	SRAM RED eTAP AXS, hydraulic disc
REAR BRAKE	SRAM RED eTAP AXS, hydraulic disc
REAR DERAILLEUR	SRAM Red XPLR eTap AXS
SHIFT LEVERS	SRAM Red eTap AXS
CHAINRINGS	SRAM X-SYNC, 46T
CHAIN	SRAM XX1 Eagle
CASSETTE	SRAM XPLR, XG-1271, 12-speed, 10-44t
UI/REMOTE	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, over-the-air updates, ANT+/Bluetooth®, w/Handlebar remote
MOTOR	Specialized SL 1.1, custom lightweight motor
BATTERY	Specialized SL1-320, fully integrated, 320Wh; 160Wh Range Extender included
TAPE	Supacaz Super Sticky Kush

PART NO.	DESCRIPTION	COLOR	SIZE
98122-0001	CREO SL SW CARBON	REDTNT/SPCTFLR/BLK	XS
98122-0002			S
98122-0003			M
98122-0004			L
98122-0005			XL
98122-0006			XXL

TURBO CREO SL EXPERT



Blue Pearl Over White/Dusty Blue Pearl



Teal Tint/Abalone

We have a long history of developing the world's highest performing road bikes. Tarmac, Venge, Roubaix, Allez, Diverge—each one dominates their respective category, featuring the best technologies in the industry. And while that's a tough palmarès to follow, the Turbo Creo SL redefines e-road bike performance. It's lightweight, smooth, capable, and lively—all with the power to flatten mountains, laugh at headwinds, and go farther than you ever thought possible. It's you, only faster.

- The Creo SL is the lightest e-bike in its class—literally kilograms lighter than the competition. Not only does the lightweight and stiff FACT 11r carbon frame inspire dancing on the pedals and diving into corners, but it also reduces overall system weight and increases the range.
- The lightweight SL 1.1 motor doubles your effort with as much as 240 watts of silent and powerful assistance to amplify your ride. The motor's responsive torque curve delivers power perfectly in-tune with your normal riding cadence and leaves no resistance when riding unassisted.
- Battery anxiety? Not on the Creo SL. With up to 80 miles of range from the internal battery, the Creo SL eats up big miles and long days. Our optional range extender provides up to 40 additional miles of mountain-flattening power.
- By connecting with our Mission Control App, you're able to tune the SL 1.1 motor to your riding style, record rides, and monitor the battery. The app can handle battery management automatically too, ensuring the battery will last as long as you need it to. The motor even has a built-in power meter that transmits to any ANT+ head unit. Don't want to connect? No worries—the Specialized MasterMind TCU on the top tube gives you all the control you need to ride.
- With the Future Shock 2.0, you'll feel a reduction in fatigue and an increase in speed, no matter the terrain. The 2.0 iteration gives you more control via a knob atop the stem. This knob adjusts
- We've learned there can be more difference between two male cyclists than between a male and a female cyclist. Gender alone doesn't provide enough data to specialize. It means that separating bikes as male or female is arbitrary and outdated. With this in mind, we've developed a geometry that's best-fit for all riders—one that's comfortable, snappy, and handles like a dream.

TURBO CREO SL EXPERT	XS	S	M	L	XL	XXL
Stack (mm)	573	575	592	615	643	675
Reach (mm)	363	373	379	384	391	399
Head-Tube Length (mm)	145.5	145.5	163.5	185.5	217	250
Head-Tube Angle (degrees)	71.5	72	72.5	73	73	73
B-B Height (mm)	264.5	264.5	267	267	269.5	269.5
B-B Drop (mm)	80.5	80.5	78	78	75.5	75.5
Trail (mm)	68	60	56	53	53	52
Fork Length (full) (mm)	390	390	390	390	390	390
Fork Rake/Offset (mm)	50	50	50	50	50	50
Front-Center (mm)	586	592	598	605	621	636
Chain-Stay Length (mm)	426	426	426	427	427	428
Wheelbase (mm)	999	1005	1012	1020	1036	1052
Top-Tube Length (horizontal) (mm)	527	539	548	566	581	605
Bike Stand-Over Height (mm)	728	731	759	782	810	840
Seat-Tube Length (mm)	415	447.5	477.5	502.5	527.5	557.5
Seat-Tube Angle (degrees)	74	74	74	73.5	73.5	73
Crank Length (mm)	165	172.5	172.5	175	170	175
Handlebar Width (mm)	380	420	420	440	400	440
Stem Length (mm)	80	100	100	110	90	110
Saddle Width (mm)	155	143	143	143	155	143
Seatpost Length (mm)	330	330	380	380	330	380

SPECS	Specifications subject to change without notice.
SEAT BINDER	Specialized Alloy, 30.8mm
FRONT TIRE	Specialized Turbo Pro, 700x28mm
REAR TIRE	Specialized Turbo Pro, 700x28mm
SADDLE	Body Geometry Power Expert, titanium rails
WIRING HARNESS	Custom Specialized wiring harness w/ chargeport
CHARGER	Custom charger, 48V System w/ SL system charger plug
FRAME	FACT 11r carbon, Open Road Geometry, front/rear thru-axles, fully integrated down tube battery, internal cable routing, fender/rack mounts, Boost™ 12x148mm
FORK	Future Shock 2.0 w/ Smooth Boot, Boost™ 12x110mm thru-axle, flat-mount disc
STEM	Future Stem, Pro
CRANKSET	Praxis Carbon Crank Arms
INNER TUBES	Presta, 48mm valve
FRONT WHEEL	Roval C 38 Disc, carbon, tubeless-ready, 38mm depth, 24h
REAR WHEEL	Roval C 38 Disc, carbon, tubeless-ready, 38mm depth, 24h
SEATPOST	Roval Terra Carbon Seat Post, 20mm Offset
FRONT BRAKE	SRAM RED eTAP AXS, hydraulic disc
REAR BRAKE	SRAM RED eTAP AXS, hydraulic disc
CHAIN	SRAM Rival 12-speed
REAR DERAILLEUR	SRAM Rival XPLR eTap AXS
SHIFT LEVERS	SRAM Rival eTap AXS
CHAINRINGS	SRAM X-SYNC, 46T
CASSETTE	SRAM XPLR, XG-1251, 12-speed, 10-44t
HANDLEBARS	Specialized Hover Expert, Alloy, 125mm Drop, 75mm Reach w/Di2 Hole
UI/REMOTE	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, over-the-air updates, ANT+/Bluetooth®, w/Handlebar remote
MOTOR	Specialized SL 1.1, custom lightweight motor
BATTERY	Specialized SL1-320, fully integrated, 320Wh
TAPE	Supacaz Super Sticky Kush

PART NO.	DESCRIPTION	COLOR	SIZE
98122-3001	CREO SL EXPERT CARBON	BLUGSTPRL/WHT/DSTBLU	XS
98122-3002			S
98122-3003			M
98122-3004			L
98122-3005			XL
98122-3006			XXL
98122-3101	CREO SL EXPERT CARBON	TLTNT/ABLBN	XS
98122-3102			S
98122-3103			M
98122-3104			L
98122-3105			XL
98122-3106			XXL

TURBO CREO SL COMP CARBON



Maroon/Red Tint



Smoke/Light Silver

We have a long history of developing the world's highest performing road bikes. Tarmac, Venge, Roubaix, Allez, Diverge—each one dominates their respective category, featuring the best technologies in the industry. And while that's a tough palmarès to follow, the Turbo Creo SL redefines e-road bike performance. It's lightweight, smooth, capable, and lively—all with the power to flatten mountains, laugh at headwinds, and go farther than you ever thought possible. It's you, only faster.

- The Creo SL is the lightest e-bike in its class—literally kilograms lighter than the competition. Not only does the lightweight and stiff FACT 11r carbon frame inspire dancing on the pedals and diving into corners, but it also reduces overall system weight and increases the range.
- The lightweight SL 1.1 motor doubles your effort with as much as 240 watts of silent and powerful assistance to amplify your ride. The motor's responsive torque curve delivers power perfectly in-tune with your normal riding cadence and leaves no resistance when riding unassisted.
- Battery anxiety? Not on the Creo SL. With up to 80 miles of range from the internal battery, the Creo SL eats up big miles and long days. Our optional range extender provides up to 40 additional miles of mountain-flattening power.
- By connecting with our Mission Control App, you're able to tune the SL 1.1 motor to your riding style, record rides, and monitor the battery. The app can handle battery management automatically too, ensuring the battery will last as long as you need it to. The motor even has a built-in power meter that transmits to any ANT+ head unit. Don't want to connect? No worries—the Specialized MasterMind TCU on the top tube gives you all the control you need to ride.
- With the Future Shock 2.0, you'll feel a reduction in fatigue and an increase in speed, no matter the terrain. The 2.0 iteration gives you more control via a knob atop the stem. This knob adjusts compression from fully-open to stiff, while hydraulically-damped internals control rebound. The new Smooth Boot, top cap, and Future Stem also enhance the aesthetic, so you get a clean transition from head tube to stem.
- We've learned there can be more difference between two male cyclists than between a male and female. Gender alone doesn't provide enough data to specialize. It means that separating bikes as male or female is arbitrary and outdated. With this in mind, we've developed a geometry that's best-fit for all riders—one that's comfortable, snappy, and handles like a dream.

TURBO CREO SL COMP CARBON

	XS	S	M	L	XL	XXL
Stack (mm)	573	575	592	615	643	675
Reach (mm)	363	373	379	384	391	399
Head-Tube Length (mm)	145.5	145.5	163.5	185.5	217	250
Head-Tube Angle (degrees)	71.5	72	72.5	73	73	73
B-B Height (mm)	264.5	264.5	267	267	269.5	269.5
B-B Drop (mm)	80.5	80.5	78	78	75.5	75.5
Trail (mm)	68	60	56	53	53	52
Fork Length (full) (mm)	390	390	390	390	390	390
Fork Rake/Offset (mm)	50	50	50	50	50	50
Front-Center (mm)	586	592	598	605	621	636
Chain-Stay Length (mm)	426	426	426	427	427	428
Wheelbase (mm)	999	1005	1012	1020	1036	1052
Top-Tube Length (horizontal) (mm)	527	539	548	566	581	605
Bike Stand-Over Height (mm)	728	731	759	782	810	840
Seat-Tube Length (mm)	415	447.5	477.5	502.5	527.5	557.5
Seat-Tube Angle (degrees)	74	74	74	73.5	73.5	73
Crank Length (mm)	165	170	172.5	175	172.5	175
Handlebar Width (mm)	380	400	420	440	420	440
Stem Length (mm)	80	90	100	110	100	110
Saddle Width (mm)	155	155	143	143	143	143
Seatpost Length (mm)	330	330	330	380	380	380

SPECS	Specifications subject to change without notice.
SEAT BINDER	Specialized Alloy, 30.8mm
HANDLEBARS	Specialized Hover Comp, Alloy, 125mm Drop, 75mm Reach w/Di2 Hole
REAR TIRE	Specialized Turbo Pro, 700x30mm
FRONT TIRE	Specialized Turbo Pro, 700x30mm
CHAINRINGS	46T
SADDLE	Body Geometry Power Sport, steel rails
WIRING HARNESS	Custom Specialized wiring harness w/ chargeport
CHARGER	Custom charger, 48V System w/ SL system charger plug
FRONT WHEEL	DT R470 Boost, 12x110mm
REAR WHEEL	DT R470 Boost, 12x148mm
FRAME	FACT 11r carbon, Open Road Geometry, front/rear thru-axles, fully integrated down tube battery, internal cable routing, fender/rack mounts, Boost™ 12x148mm
FORK	Future Shock 2.0 w/ Smooth Boot, Boost™ 12x110mm thru-axle, flat-mount disc
STEM	Future Stem, Comp
CHAIN	KMC X11 Extra Lightweight, 11-speed
CRANKSET	Praxis, Forged alloy M30, custom offset
INNER TUBES	Presta, 48mm valve
SEATPOST	Roval Terra Carbon Seat Post, 20mm Offset
REAR BRAKE	Shimano 105, Hydraulic disc
FRONT BRAKE	Shimano 105, Hydraulic disc
SHIFT LEVERS	Shimano GRX 810 hydraulic brake levers, mechanical shifting
REAR DERAILLEUR	Shimano RX812 GX, Shadow Plus, 11-speed
UI/REMOTE	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, over-the-air updates, ANT+/Bluetooth®, w/Handlebar remote
MOTOR	Specialized SL 1.1, custom lightweight motor
BATTERY	Specialized SL1-320, fully integrated, 320Wh
CASSETTE	Sunrace, 11-speed, alloy spider, 11-42t
TAPE	Supacaz Super Sticky Kush

PART NO.	DESCRIPTION	COLOR	SIZE
98122-5001	CREO SL COMP CARBON	MRN/REDTNT	XS
98122-5002			S
98122-5003			M
98122-5004			L
98122-5005			XL
98122-5006			XXL
98122-5101	CREO SL COMP CARBON	SMK/LTSIL	XS
98122-5102			S
98122-5103			M
98122-5104			L
98122-5105			XL
98122-5106			XXL

TURBO CREO SL COMP E5



Cast Umber/Clay



Dove Grey/Smoke



Tarmac Black/Metallic White Silver

We have a long history of developing the world's highest performing road bikes. Tarmac, Venge, Roubaix, Allez, Diverge—each one dominates their respective category, featuring the best technologies in the industry. And while that's a tough palmarès to follow, the Turbo Creo SL redefines e-road bike performance. It's lightweight, smooth, capable, and lively—all with the power to flatten mountains, laugh at headwinds, and go farther than you ever thought possible. It's you, only faster.

- The Creo SL is the lightest e-bike in its class—literally kilograms lighter than the competition. Not only does the lightweight and stiff, premium E5 alloy frame inspire dancing on the pedals and diving into corners, it also reduces overall system weight and increases the range.
- The lightweight SL 1.1 motor doubles your effort with as much as 240 watts of silent and powerful assistance to amplify your ride. The motor's responsive torque curve delivers power perfectly in-tune with your normal riding cadence and leaves no resistance when riding unassisted.
- Battery anxiety? Not on the Creo SL. With up to 80 miles of range from the internal battery, the Creo SL eats up big miles and long days. Our optional range extender provides up to 40 additional miles of mountain-flattening power.
- By connecting with our Mission Control App, you're able to tune the SL 1.1 motor to your riding style, record rides, and monitor the battery. The app can handle battery management automatically too, ensuring the battery will last as long as you need it to. The motor even has a built-in power meter that transmits to any ANT+ head unit. Don't want to connect? No worries— the Turbo Connect Unit (TCU) on the top tube gives you all the control you need to ride.
- With 20mm of rough-road-taming travel, the Future Shock 1.5 not only delivers a smoother, more comfortable ride, but it also reduces fatigue and increases speed over harsh terrain. The new Smooth Boot, meanwhile, enhances the aesthetics to bring a clean transition from the head tube to the stem.
- We've learned there can be more difference between two male cyclists than between a male and a female cyclist. Gender alone doesn't provide enough data to specialize. It means that separating bikes as male or female is arbitrary and outdated. With this in mind, we've developed a geometry that's best-fit for all riders—one that's comfortable, snappy, and handles like a dream.

TURBO CREO SL COMP E5	S	M	L	XL	XXL
Head-Tube Length (mm)	145.5	163.5	185.5	217	250
Wheelbase (mm)	1005	1012	1020	1036	1052
Seat-Tube Length (mm)	502.5	527.5	557.5	447.5	477.5
Fork Length (full) (mm)	390	390	390	390	390
Seat-Tube Angle (degrees)	74	74	73.5	73.5	73
Stack (mm)	575	592	615	643	675
B-B Drop (mm)	80.5	78	78	75.5	75.5
Trail (mm)	60	56	53	53	52
Front-Center (mm)	592	598	605	621	636
Top-Tube Length (horizontal) (mm)	539	548	566	581	605
Bike Stand-Over Height (mm)	731	759	782	810	840
Reach (mm)	373	379	384	391	399
Head-Tube Angle (degrees)	72	72.5	73	73	73
B-B Height (mm)	264.5	267	267	269.5	269.5
Fork Rake/Offset (mm)	50	50	50	50	50
Chain-Stay Length (mm)	426	426	427	427	428
Crank Length (mm)	170	172.5	175	172.5	175
Handlebar Width (mm)	400	420	440	420	440
Stem Length (mm)	90	100	110	100	110
Saddle Width (mm)	155	143	143	143	143
Seatpost Length (mm)	350	350	400	400	400

SPECS	Specifications subject to change without notice.
FRAME	Specialized E5 Premium Aluminum frame, Open Road Geometry, front/rear thru-axes, fully integrated down tube battery, internal cable routing, fender/rack mounts, Boost™ 12x148mm
FORK	Future Shock 1.5 w/ Smooth Boot, Boost™ 12x110mm thru-axle, flat-mount disc
STEM	Future Stem, Comp
HANDLEBARS	Specialized Hover Comp, Alloy, 125mm Drop, 75mm Reach w/Di2 Hole
TAPE	Roubaix S-Wrap
FRONT BRAKE	Shimano 105, Hydraulic disc
REAR BRAKE	Shimano 105, Hydraulic disc
REAR DERAILLEUR	Shimano RX812 GX, Shadow Plus, 11-speed
SHIFT LEVERS	Shimano GRX 810 hydraulic brake levers, mechanical shifting
CASSETTE	Sunrace, 11-speed, alloy spider, 11-42t
CHAIN	KMC X11 Extra Lightweight, 11-speed
CRANKSET	Praxis, Forged alloy M30, custom offset
CHAINRINGS	46T
FRONT WHEEL	DT R470 Boost, 12x110mm
REAR WHEEL	DT R470 Boost, 12x148mm
FRONT TIRE	Specialized Turbo Pro, 700x28mm
REAR TIRE	Specialized Turbo Pro, 700x28mm
INNER TUBES	Presta valve, 48mm
SADDLE	Body Geometry Power Sport, steel rails
SEATPOST	Carbon, single-bolt, 27.2mm
SEAT BINDER	Alloy, 30.8mm
MOTOR	Specialized SL 1.1, custom lightweight motor
UI/REMOTE	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®, w/Handlebar remote
BATTERY	Specialized SL1-320, fully integrated, 320Wh
CHARGER	Custom charger, 48V System w/ SL system charger plug
WIRING HARNESS	Custom Specialized wiring harness w/ chargeport

PART NO.	DESCRIPTION	COLOR	SIZE
98122-5202	CREO SL E5 COMP	CSTUMBR/CLY	S
98122-5203			M
98122-5204			L
98122-5205			XL
98122-5206			XXL
98122-5302	CREO SL E5 COMP	DOVGRY/SMK	S
98122-5303			M
98122-5304			L
98122-5305			XL
98122-5306			XXL
98122-5402	CREO SL E5 COMP	TARBLK/METWHTSIL	S
98122-5403			M
98122-5404			L
98122-5405			XL
98122-5406			XXL

CREO SL EVO

S-WORKS TURBO CREO SL EVO



Brushed/Smoked Liquid Metal/Black Liquid Metal

What is it about gravel that's so appealing? Is it the break from hectic city streets and cars? Is it the audible crunch of rocks beneath your tires? Or maybe it's just the feeling of adventure? Whatever it is, the Turbo Creo SL EVO is here to assist you further into the forest, down the gravel road, or on your next adventure. It features the same motor, battery, and frame as its road-oriented cousin, but takes advantage of tire clearance and adds in some adventure-ready components to take you wherever your heart desires. It's you, only faster.

- The Creo SL is the lightest e-bike in its class—literally kilograms lighter than the competition. Not only does the lightweight and stiff FACT 11r carbon frame inspire dancing on the pedals and diving into corners, but it also reduces overall system weight and increases the range.
- The lightweight SL 1.1 motor doubles your effort with as much as 240 watts of silent and powerful assistance to amplify your ride. The motor's responsive torque curve delivers power perfectly in-tune with your normal riding cadence and leaves no resistance when riding unassisted.
- Battery anxiety? Not on the Creo SL. With up to 80 miles of range from the internal battery, the Creo SL eats up big miles and long days. Our optional range extender provides up to 40 additional miles of mountain-flattening power.
- By connecting with our Mission Control App, you're able to tune the SL 1.1 motor to your riding style, record rides, and monitor the battery. The app can handle battery management automatically too, ensuring the battery will last as long as you need it to. The motor even has a built-in power meter that transmits to any ANT+ head unit. Don't want to connect? No worries—the Specialized MasterMind TCU on the top tube gives you all the control you need to ride.
- With the Future Shock 2.0, you'll feel a reduction in fatigue and an increase in speed, no matter the terrain. The 2.0 iteration gives you more control via a knob atop the stem. This knob adjusts compression from fully-open to stiff, while hydraulically-damped internals control rebound. The new Smooth Boot, top cap, and Future Stem also enhance the aesthetic, so you get a clean transition from head tube to stem.
- We've learned there can be more difference between two male cyclists than between a male and female. Gender alone doesn't provide enough data to specialize. It means that separating bikes as male or female is arbitrary and outdated. With this in mind, we've developed a geometry that's best-fit for all riders. One that's comfortable and snappy on the road, yet features all of the attributes you'd want from a proper gravel bike—a long wheelbase, raked-out fork, and low bottom bracket that keeps the Turbo Creo SL EVO stable at high speeds and delivers control in corners.

S-WORKS TURBO CREO SL EVO

	XS	S	M	L	XL	XXL
Stack (mm)	573	575	592	615	643	675
Reach (mm)	363	373	379	384	391	399
Head-Tube Length (mm)	145.5	145.5	163.5	185.5	217	250
Head-Tube Angle (degrees)	71.5	72	72.5	73	73	73
B-B Height (mm)	264.5	264.5	267	267	269.5	269.5
B-B Drop (mm)	80.5	80.5	78	78	75.5	75.5
Trail (mm)	68	60	56	53	53	52
Fork Length (full) (mm)	390	390	390	390	390	390
Fork Rake/Offset (mm)	50	50	50	50	50	50
Front-Center (mm)	586	592	598	605	621	636
Chain-Stay Length (mm)	426	426	426	427	427	428
Wheelbase (mm)	999	1005	1012	1020	1036	1052
Top-Tube Length (horizontal) (mm)	527	539	548	566	581	605
Bike Stand-Over Height (mm)	728	731	759	782	810	840
Seat-Tube Length (mm)	415	447.5	477.5	502.5	527.5	557.5
Seat-Tube Angle (degrees)	74	74	74	73.5	73.5	73
Crank Length (mm)	165	172.5	172.5	175	170	175
Handlebar Width (mm)	380	420	420	440	400	440
Stem Length (mm)	80	100	100	110	90	110
Saddle Width (mm)	155	143	143	143	155	143
Seatpost Length (mm)	350	350	400	400	350	400

SPECS	Specifications subject to change without notice.
SEAT BINDER	Specialized Alloy, 30.8mm
SADDLE	Body Geometry S-Works Power, carbon fiber rails, carbon fiber base
WIRING HARNESS	Custom Specialized wiring harness w/ chargeport
CHARGER	Custom charger, 48V System w/ SL system charger plug
FRAME	FACT 11r carbon, Open Road Geometry, front/rear thru-axles, fully integrated down tube battery, internal cable routing, fender/rack mounts, Boost™ 12x148mm
FORK	Future Shock 2.0 w/ Smooth Boot, Boost™ 12x110mm thru-axle, flat-mount disc
FRONT TIRE	Pathfinder Pro 2Bliss Ready, Transparent Sidewall, 700x38c
REAR TIRE	Pathfinder Pro 2Bliss Ready, Transparent Sidewall, 700x38c
CRANKSET	Praxis Carbon Crank Arms
INNER TUBES	Presta valve, 48mm
SEATPOST	RockShox Reverb AXS, 27.2mm
REAR WHEEL	Roval Terra CLX, 30mm inner width carbon rim, 32mm depth, Roval AFD hub, 24h, DT Swiss Aerolite spokes
FRONT WHEEL	Roval Terra CLX, 30mm inner width carbon rim, 32mm depth, Roval AFD hub, 24h, DT Swiss Aerolite spokes
HANDLEBARS	Roval Terra, carbon, 103mm drop x 70mm reach x 12° flare
STEM	S-Works Future Stem w/ Integrated Computer mount
REAR BRAKE	SRAM RED eTAP AXS, hydraulic disc
FRONT BRAKE	SRAM RED eTAP AXS, hydraulic disc
SHIFT LEVERS	SRAM Red eTap AXS
CHAINRINGS	SRAM X-SYNC, 44T
CHAIN	SRAM XX1 Eagle
CASSETTE	SRAM XG-1295 Eagle, 12-speed, 10-50t
REAR DERAILLEUR	SRAM XX1 Eagle AXS
UI/REMOTE	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, over-the-air updates, ANT+/Bluetooth®, w/Handlebar remote
MOTOR	Specialized SL 1.1, custom lightweight motor
BATTERY	Specialized SL1-320, fully integrated, 320Wh; 160Wh Range Extender included
TAPE	Supacaz Super Sticky Kush

PART NO.	DESCRIPTION	COLOR	SIZE
98122-0101	CREO SL SW CARBON EVO	BRSH/SMKLDQMET/BLK/BLK	XS
98122-0102		QDQMET	S
98122-0103			M
98122-0104			L
98122-0105			XL
98122-0106			XXL

TURBO CREO SL EXPERT EVO



SATIN GUN WHITE MOUNTAIN

What is it about gravel that's so appealing? Is it the break from hectic city streets and cars? Is it the audible crunch of rocks beneath your tires? Or maybe it's just the feeling of adventure? Whatever it is, the Turbo Creo SL EVO is here to assist you further into the forest, down the gravel road, or on your next adventure. It features the same motor, battery, and frame as its road-oriented cousin, but takes advantage of tire clearance and adds in some adventure-ready components to take you wherever your heart desires. It's you, only faster.

- The Creo SL is the lightest e-bike in its class—literally kilograms lighter than the competition. Not only does the lightweight and stiff FACT 11r carbon frame inspire dancing on the pedals and diving into corners, but it also reduces overall system weight and increases the range.
- The lightweight SL 1.1 motor doubles your effort with as much as 240 watts of silent and powerful assistance to amplify your ride. The motor's responsive torque curve delivers power perfectly in-tune with your normal riding cadence and leaves no resistance when riding unassisted.
- Battery anxiety? Not on the Creo SL. With up to 80 miles of range from the internal battery, the Creo SL eats up big miles and long days. Our optional range extender provides up to 40 additional miles of mountain-flattening power.
- By connecting with our Mission Control App, you're able to tune the SL 1.1 motor to your riding style, record rides, and monitor the battery. The app can handle battery management automatically too, ensuring the battery will last as long as you need it to. The motor even has a built-in power meter that transmits to any ANT+ head unit. Don't want to connect? No worries—the Specialized MasterMind TCU on the top tube gives you all the control you need to ride.
- With the Future Shock 2.0, you'll feel a reduction in fatigue and an increase in speed, no matter the terrain. The 2.0 iteration gives you more control via a knob atop the stem. This knob adjusts compression from fully-open to stiff, while hydraulically-damped internals control rebound. The new Smooth Boot, top cap, and Future Stem also enhance the aesthetic, so you get a clean transition from head tube to stem.
- We've learned there can be more difference between two male cyclists than between a male and female. Gender alone doesn't provide enough data to specialize. It means that separating bikes as male or female is arbitrary and outdated. With this in mind, we've developed a geometry that's best-fit for all riders. One that's comfortable and snappy on the road, yet features all of the attributes you'd want from a proper gravel bike—a long wheelbase, raked-out fork, and low bottom bracket that keeps the Turbo Creo SL EVO stable at high speeds and delivers control in corners.

TURBO CREO SL EXPERT EVO	XS	S	M	L	XL	XXL
Stack (mm)	573	575	592	615	643	675
Reach (mm)	363	373	379	384	391	399
Head-Tube Length (mm)	145.5	145.5	163.5	185.5	217	250
Head-Tube Angle (degrees)	71.5	72	72.5	73	73	73
B-B Height (mm)	264.5	264.5	267	267	269.5	269.5
B-B Drop (mm)	80.5	80.5	78	78	75.5	75.5
Trail (mm)	68	60	56	53	53	52
Fork Length (full) (mm)	390	390	390	390	390	390
Fork Rake/Offset (mm)	50	50	50	50	50	50
Front-Center (mm)	586	592	598	605	621	636
Chain-Stay Length (mm)	426	426	426	427	427	428
Wheelbase (mm)	999	1005	1012	1020	1036	1052
Top-Tube Length (horizontal) (mm)	527	539	548	566	581	605
Bike Stand-Over Height (mm)	728	731	759	782	810	840
Seat-Tube Length (mm)	415	447.5	477.5	502.5	527.5	557.5
Seat-Tube Angle (degrees)	74	74	74	73.5	73.5	73
Crank Length (mm)	165	170	172.5	172.5	175	175
Handlebar Width (mm)	380	400	420	420	440	440
Stem Length (mm)	80	90	100	100	110	110
Saddle Width (mm)	155	155	143	143	143	143
Seatpost Length (mm)	350	350	350	400	400	400

SPECS	Specifications subject to change without notice.
SEAT BINDER	Specialized Alloy, 30.8mm
SADDLE	Body Geometry Power Expert, titanium rails
WIRING HARNESS	Custom Specialized wiring harness w/ chargeport
CHARGER	Custom charger, 48V System w/ SL system charger plug
FRAME	FACT 11r carbon, Open Road Geometry, front/rear thru-axles, fully integrated down tube battery, internal cable routing, fender/rack mounts, Boost™ 12x148mm
FORK	Future Shock 2.0 w/ Smooth Boot, Boost™ 12x110mm thru-axle, flat-mount disc
STEM	Future Stem, Pro
REAR TIRE	Pathfinder Pro 2Bliss Ready, Transparent Sidewall, 700x38c
FRONT TIRE	Pathfinder Pro 2Bliss Ready, Transparent Sidewall, 700x38c
CRANKSET	Praxis Carbon Crank Arms
INNER TUBES	Presta, 48mm valve
FRONT WHEEL	Roval C 38 Disc, carbon, tubeless-ready, 38mm depth, 24h
REAR WHEEL	Roval C 38 Disc, carbon, tubeless-ready, 38mm depth, 24h
REAR DERAILLEUR	SRAM GX1 Eagle
CASSETTE	SRAM NX Eagle PG-1230, 12-speed, 11-50t
REAR BRAKE	SRAM RED eTAP AXS, hydraulic disc
FRONT BRAKE	SRAM RED eTAP AXS, hydraulic disc
SHIFT LEVERS	SRAM Rival eTap AXS
CHAINRINGS	SRAM X-SYNC, 44T
CHAIN	SRAM, NX Eagle, 12-speed
HANDLEBARS	Specialized Adventure Gear Hover, 103mm drop x 70mm reach x 12° flare
UI/REMOTE	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, over-the-air updates, ANT+/Bluetooth®, w/Handlebar remote
MOTOR	Specialized SL 1.1, custom lightweight motor
BATTERY	Specialized SL1-320, fully integrated, 320Wh
TAPE	Supacaz Super Sticky Kush
SEATPOST	X-Fusion Manic Dropper, 50mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
98122-3201	CREO SL EXPERT CARBON	GUN/WHTMTN	XS
98122-3202			S
98122-3203			M
98122-3204			L
98122-3205			XL
98122-3206			XXL

TURBO CREO SL COMP CARBON EVO



Carbon/Oak Green Metallic



White Sage/Smoke

What is it about gravel that's so appealing? Is it the break from hectic city streets and cars? Is it the audible crunch of rocks beneath your tires? Or maybe it's just the feeling of adventure? Whatever it is, the Turbo Creo SL EVO is here to assist you further into the forest, down the gravel road, or on your next adventure. It features the same motor, battery, and frame as its road-oriented cousin, but takes advantage of tire clearance and adds in some adventure-ready components to take you wherever your heart desires. It's you, only faster.

- The Creo SL is the lightest e-bike in its class—literally kilograms lighter than the competition. Not only does the lightweight and stiff FACT 11r carbon frame inspire dancing on the pedals and diving into corners, but it also reduces overall system weight and increases the range.
- The lightweight SL 1.1 motor doubles your effort with as much as 240 watts of silent and powerful assistance to amplify your ride. The motor's responsive torque curve delivers power perfectly in-tune with your normal riding cadence and leaves no resistance when riding unassisted.
- Battery anxiety? Not on the Creo SL. With up to 80 miles of range from the internal battery, the Creo SL eats up big miles and long days. Our optional range extender provides up to 40 additional miles of mountain-flattening power.
- By connecting with our Mission Control App, you're able to tune the SL 1.1 motor to your riding style, record rides, and monitor the battery. The app can handle battery management automatically too, ensuring the battery will last as long as you need it to. The motor even has a built-in power meter that transmits to any ANT+ head unit. Don't want to connect? No worries—the Specialized MasterMind TCU on the top tube gives you all the control you need to ride.
- With the Future Shock 2.0, you'll feel a reduction in fatigue and an increase in speed, no matter the terrain. The 2.0 iteration gives you more control via a knob atop the stem. This knob adjusts compression from fully-open to stiff, while hydraulically-damped internals control rebound. The new Smooth Boot, top cap, and Future Stem also enhance the aesthetic, so you get a clean transition from head tube to stem.
- We've learned there can be more difference between two male cyclists than between a male and female. Gender alone doesn't provide enough data to specialize. It means that separating bikes as male or female is arbitrary and outdated. With this in mind, we've developed a geometry that's best-fit for all riders. One that's comfortable and snappy on the road, yet features all of the attributes you'd want from a proper gravel bike—a long wheelbase, raked-out fork, and low bottom bracket that keeps the Turbo Creo SL EVO stable at high speeds and delivers control in corners.

TURBO CREO SL COMP CARBON EVO

	XS	S	M	L	XL	XXL
Stack (mm)	573	575	592	615	643	675
Reach (mm)	363	373	379	384	391	399
Head-Tube Length (mm)	145.5	145.5	163.5	185.5	217	250
Head-Tube Angle (degrees)	71.5	72	72.5	73	73	73
B-B Height (mm)	264.5	264.5	267	267	269.5	269.5
B-B Drop (mm)	80.5	80.5	78	78	75.5	75.5
Trail (mm)	68	60	56	53	53	52
Fork Length (full) (mm)	390	390	390	390	390	390
Fork Rake/Offset (mm)	50	50	50	50	50	50
Front-Center (mm)	586	592	598	605	621	636
Chain-Stay Length (mm)	426	426	426	427	427	428
Wheelbase (mm)	999	1005	1012	1020	1036	1052
Top-Tube Length (horizontal) (mm)	527	539	548	566	581	605
Bike Stand-Over Height (mm)	728	731	759	782	810	840
Seat-Tube Length (mm)	415	447.5	477.5	502.5	527.5	557.5
Seat-Tube Angle (degrees)	74	74	74	73.5	73.5	73
Crank Length (mm)	165	170	172.5	175	172.5	175
Handlebar Width (mm)	380	400	420	440	420	440
Stem Length (mm)	80	90	100	110	100	110
Saddle Width (mm)	155	155	143	143	143	143
Seatpost Length (mm)	350	350	400	400	350	400

SPECS	Specifications subject to change without notice.
SEAT BINDER	Specialized Alloy, 30.8mm
CHAINRINGS	44T
SADDLE	Body Geometry Power Sport, hollow Cr-Mo rails
WIRING HARNESS	Custom Specialized wiring harness w/ chargeport
CHARGER	Custom charger, 48V System w/ SL system charger plug
FRONT WHEEL	DT R470 Boost, 12x110mm
REAR WHEEL	DT R470 Boost, 12x148mm
FRAME	FACT 11r carbon, Open Road Geometry, front/rear thru-axles, fully integrated down tube battery, internal cable routing, fender/rack mounts, Boost™ 12x148mm
FORK	Future Shock 2.0 w/ Smooth Boot, Boost™ 12x110mm thru-axle, flat-mount disc
STEM	Future Stem, Pro
FRONT TIRE	Pathfinder Pro 2Bliss Ready, Transparent Sidewall, 700x38c
REAR TIRE	Pathfinder Pro 2Bliss Ready, Transparent Sidewall, 700x38c
CRANKSET	Praxis, Forged alloy M30, custom offset
INNER TUBES	Presta valve, 48mm
TAPE	Roubaix S-Wrap
REAR BRAKE	Shimano 105, Hydraulic disc
FRONT BRAKE	Shimano 105, Hydraulic disc
SHIFT LEVERS	Shimano GRX 810 hydraulic brake levers, mechanical shifting
CHAIN	Shimano HG601, 11spd
REAR DERAILLEUR	Shimano RX812 GX, Shadow Plus, 11-speed
HANDLEBARS	Specialized Adventure Gear Hover, 103mm drop x 70mm reach x 12° flare
UI/REMOTE	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, over-the-air updates, ANT+/Bluetooth®, w/Handlebar remote
MOTOR	Specialized SL 1.1, custom lightweight motor
BATTERY	Specialized SL1-320, fully integrated, 320Wh
CASSETTE	Sunrace, 11-speed, alloy spider, 11-42t
SEATPOST	X-Fusion Manic Dropper, 50mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
98122-5501	CREO SL COMP CARBON	CARB/OAKGRNMET	XS
98122-5502			S
98122-5503			M
98122-5504			L
98122-5505			XL
98122-5506			XXL
98122-5601	CREO SL COMP CARBON	WHTSGE/SMK	XS
98122-5602			S
98122-5603			M
98122-5604			L
98122-5605			XL
98122-5606			XXL

TERO

TURBO TERO 5.0



Red Onyx / Smoke

The new Turbo Tero is an electric mountain bike equipped for everyday rides. A mountain bike that you can commute on. A commuter you can take touring. A touring bike that you can haul freight with. Whatever you need it to be, for wherever you want to go. A true do-it-all superhero, Tero combines adaptable utility with World Champion mountain bike DNA and category-leading electric pedal assist.

- Turbo Full Power 2.2 Motor and 710 Wh Battery- Integrated into the aluminum frame of the Tero 5.0, they effectively quadruple your own power, cranking out ample wattage to make short work of the steepest climbs and providing enough extra muscle to let you carry a mountain of adventure gear, groceries, kids and daydreams without breaking a sweat. It's you, only faster. But what really sets this motor apart from the rest is how efficiently and seamlessly it melds with your own efforts.
- Mission Control and MasterMind- Mission Control allows you to tailor Tero's power output levels to your desired preference—all three standard power modes can be almost infinitely adjusted to suit your power and range needs. MasterMind's MicroTune function can adjust power output levels in 10% increments so that you can tune the range to suit your needs.
- Mountain Bike DNA- Tero's componentry is tailored to enhance control and confidence. Aggressive but smooth rolling 29" wheels with 2.3" Ground Control tires offer ample traction in every situation, SRAM disc brakes deliver substantial braking bite, 110 mm of front suspension travel smooths the trail, and a dropper seatpost is there for when you need to really get down in technical off-road situations.
- Turbo System Lock - Use the Mission Control app to disable your bike's motor and activate the motion sensor alarm. Once locked, the motor cannot be enabled again except by the owner.
- Fender, Rack, and Kickstand mounts. Rated to pull a thru-axle trailer. Child seat compatible.

TURBO TERO 5.0	S	M	L	XL
Stack (mm)	637	651	664	687
Reach (mm)	405	426	446	462
Headtube Length (mm)	135	150	165	190
Headtube Angle (°)	66.4	66.4	66.4	66.4
BB Height (mm)	313	313	313	313
BB Drop (mm)	57	57	57	57
Trail (mm)	114	114	114	114
Fork Length (full) (mm)	516	516	516	516
Fork Rake/Offset (mm)	44	44	44	44
Front Center (mm)	709	736	761	787
Chainstay Length (mm)	470.4	470.4	470.4	470.4
Wheelbase (mm)	1173	1200	1226	1252
Toptube Length (horizontal) (mm)	589	620	650	680
Bike Standover Height (mm)	773	807	807	835
Seat Tube Length (mm)	400	450	460	500
Seat Tube Angle (Virtual) (°)	73.9	73.4	72.9	72.4
Crank Length (mm)	170			
Seatpost Length (mm)	360			
Stem Length (mm)	60			
Crank Length (mm)	170			
Seatpost Length (mm)	400			
Stem Length (mm)	60			
Crank Length (mm)	170			
Seatpost Length (mm)	400			
Stem Length (mm)	70			
Crank Length (mm)	170			
Seatpost Length (mm)	400			
Stem Length (mm)	70			
Handlebar Width (mm)	720	750	750	750
Saddle Width (mm)	155	155	155	155

SPECS	Specifications subject to change without notice.
Frame	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount
Fork	Rockshox Recon Silver RL, 110mm travel, Motion-Control
Stem	Stout 3D-forged alloy, 31.8mm, 6-degree rise
Handlebars	Specialized Trail, 6061 alloy, 8-degree backsweep, 6-degree upsweep, 27mm rise, 31.8mm clamp, S 720mm, M-XL 750mm
Front Brake	SRAM G2 RS, 4-piston caliper, hydraulic disc, 200mm
Rear Brake	SRAM G2 RS, 4-piston caliper, hydraulic disc, 180mm
Rear Derailleur	SRAM GX, long cage, 11-speed
Shift Levers	SRAM S700, single-click lever
Cassette	SRAM PG-1130, 11-speed, 11-42t
Chain	KMC e11T, 11-speed w/ Missing Link™
Crankset	Custom alloy forged crankarms
Chainrings	Praxis, 36T, 104BCD
Pedals	Specialized platform pedal
Rims	Stout XC 29, 25mm internal width, disc-specific
Front Hub	Specialized alloy front hub disc, sealed cartridge bearings, 6-bolt, 15x110mm thru-axle, 32h
Rear Hub	Specialized alloy rear hub disc, sealed cartridge bearings, 6-bolt, 12x148mm thru-axle, 32h
Spokes	DT Swiss Industry
Front Tire	Ground Control, 2Bliss Ready, 29x2.35"
Rear Tire	Ground Control, 2Bliss Ready, 29x2.35"
Inner Tubes	Presta, 48mm valve
Saddle	Rivo Sport, steel rails, 155mm
SeatPost	TranzX Dropper, 30.9mm, S: 100mm, M-XL: 120mm
Seat Binder	Specialized Alloy, 34.9mm
Motor	Specialized 2.2, 90Nm torque, custom tuned motor, 250W nominal
UI/Remote	MasterMind TCD, w/handlebar remote, built-in anti-theft feature, Bluetooth® connectivity, customizable display pages
Battery	Specialized U2-710, alloy casing, state of charge display, 710Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Wiring Harness	Custom wire harness
SWAT	Specialized Stealth Stem, Display Insert
Bike Lock	Turbo System Lock
Bell	Simple bell

PART NO.	DESCRIPTION	COLOR	SIZE
95123-3102	TERO 5.0 NB	Red Onyx / Smoke	S
95123-3103			M
95123-3104			L
95123-3105			XL

TURBO TERO 5.0



Red Onyx / Smoke

	S	M	L	XL
Stack (mm)	637	651	664	687
Reach (mm)	405	426	446	462
Headtube Length (mm)	135	150	165	190
Headtube Angle (°)	66.4	66.4	66.4	66.4
BB Height (mm)	313	313	313	313
BB Drop (mm)	57	57	57	57
Trail (mm)	114	114	114	114
Fork Length (full) (mm)	516	516	516	516
Fork Rake/Offset (mm)	44	44	44	44
Front Center (mm)	709	736	761	787
Chainstay Length (mm)	470.4	470.4	470.4	470.4
Wheelbase (mm)	1173	1200	1226	1252
Toptube Length (horizontal) (mm)	589	620	650	680
Bike Standover Height (mm)	773	807	807	835
Seat Tube Length (mm)	400	450	460	500
Seat Tube Angle (Virtual) (°)	73.9	73.4	72.9	72.4
Crank Length (mm)	170	170	170	170
Handlebar Width (mm)	720	750	750	750
Stem Length (mm)	60	60	70	70
Saddle Width (mm)	155	155	155	155
Seatpost Length (mm)	360	400	400	400

SPECS	Specifications subject to change without notice.
Frame	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount
Fork	Rockshox Recon Silver RL, 110mm travel, Motion-Control
Stem	Stout 3D-forged alloy, 31.8mm, 6-degree rise
Handlebars	Specialized Trail, 6061 alloy, 8-degree backsweep, 6-degree upsweep, 27mm rise, 31.8mm clamp, S 720mm, M-XL 750mm,
Front Brake	SRAM G2 RS, 4-piston caliper, hydraulic disc, 200mm
Rear Brake	SRAM G2 RS, 4-piston caliper, hydraulic disc, 180mm
Rear Derailleur	SRAM GX, long cage, 11-speed
Shift Levers	SRAM S700, single-click lever
Cassette	SRAM PG-1130, 11-speed, 11-42t
Chain	KMC e11T, 11-speed w/ Missing Link™
Crankset	Custom alloy forged crankarms
Chainrings	40T
Rims	Stout XC 29, 25mm internal width, disc-specific
Front Hub	Alloy, sealed cartridge bearings, 15x110mm thru-axle, 32h
Rear Hub	Alloy, sealed cartridge bearings, 12x148mm thru-axle, 32h
Spokes	DT Swiss Industry
Front Tire	GROUND CONTROL CONTROL 2BR, 29x2.35
Rear Tire	GROUND CONTROL CONTROL 2BR, 29x2.35
Inner Tubes	TUBES, STANDARD 48MM PV LOW LEAD 29x1.75/2.4
Saddle	Bridge Sport, Steel rails, 155mm
SeatPost	TranzX Dropper, 30.9mm, S: 100mm, M-XL: 120mm
Seat Binder	Specialized Alloy, 34.9mm
Motor	TBD
UI/Remote	TBD
Battery	SPECIALIZED U2-710, INTEGRATED BATTERY, 710WH
Charger	Custom charger, 42V4A w/ Rosenberger plug, 230V
Wiring Harness	Custom wire harness
SWAT	Specialized Stealth Stem, Display Insert
Bell	Simple bell

PART NO.	DESCRIPTION	COLOR	SIZE
95122-3102	TERO 5.0 NB	Red Onyx / Smoke	S
95122-3103			M
95122-3104			L
95122-3105			XL

TURBO TERO 4.0 EQ



Black / Black



Redwood / Black

The new Turbo Tero is an electric mountain bike equipped for everyday rides. A mountain bike that you can commute on. A commuter you can take touring. A touring bike that you can haul freight with. Whatever you need it to be, for wherever you want to go. A true do-it-all superhero, Tero combines adaptable utility with World Champion mountain bike DNA and category-leading electric pedal assist.

- Turbo Full Power 2.0 Motor and 710 Wh Battery- Integrated into the aluminum frame of the Tero 4.0, they effectively quadruple your own power, cranking out ample wattage to make short work of the steepest climbs and providing enough extra muscle to let you carry a mountain of adventure gear, groceries, kids and daydreams without breaking a sweat. It's you, only faster. But what really sets this motor apart from the rest is how efficiently and seamlessly it melds with your own efforts.
- Mission Control and MasterMind- Mission Control allows you to tailor Tero's power output levels to your desired preference—all three standard power modes can be almost infinitely adjusted to suit your power and range needs. MasterMind's MicroTune function can adjust power output levels in 10% increments so that you can tune the range to suit your needs.
- Mountain Bike DNA- Tero's componentry is tailored to enhance control and confidence. Aggressive but smooth rolling 29" wheels with 2.3" Ground Control tires offer ample traction in every situation, SRAM disc brakes deliver substantial braking bite, 110 mm of front suspension travel smooths the trail, and a dropper seatpost is there for when you need to really get down in technical off-road situations.
- Turbo System Lock - Use the Mission Control app to disable your bike's motor and activate the motion sensor alarm. Once locked, the motor cannot be enabled again except by the owner.
- Equipped with DRYTECH Fenders, LED front and rear lights, and 27kg capacity rear HD Rack. The rear rack is compatible with child bike seats, and the bike is rated to pull a thru-axle trailer.

TURBO TERO 4.0 EQ	S	M	L	XL
Stack (mm)	637	651	664	687
Reach (mm)	405	426	446	462
Headtube Length (mm)	135	150	165	190
Headtube Angle (°)	66.4	66.4	66.4	66.4
BB Height (mm)	313	313	313	313
BB Drop (mm)	57	57	57	57
Trail (mm)	114	114	114	114
Fork Length (full) (mm)	516	516	516	516
Fork Rake/Offset (mm)	44	44	44	44
Front Center (mm)	709	736	761	787
Chainstay Length (mm)	470.4	470.4	470.4	470.4
Wheelbase (mm)	1173	1200	1226	1252
Toptube Length (horizontal) (mm)	589	620	650	680
Bike Standover Height (mm)	773	807	807	835
Seat Tube Length (mm)	400	450	460	500
Seat Tube Angle (Virtual) (°)	73.9	73.4	72.9	72.4
Crank Length (mm)	170			
Seatpost Length (mm)	360			
Stem Length (mm)	60			
Crank Length (mm)	170			
Seatpost Length (mm)	400			
Stem Length (mm)	60			
Crank Length (mm)	170			
Seatpost Length (mm)	400			
Stem Length (mm)	75			
Crank Length (mm)	170			
Seatpost Length (mm)	400			
Stem Length (mm)	75			
Handlebar Width (mm)	720	750	750	750
Saddle Width (mm)	155	155	155	155

SPECS	Specifications subject to change without notice.
Frame	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount
Fork	Rockshox Recon Silver TK, 110mm travel, Motion-Control
Stem	Specialized Stealth Stem, alloy, 14 deg, 31.8mm, integrated TCD mount
Handlebars	Specialized Trail, 6061 alloy, 8-degree backsweep, 6-degree upsweep, 27mm rise, 31.8mm clamp, S 720mm, M-XL 750mm
Grips	Specialized Body Geometry Contour, lock-on
Front Brake	SRAM Guide T, 4-piston caliper, hydraulic disc, 200mm
Rear Brake	SRAM Guide T, 4-piston caliper, hydraulic disc, 180mm
Rear Derailleur	SRAM NX, 11-speed
Shift Levers	SRAM NX, 11-speed
Cassette	SRAM PG-1130, 11-speed, 11-42t
Chain	KMC e11S, 11-speed w/ Missing Link™
Crankset	Custom alloy forged crankarms
Chainrings	Praxis, 40T, 104BCD
Pedals	Specialized platform pedal
Rims	Stout XC 29, 25mm internal width, disc-specific
Front Hub	Specialized alloy front hub disc, sealed cartridge bearings, 6-bolt, 15x110mm thru-axle, 32h
Rear Hub	Specialized alloy rear hub disc, sealed cartridge bearings, 6-bolt, 12x148mm thru-axle, 32h
Spokes	DT Swiss Industry
Front Tire	Ground Control, 2Bliss Ready, 29x2.35"
Rear Tire	Ground Control, 2Bliss Ready, 29x2.35"
Inner Tubes	Presta, 48mm valve
Saddle	Rivo Sport, steel rails, 155mm
SeatPost	TranzX Dropper, 30.9mm, S: 100mm, M-XL: 120mm
Seat Binder	Alloy, bolt-type, 34.9mm
Motor	Specialized 2.0, 70Nm torque, custom tuned motor, 250W nominal
UI/Remote	MasterMind TCD, w/handlebar remote, built-in anti-theft feature, Bluetooth® connectivity, customizable display pages
Battery	Specialized U2-710, alloy casing, state of charge display, 710Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Wiring Harness	Custom wire harness
SWAT	Specialized Stealth Stem, Display Insert
Headlight	Lezyne EBIKE MINI STVZO E65, 210 Lumen, 12V
Taillight	Spanninga Commuter Glow XE, 12V
Chaincase	Custom chaincover
Kickstand	Specialized kickstand, 40mm mount
Rack	Specialized rack, MIK HD interface, built-in pannier mounts, 27kg max load
Fenders	Specialized DRYTECH fenders, 65mm width, alloy fenderstays
Bike Lock	Turbo System Lock

PART NO.	DESCRIPTION	COLOR	SIZE
95123-5102	TERO 4.0 EQ NB	Black / Black	S
95123-5103			M
95123-5104			L
95123-5105			XL
95123-5202	TERO 4.0 EQ NB	Redwood / Black	S
95123-5203			M
95123-5204			L
95123-5205			XL

TURBO TERO 4.0 EQ



Black / Black



Redwood / Black

	S	M	L	XL
Stack (mm)	637	651	664	687
Reach (mm)	405	426	446	462
Headtube Length (mm)	135	150	165	190
Headtube Angle (°)	66.4	66.4	66.4	66.4
BB Height (mm)	313	313	313	313
BB Drop (mm)	57	57	57	57
Trail (mm)	114	114	114	114
Fork Length (full) (mm)	516	516	516	516
Fork Rake/Offset (mm)	44	44	44	44
Front Center (mm)	709	736	761	787
Chainstay Length (mm)	470.4	470.4	470.4	470.4
Wheelbase (mm)	1173	1200	1226	1252
Toptube Length (horizontal) (mm)	589	620	650	680
Bike Standover Height (mm)	773	807	807	835
Seat Tube Length (mm)	400	450	460	500
Seat Tube Angle (Virtual) (°)	73.9	73.4	72.9	72.4
Crank Length (mm)	170	170	170	170
Handlebar Width (mm)	720	750	750	750
Stem Length (mm)	60	60	75	75
Saddle Width (mm)	155	155	155	155
Seatpost Length (mm)	360	400	400	400

SPECS	Specifications subject to change without notice.
Frame	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount
Fork	Rockshox Recon Silver TK, 110mm travel, Motion-Control
Stem	Specialized Stealth Stem, alloy, 14 deg, 31.8mm, integrated TCD mount
Handlebars	Specialized Trail, 6061 alloy, 8-degree backsweep, 6-degree upsweep, 27mm rise, 31.8mm clamp, S 720mm, M-XL 750mm,
Grips	Specialized Body Geometry Contour, lock-on
Front Brake	SRAM Guide T, 4-piston caliper, hydraulic disc, 200mm
Rear Brake	SRAM Guide T, 4-piston caliper, hydraulic disc, 180mm
Rear Derailleur	SRAM NX, 11-speed
Shift Levers	SRAM NX, 11-speed
Cassette	SRAM PG-1130, 11-speed, 11-42t
Chain	KMC e11S, 11-speed w/ Missing Link™
Crankset	Custom alloy forged crankarms
Chainrings	40T
Rims	Stout XC 29, 25mm internal width, disc-specific
Front Hub	Alloy, sealed cartridge bearings, 15x110mm thru-axle, 32h
Rear Hub	Alloy, sealed cartridge bearings, 12x148mm thru-axle, 32h
Spokes	DT Swiss Industry
Front Tire	GROUND CONTROL CONTROL 2BR, 29x2.35
Rear Tire	GROUND CONTROL CONTROL 2BR, 29x2.35
Inner Tubes	TUBES, STANDARD 48MM PV LOW LEAD 29x1.75/2.4
Saddle	Bridge Sport, Steel rails, 155mm
SeatPost	TranzX Dropper, 30.9mm, S: 100mm, M-XL: 120mm
Seat Binder	Alloy, bolt-type, 34.9mm
Motor	TBD
UI/Remote	TBD
Battery	SPECIALIZED U2-710, INTEGRATED BATTERY, 710WH
Charger	Custom charger, 42V4A w/ Rosenberger plug, 230V
Wiring Harness	Custom wire harness
SWAT	Specialized Stealth Stem, Display Insert
Headlight	LEZYNE, EBIKE MINI STVZO E65, 65LUX 210LUMEN
Taillight	Spanninga Commuter Glow
Chaincase	custom chaincover
Kickstand	Specialized kickstand, 40mm mount
Rack	Specialized rack, MIK HD interface, built-in pannier mounts, 27kg max load
Fenders	Specialized DRYTECH fenders, 65mm width, alloy fenderstays
Bell	Simple bell

PART NO.	DESCRIPTION	COLOR	SIZE
95122-5202	TERO 4.0 EQ NB	Black / Black	S
95122-5203			M
95122-5204			L
95122-5205			XL
95122-5302	TERO 4.0 EQ NB	Redwood / Black	S
95122-5303			M
95122-5304			L
95122-5305			XL

TURBO TERO 4.0 STEP-THROUGH EQ



Black / Black



Redwood / Black

The new Turbo Tero is an electric mountain bike equipped for everyday rides. A mountain bike that you can commute on. A commuter you can take touring. A touring bike that you can haul freight with. Whatever you need it to be, for wherever you want to go. A true do-it-all superhero, Tero combines adaptable utility with World Champion mountain bike DNA and category-leading electric pedal assist.

- Turbo Full Power 2.0 Motor and 710 Wh Battery- Integrated into the aluminum frame of the Tero 4.0, they effectively quadruple your own power, cranking out ample wattage to make short work of the steepest climbs and providing enough extra muscle to let you carry a mountain of adventure gear, groceries, kids and daydreams without breaking a sweat. It's you, only faster. But what really sets this motor apart from the rest is how efficiently and seamlessly it melds with your own efforts.
- Mission Control and MasterMind- Mission Control allows you to tailor Tero's power output levels to your desired preference—all three standard power modes can be almost infinitely adjusted to suit your power and range needs. MasterMind's MicroTune function can adjust power output levels in 10% increments so that you can tune the range to suit your needs.
- Mountain Bike DNA- Tero's componentry is tailored to enhance control and confidence. Aggressive but smooth rolling 29" wheels with 2.3" Ground Control tires offer ample traction in every situation, SRAM disc brakes deliver substantial braking bite, 110 mm of front suspension travel smooths the trail, and a dropper seatpost is there for when you need to really get down in technical off-road situations.
- Turbo System Lock - Use the Mission Control app to disable your bike's motor and activate the motion sensor alarm. Once locked, the motor cannot be enabled again except by the owner.
- Equipped with DRYTECH Fenders, LED front and rear lights, and 27kg capacity rear HD Rack. The rear rack is compatible with child bike seats, and the bike is rated to pull a thru-axle trailer.

TURBO TERO 4.0 STEP-THROUGH EQ

	S	M	L	XL
Stack (mm)	637	651	664	687
Reach (mm)	405	426	446	462
Headtube Length (mm)	135	150	165	190
Headtube Angle (°)	66.4	66.4	66.4	66.4
BB Height (mm)	313	313	313	313
BB Drop (mm)	57	57	57	57
Trail (mm)	114	114	114	114
Fork Length (full) (mm)	516	516	516	516
Fork Rake/Offset (mm)	44	44	44	44
Front Center (mm)	709	736	761	787
Chainstay Length (mm)	470.4	470.4	470.4	470.4
Wheelbase (mm)	1173	1200	1226	1252
Toptube Length (horizontal) (mm)	589	620	650	680
Bike Standover Height (mm)	658	655	655	664
Seat Tube Length (mm)	400	450	460	500
Seat Tube Angle (Virtual) (°)	73.9	73.4	72.9	72.4
Crank Length (mm)	170			
Seatpost Length (mm)	360			
Stem Length (mm)	60			
Crank Length (mm)	170			
Seatpost Length (mm)	400			
Stem Length (mm)	60			
Crank Length (mm)	170			
Seatpost Length (mm)	400			
Stem Length (mm)	75			
Crank Length (mm)	170			
Seatpost Length (mm)	400			
Stem Length (mm)	75			
Handlebar Width (mm)	720	750	750	750

SPECS Specifications subject to change without notice.

Frame	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount
Fork	Rockshox Recon Silver TK, 110mm travel, Motion-Control
Stem	Specialized Stealth Stem, alloy, 14 deg, 31.8mm, integrated TCD mount
Handlebars	Specialized Trail, 6061 alloy, 8-degree backsweep, 6-degree upsweep, 27mm rise, 31.8mm clamp, S 720mm, M-XL 750mm
Grips	Specialized Body Geometry Contour, lock-on
Front Brake	SRAM Guide T, 4-piston caliper, hydraulic disc, 200mm
Rear Brake	SRAM Guide T, 4-piston caliper, hydraulic disc, 180mm
Rear Derailleur	SRAM NX, 11-speed
Shift Levers	SRAM NX, 11-speed
Cassette	SRAM PG-1130, 11-speed, 11-42t
Chain	KMC e11S, 11-speed w/ Missing Link™
Crankset	Custom alloy forged crankarms
Chainrings	Praxis, 40T, 104BCD
Pedals	Specialized platform pedal
Rims	Stout XC 29, 25mm internal width, disc-specific
Front Hub	Specialized alloy front hub disc, sealed cartridge bearings, 6-bolt, 15x110mm thru-axle, 32h
Rear Hub	Specialized alloy rear hub disc, sealed cartridge bearings, 6-bolt, 12x148mm thru-axle, 32h
Spokes	DT Swiss Industry
Front Tire	Ground Control, 2Bliss Ready, 29x2.35"
Rear Tire	Ground Control, 2Bliss Ready, 29x2.35"
Inner Tubes	Presta, 48mm valve
Saddle	Rivo Sport, steel rails, 155mm
SeatPost	TranzX Dropper, 30.9mm, S: 100mm, M-XL: 120mm
Seat Binder	Alloy, bolt-type, 34.9mm
Motor	Specialized 2.0, 70Nm torque, custom tuned motor, 250W nominal
UI/Remote	MasterMind TCD, w/handlebar remote, built-in anti-theft feature, Bluetooth® connectivity, customizable display pages
Battery	Specialized U2-710, alloy casing, state of charge display, 710Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Wiring Harness	Custom wire harness
SWAT	Specialized Stealth Stem, Display Insert
Headlight	Lezyne EBIKE MINI STVZO E65, 210 Lumen, 12V
Taillight	Spanninga Commuter Glow XE, 12V
Chaincase	Custom chaincover
Kickstand	Specialized kickstand, 40mm mount
Rack	Specialized rack, MIK HD interface, built-in pannier mounts, 27kg max load
Fenders	Specialized DRYTECH fenders, 65mm width, alloy fenderstays
Bike Lock	Turbo System Lock

PART NO.	DESCRIPTION	COLOR	SIZE
95123-5402	TERO 4.0 ST EQ NB	Black / Black	S
95123-5403			M
95123-5404			L
95123-5405			XL
95123-5502	TERO 4.0 ST EQ NB	Redwood / Black	S
95123-5503			M
95123-5504			L
95123-5505			XL

TURBO TERO 4.0 STEP-THROUGH EQ



Black / Black



Redwood / Black

	S	M	L	XL
Stack (mm)	637	651	664	687
Reach (mm)	405	426	446	462
Headtube Length (mm)	135	150	165	190
Headtube Angle (°)	66.4	66.4	66.4	66.4
BB Height (mm)	313	313	313	313
BB Drop (mm)	57	57	57	57
Trail (mm)	114	114	114	114
Fork Length (full) (mm)	516	516	516	516
Fork Rake/Offset (mm)	44	44	44	44
Front Center (mm)	709	736	761	787
Chainstay Length (mm)	470.4	470.4	470.4	470.4
Wheelbase (mm)	1173	1200	1226	1252
Toptube Length (horizontal) (mm)	589	620	650	680
Bike Standover Height (mm)	658	655	655	664
Seat Tube Length (mm)	400	450	460	500
Seat Tube Angle (Virtual) (°)	73.9	73.4	72.9	72.4
Crank Length (mm)	170	170	170	170
Handlebar Width (mm)	720	750	750	750
Stem Length (mm)	60	60	75	75
Saddle Width (mm)	155	155	155	155
Seatpost Length (mm)	360	400	400	400

SPECS	Specifications subject to change without notice.
Frame	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount
Fork	Rockshox Recon Silver TK, 110mm travel, Motion-Control
Stem	Specialized Stealth Stem, alloy, 14 deg, 31.8mm, integrated TCD mount
Handlebars	Specialized Trail, 6061 alloy, 8-degree backsweep, 6-degree upsweep, 27mm rise, 31.8mm clamp, S 720mm, M-XL 750mm,
Grips	Body Geometry Women's Contour
Front Brake	SRAM Guide T, 4-piston caliper, hydraulic disc, 200mm
Rear Brake	SRAM Guide T, 4-piston caliper, hydraulic disc, 180mm
Rear Derailleur	SRAM NX, 11-speed
Shift Levers	SRAM NX, 11-speed
Cassette	SRAM PG-1130, 11-speed, 11-42t
Chain	KMC e11S, 11-speed w/ Missing Link™
Crankset	Custom alloy forged crankarms
Chainrings	40T
Rims	Stout XC 29, 25mm internal width, disc-specific
Front Hub	Alloy, sealed cartridge bearings, 15x110mm thru-axle, 32h
Rear Hub	Alloy, sealed cartridge bearings, 12x148mm thru-axle, 32h
Spokes	DT Swiss Industry
Front Tire	GROUND CONTROL CONTROL 2BR, 29x2.35
Rear Tire	GROUND CONTROL CONTROL 2BR, 29x2.35
Inner Tubes	TUBES, STANDARD 48MM PV 29x1.75/2.4
Saddle	Bridge Sport, Steel rails, 155mm
SeatPost	TranzX Dropper, 30.9mm, S: 100mm, M-XL: 120mm
Seat Binder	Alloy, bolt-type, 34.9mm
Motor	TBD
UI/Remote	TBD
Battery	SPECIALIZED U2-710, INTEGRATED BATTERY, 710WH
Charger	Custom charger, 42V4A w/ Rosenberger plug, 230V
Wiring Harness	Custom wire harness
SWAT	Specialized Stealth Stem, Display Insert
Headlight	LEZYNE, EBIKE MINI STVZO E65, 65LUX 210LUMEN
Taillight	Spanninga Commuter Glow
Chaincase	custom chaincover
Kickstand	Specialized kickstand, 40mm mount
Rack	Specialized rack, MIK HD interface, built-in pannier mounts, 27kg max load
Fenders	Specialized DRYTECH fenders, 65mm width, alloy fenderstays
Bell	Simple bell

PART NO.	DESCRIPTION	COLOR	SIZE
95122-6202	TERO 4.0 STEP THROUGH EQ NB	Black / Black	S
95122-6203			M
95122-6204			L
95122-6205			XL
95122-6302			S
95122-6303			M
95122-6304			L
95122-6305			XL

TURBO TERO 4.0



Black / Black

The new Turbo Tero is an electric mountain bike equipped for everyday rides. A mountain bike that you can commute on. A commuter you can take touring. A touring bike that you can haul freight with. Whatever you need it to be, for wherever you want to go. A true do-it-all superhero, Tero combines adaptable utility with World Champion mountain bike DNA and category-leading electric pedal assist.

- **Turbo Full Power 2.0 Motor and 710 Wh Battery**- Integrated into the aluminum frame of the Tero 4.0, they effectively quadruple your own power, cranking out ample wattage to make short work of the steepest climbs and providing enough extra muscle to let you carry a mountain of adventure gear, groceries, kids and daydreams without breaking a sweat. It's you, only faster. But what really sets this motor apart from the rest is how efficiently and seamlessly it melds with your own efforts.
- **Mission Control and MasterMind**- Mission Control allows you to tailor Tero's power output levels to your desired preference—all three standard power modes can be almost infinitely adjusted to suit your power and range needs. MasterMind's MicroTune function can adjust power output levels in 10% increments so that you can tune the range to suit your needs.
- **Mountain Bike DNA**- Tero's componentry is tailored to enhance control and confidence. Aggressive but smooth rolling 29" wheels with 2.3" Ground Control tires offer ample traction in every situation, SRAM disc brakes deliver substantial braking bite, 110 mm of front suspension travel smooths the trail, and a dropper seatpost is there for when you need to really get down in technical off-road situations.
- **Turbo System Lock** - Use the Mission Control app to disable your bike's motor and activate the motion sensor alarm. Once locked, the motor cannot be enabled again except by the owner.
- **Fender, Rack, and Kickstand mounts.** Rated to pull a thru-axle trailer. Child seat compatible.

TURBO TERO 4.0	S	M	L	XL
Stack (mm)	637	651	664	687
Reach (mm)	405	426	446	462
Headtube Length (mm)	135	150	165	190
Headtube Angle (°)	66.4	66.4	66.4	66.4
BB Height (mm)	313	313	313	313
BB Drop (mm)	57	57	57	57
Trail (mm)	114	114	114	114
Fork Length (full) (mm)	516	516	516	516
Fork Rake/Offset (mm)	44	44	44	44
Front Center (mm)	709	736	761	787
Chainstay Length (mm)	470.4	470.4	470.4	470.4
Wheelbase (mm)	1173	1200	1226	1252
Toptube Length (horizontal) (mm)	589	620	650	680
Bike Standover Height (mm)	773	807	807	835
Seat Tube Length (mm)	400	450	460	500
Seat Tube Angle (Virtual) (°)	73.9	73.4	72.9	72.4
Crank Length (mm)	170			
Seatpost Length (mm)	360			
Stem Length (mm)	60			
Crank Length (mm)	170			
Seatpost Length (mm)	400			
Stem Length (mm)	60			
Crank Length (mm)	170			
Seatpost Length (mm)	400			
Stem Length (mm)	70			
Crank Length (mm)	170			
Seatpost Length (mm)	400			
Stem Length (mm)	70			
Handlebar Width (mm)	720	750	750	750
Saddle Width (mm)	155	155	155	155

SPECS	Specifications subject to change without notice.
Frame	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount
Fork	Rockshox Recon Silver TK, 110mm travel, Motion-Control
Stem	Stout 3D-forged alloy, 31.8mm, 6-degree rise
Handlebars	Specialized Trail, 6061 alloy, 8-degree backsweep, 6-degree upsweep, 27mm rise, 31.8mm clamp, S 720mm, M-XL 750mm
Front Brake	SRAM Guide T, 4-piston caliper, hydraulic disc, 200mm
Rear Brake	SRAM Guide T, 4-piston caliper, hydraulic disc, 180mm
Rear Derailleur	SRAM NX, 11-speed
Shift Levers	SRAM NX, 11-speed
Cassette	SRAM PG-1130, 11-speed, 11-42t
Chain	KMC e11S, 11-speed w/ Missing Link™
Crankset	Custom alloy forged crankarms
Chainrings	Praxis, 36T, 104BCD
Pedals	Specialized Body Geometry Fitness, platform, plastic
Rims	Stout XC 29, 25mm internal width, disc-specific
Front Hub	Specialized alloy front hub disc, sealed cartridge bearings, 6-bolt, 15x110mm thru-axle, 32h
Rear Hub	Specialized alloy rear hub disc, sealed cartridge bearings, 6-bolt, 12x148mm thru-axle, 32h
Spokes	DT Swiss Industry
Front Tire	Ground Control, 2Bliss Ready, 29x2.35"
Rear Tire	Ground Control, 2Bliss Ready, 29x2.35"
Inner Tubes	Presta, 48mm valve
Saddle	Rivo Sport, steel rails, 155mm
SeatPost	TranzX Dropper, 30.9mm, S: 100mm, M-XL: 120mm
Seat Binder	Alloy, bolt-type, 34.9mm
Motor	Specialized 2.0, 70Nm torque, custom tuned motor, 250W nominal
UI/Remote	MasterMind TCD, w/handlebar remote, built-in anti-theft feature, Bluetooth® connectivity, customizable display pages
Battery	Specialized U2-710, alloy casing, state of charge display, 710Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Wiring Harness	Custom wire harness
SWAT	Specialized Stealth Stem, Display Insert
Bike Lock	Turbo System Lock
Bell	Simple bell

PART NO.	DESCRIPTION	COLOR	SIZE
95123-5302	TERO 4.0 NB	Black / Black	S
95123-5303			M
95123-5304			L
95123-5305			XL

TURBO TERO 4.0



Black / Black

	S	M	L	XL
Stack (mm)	637	651	664	687
Reach (mm)	405	426	446	462
Headtube Length (mm)	135	150	165	190
Headtube Angle (°)	66.4	66.4	66.4	66.4
BB Height (mm)	313	313	313	313
BB Drop (mm)	57	57	57	57
Trail (mm)	114	114	114	114
Fork Length (full) (mm)	516	516	516	516
Fork Rake/Offset (mm)	44	44	44	44
Front Center (mm)	709	736	761	787
Chainstay Length (mm)	470.4	470.4	470.4	470.4
Wheelbase (mm)	1173	1200	1226	1252
Toptube Length (horizontal) (mm)	589	620	650	680
Bike Standover Height (mm)	773	807	807	835
Seat Tube Length (mm)	400	450	460	500
Seat Tube Angle (Virtual) (°)	73.9	73.4	72.9	72.4
Crank Length (mm)	170	170	170	170
Handlebar Width (mm)	720	750	750	750
Stem Length (mm)	60	60	70	70
Saddle Width (mm)	155	155	155	155
Seatpost Length (mm)	360	400	400	400

SPECS	Specifications subject to change without notice.
Frame	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount
Fork	Rockshox Recon Silver TK, 110mm travel, Motion-Control
Stem	Stout 3D-forged alloy, 31.8mm, 6-degree rise
Handlebars	Specialized Trail, 6061 alloy, 8-degree backsweep, 6-degree upsweep, 27mm rise, 31.8mm clamp, S 720mm, M-XL 750mm,
Front Brake	SRAM Guide T, 4-piston caliper, hydraulic disc, 200mm
Rear Brake	SRAM Guide T, 4-piston caliper, hydraulic disc, 180mm
Rear Derailleur	SRAM NX, 11-speed
Shift Levers	SRAM NX, 11-speed
Cassette	SRAM PG-1130, 11-speed, 11-42t
Chain	KMC e11S, 11-speed w/ Missing Link™
Crankset	Custom alloy forged crankarms
Chainrings	40T
Rims	Stout XC 29, 25mm internal width, disc-specific
Front Hub	Alloy, sealed cartridge bearings, 15x110mm thru-axle, 32h
Rear Hub	Alloy, sealed cartridge bearings, 12x148mm thru-axle, 32h
Spokes	DT Swiss Industry
Front Tire	GROUND CONTROL CONTROL 2BR, 29x2.35
Rear Tire	GROUND CONTROL CONTROL 2BR, 29x2.35
Inner Tubes	TUBES, STANDARD 48MM PV 29x1.75/2.4
Saddle	Bridge Sport, Steel rails, 155mm
SeatPost	TranzX Dropper, 30.9mm, S: 100mm, M-XL: 120mm
Seat Binder	Alloy, bolt-type, 34.9mm
Motor	TBD
UI/Remote	TBD
Battery	SPECIALIZED U2-710, INTEGRATED BATTERY, 710WH
Charger	Custom charger, 42V4A w/ Rosenberger plug, 230V
Wiring Harness	Custom wire harness
SWAT	Specialized Stealth Stem, Display Insert
Bell	Simple bell

PART NO.	DESCRIPTION	COLOR	SIZE
95122-6002	TERO 4.0 NB	Black / Black	S
95122-6003			M
95122-6004			L
95122-6005			XL

TURBO TERO 3.0



Oak Green Metallic / Smoke



White Mountains / Gunmetal

The new Turbo Tero is an electric mountain bike equipped for everyday rides. A mountain bike that you can commute on. A commuter you can take touring. A touring bike that you can haul freight with. Whatever you need it to be, for wherever you want to go. A true do-it-all superhero, Tero combines adaptable utility with World Champion mountain bike DNA and category-leading electric pedal assist.

- Turbo Full Power 2.0E Motor and 530 Wh Battery- Integrated into the aluminum frame of the Tero 3.0, they effectively quadruple your own power, cranking out ample wattage to make short work of the steepest climbs and providing enough extra muscle to let you carry a mountain of adventure gear, groceries, kids and daydreams without breaking a sweat. It's you, only faster. But what really sets this motor apart from the rest is how efficiently and seamlessly it melds with your own efforts.
- Mission Control and MasterMind- Mission Control allows you to tailor Tero's power output levels to your desired preference—all three standard power modes can be almost infinitely adjusted to suit your power and range needs. MasterMind's MicroTune function can adjust power output levels in 10% increments so that you can tune the range to suit your needs.
- Mountain Bike DNA- Tero's componentry is tailored to enhance control and confidence. Aggressive but smooth rolling 29" wheels with 2.3" Ground Control tires offer ample traction in every situation, SRAM disc brakes deliver substantial braking bite, 110 mm of front suspension travel smooths the trail.
- Turbo System Lock - Use the Mission Control app to disable your bike's motor and activate the motion sensor alarm. Once locked, the motor cannot be enabled again except by the owner.
- Fender, Rack, and Kickstand mounts. Rated to pull a thru-axle trailer. Child seat compatible.

TURBO TERO 3.0	S	M	L	XL
Stack (mm)	637	651	664	687
Reach (mm)	405	426	446	462
Headtube Length (mm)	135	150	165	190
Headtube Angle (°)	66.4	66.4	66.4	66.4
BB Height (mm)	313	313	313	313
BB Drop (mm)	57	57	57	57
Trail (mm)	114	114	114	114
Fork Length (full) (mm)	516	516	516	516
Fork Rake/Offset (mm)	44	44	44	44
Front Center (mm)	709	736	761	787
Chainstay Length (mm)	470.4	470.4	470.4	470.4
Wheelbase (mm)	1173	1200	1226	1252
Toptube Length (horizontal) (mm)	589	620	650	680
Bike Standover Height (mm)	773	807	807	835
Seat Tube Length (mm)	400	450	460	500
Seat Tube Angle (Virtual) (°)	73.9	73.4	72.9	72.4
Crank Length (mm)	170			
Seatpost Length (mm)	300			
Stem Length (mm)	60			
Crank Length (mm)	170			
Seatpost Length (mm)	400			
Stem Length (mm)	60			
Crank Length (mm)	170			
Seatpost Length (mm)	400			
Stem Length (mm)	70			
Crank Length (mm)	170			
Seatpost Length (mm)	400			
Stem Length (mm)	70			
Handlebar Width (mm)	720	750	750	750
Saddle Width (mm)	155	155	155	155

SPECS	Specifications subject to change without notice.
Frame	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount
Fork	SR Suntour XCM32, 110mm travel, lockout
Stem	Stout 3D-forged alloy, 31.8mm, 6-degree rise
Handlebars	Specialized Trail, 6061 alloy, 8-degree backsweep, 6-degree upsweep, 27mm rise, 31.8mm clamp, S 720mm, M-XL 750mm
Front Brake	Shimano BR-MT200, hydraulic disc, 180mm
Rear Brake	Shimano BR-MT200, hydraulic disc, 180mm
Rear Derailleur	Shimano Alivio, SGS, 9-speed
Shift Levers	Shimano Alivio, 9-speed w/ Optical Gear Display
Cassette	Shimano CS-HG400, 9-speed, 11-36t
Chain	KMC e9T, 9-speed w/ Missing Link™
Crankset	Custom alloy forged crankarms
Chainrings	40T
Pedals	Specialized Body Geometry Fitness, platform, plastic
Rims	Stout XC 29, 25mm internal width, disc-specific
Front Hub	Shimano MT400, Centerlock, 15x100mm, 32h
Rear Hub	Shimano MT400-B, Centerlock, 12x148 Boost, 32h
Spokes	DT Swiss Industry
Front Tire	Ground Control, 2Bliss Ready, 29x2.35"
Rear Tire	Ground Control, 2Bliss Ready, 29x2.35"
Inner Tubes	Presta, 48mm valve
Saddle	Bridge Sport, Steel rails, 155mm
SeatPost	Specialized, 6061 alloy, 2-bolt clamp, 0mm setback, 30.9mm
Seat Binder	Alloy, bolt-type, 34.9mm
Motor	Specialized 2.0E, 50Nm torque, custom tuned motor, 250W nominal
UI/Remote	MasterMind TCD, w/handlebar remote, built-in anti-theft feature, Bluetooth® connectivity, customizable display pages
Battery	Specialized U2-530, alloy casing, state of charge display, 530Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Wiring Harness	Custom wire harness
Bike Lock	Turbo System Lock
Bell	Simple bell

PART NO.	DESCRIPTION	COLOR	SIZE
95123-7202	TERO 3.0 NB	Oak Green Metallic / Smoke	S
95123-7203			M
95123-7204			L
95123-7205			XL
95123-7302	TERO 3.0 NB	White Mountains / Gunmetal	S
95123-7303			M
95123-7304			L
95123-7305			XL

TURBO TERO 3.0



Oak Green Metallic / Smoke



White Mountains / Gunmetal

	S	M	L	XL
Stack (mm)	637	651	664	687
Reach (mm)	405	426	446	462
Headtube Length (mm)	135	150	165	190
Headtube Angle (°)	66.4	66.4	66.4	66.4
BB Height (mm)	313	313	313	313
BB Drop (mm)	57	57	57	57
Trail (mm)	114	114	114	114
Fork Length (full) (mm)	516	516	516	516
Fork Rake/Offset (mm)	44	44	44	44
Front Center (mm)	709	736	761	787
Chainstay Length (mm)	470.4	470.4	470.4	470.4
Wheelbase (mm)	1173	1200	1226	1252
Toptube Length (horizontal) (mm)	589	620	650	680
Bike Standover Height (mm)	773	807	807	835
Seat Tube Length (mm)	400	450	460	500
Seat Tube Angle (Virtual) (°)	73.9	73.4	72.9	72.4
Crank Length (mm)	170	170	170	170
Handlebar Width (mm)	720	750	750	750
Stem Length (mm)	60	60	70	70
Saddle Width (mm)	155	155	155	155
Seatpost Length (mm)	300	400	400	400

SPECS	Specifications subject to change without notice.
Frame	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount
Fork	SR Suntour XCM32, 110mm travel, lockout
Stem	Stout 3D-forged alloy, 31.8mm, 6-degree rise
Handlebars	Specialized Trail, 6061 alloy, 8-degree backsweep, 6-degree upsweep, 27mm rise, 31.8mm clamp, S 720mm, M-XL 750mm,
Front Brake	Shimano BR-MT200, hydraulic disc, 180mm
Rear Brake	Shimano BR-MT200, hydraulic disc, 180mm
Rear Derailleur	Shimano Acera, RapidFire Plus, 9-speed
Shift Levers	Shimano Alivio, 9-speed w/ Optical Gear Display
Cassette	Shimano CS-HG400, 9-speed, 11-36t
Chain	KMC e9T, 9-speed w/ Missing Link™
Crankset	Custom alloy forged crankarms
Chainrings	40T
Rims	Stout XC 29, 25mm internal width, disc-specific
Front Hub	Shimano MT400, Centerlock 32h, 15x100mm
Rear Hub	Shimano MT400-B, Centerlock 32h, 12x148 Boost
Spokes	DT Swiss Industry
Front Tire	GROUND CONTROL CONTROL 2BR, 29x2.35
Rear Tire	GROUND CONTROL CONTROL 2BR, 29x2.35
Inner Tubes	TUBES, STANDARD 48MM PV 29x1.75/2.4
Saddle	Bridge Sport, Steel rails, 155mm
SeatPost	Specialized, 6061 alloy, 2-bolt clamp, 0mm setback, 30.9mm
Seat Binder	Alloy, bolt-type, 34.9mm
Motor	TBD
UI/Remote	TBD
Battery	SPECIALIZED U2-530, INTEGRATED BATTERY, 530WH
Charger	Custom charger, 42V4A w/ Rosenberger plug, 230V
Wiring Harness	Custom wire harness
Bell	Simple bell

PART NO.	DESCRIPTION	COLOR	SIZE
95122-8002	TERO 3.0 NB	Oak Green Metallic / Smoke	S
95122-8003			M
95122-8004			L
95122-8005			XL
95122-8102	TERO 3.0 NB	White Mountains / Gunmetal	S
95122-8103			M
95122-8104			L
95122-8105			XL

TURBO TERO 3.0 STEP-THROUGH



Oak Green Metallic / Smoke



White Mountains / Gunmetal

The new Turbo Tero is an electric mountain bike equipped for everyday rides. A mountain bike that you can commute on. A commuter you can take touring. A touring bike that you can haul freight with. Whatever you need it to be, for wherever you want to go. A true do-it-all superhero, Tero combines adaptable utility with World Champion mountain bike DNA and category-leading electric pedal assist.

- Turbo Full Power 2.0E Motor and 530 Wh Battery- Integrated into the aluminum frame of the Tero 3.0, they effectively quadruple your own power, cranking out ample wattage to make short work of the steepest climbs and providing enough extra muscle to let you carry a mountain of adventure gear, groceries, kids and daydreams without breaking a sweat. It's you, only faster. But what really sets this motor apart from the rest is how efficiently and seamlessly it melds with your own efforts.
- Mission Control and MasterMind- Mission Control allows you to tailor Tero's power output levels to your desired preference—all three standard power modes can be almost infinitely adjusted to suit your power and range needs. MasterMind's MicroTune function can adjust power output levels in 10% increments so that you can tune the range to suit your needs.
- Mountain Bike DNA- Tero's componentry is tailored to enhance control and confidence. Aggressive but smooth rolling 29" wheels with 2.3" Ground Control tires offer ample traction in every situation, SRAM disc brakes deliver substantial braking bite, 110 mm of front suspension travel smooths the trail.
- Turbo System Lock - Use the Mission Control app to disable your bike's motor and activate the motion sensor alarm. Once locked, the motor cannot be enabled again except by the owner.
- Fender, Rack, and Kickstand mounts. Rated to pull a thru-axle trailer. Child seat compatible.

TURBO TERO 3.0 STEP-THROUGH

	S	M	L	XL
Stack (mm)	637	651	664	687
Reach (mm)	405	426	446	462
Headtube Length (mm)	135	150	165	190
Headtube Angle (°)	66.4	66.4	66.4	66.4
BB Height (mm)	313	313	313	313
BB Drop (mm)	57	57	57	57
Trail (mm)	114	114	114	114
Fork Length (full) (mm)	516	516	516	516
Fork Rake/Offset (mm)	44	44	44	44
Front Center (mm)	709	736	761	787
Chainstay Length (mm)	470.4	470.4	470.4	470.4
Wheelbase (mm)	1173	1200	1226	1252
Toptube Length (horizontal) (mm)	589	620	650	680
Bike Standover Height (mm)	658	655	655	664
Seat Tube Length (mm)	400	450	460	500
Seat Tube Angle (Virtual) (°)	73.9	73.4	72.9	72.4
Crank Length (mm)	170			
Seatpost Length (mm)	300			
Stem Length (mm)	60			
Crank Length (mm)	170			
Seatpost Length (mm)	400			
Stem Length (mm)	60			
Crank Length (mm)	170			
Seatpost Length (mm)	400			
Stem Length (mm)	70			
Crank Length (mm)	170			
Seatpost Length (mm)	400			
Stem Length (mm)	70			
Handlebar Width (mm)	720	750	750	750
Saddle Width (mm)	155	155	155	155

SPECS	Specifications subject to change without notice.
Frame	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount
Fork	SR Suntour XCM32, 110mm travel, lockout
Stem	Stout 3D-forged alloy, 31.8mm, 6-degree rise
Handlebars	Specialized Trail, 6061 alloy, 8-degree backsweep, 6-degree upsweep, 27mm rise, 31.8mm clamp, S 720mm, M-XL 750mm
Front Brake	Shimano BR-MT200, hydraulic disc, 180mm
Rear Brake	Shimano BR-MT200, hydraulic disc, 180mm
Rear Derailleur	Shimano Alivio, SGS, 9-speed
Shift Levers	Shimano Alivio, 9-speed w/ Optical Gear Display
Cassette	Shimano CS-HG400, 9-speed, 11-36t
Chain	KMC e9T, 9-speed w/ Missing Link™
Crankset	Custom alloy forged crankarms
Chainrings	40T
Pedals	Specialized Body Geometry Fitness, platform, plastic
Rims	Stout XC 29, 25mm internal width, disc-specific
Front Hub	Shimano MT400, Centerlock, 15x100mm, 32h
Rear Hub	Shimano MT400-B, Centerlock, 12x148 Boost, 32h
Spokes	DT Swiss Industry
Front Tire	Ground Control, 2Bliss Ready, 29x2.35"
Rear Tire	Ground Control, 2Bliss Ready, 29x2.35"
Inner Tubes	Presta, 48mm valve
Saddle	Bridge Sport, Steel rails, 155mm
SeatPost	Specialized, 6061 alloy, 2-bolt clamp, 0mm setback, 30.9mm
Seat Binder	Alloy, bolt-type, 34.9mm
Motor	Specialized 2.0E, 50Nm torque, custom tuned motor, 250W nominal
UI/Remote	MasterMind TCD, w/handlebar remote, built-in anti-theft feature, Bluetooth® connectivity, customizable display pages
Battery	Specialized U2-530, alloy casing, state of charge display, 530Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Wiring Harness	Custom wire harness
Bike Lock	Turbo System Lock
Bell	Simple bell

PART NO.	DESCRIPTION	COLOR	SIZE
95123-7602	TURO 3.0 STEP THROUGH NB	Oak Green Metallic / Smoke	S
95123-7603			M
95123-7604			L
95123-7605			XL
95123-7702	TURO 3.0 STEP THROUGH NB	White Mountains / Gunmetal	S
95123-7703			M
95123-7704			L
95123-7705			XL

TURBO TERO 3.0 STEP-THROUGH



Oak Green Metallic / Smoke



White Mountains / Gunmetal

	S	M	L	XL
Stack (mm)	637	651	664	687
Reach (mm)	405	426	446	462
Headtube Length (mm)	135	150	165	190
Headtube Angle (°)	66.4	66.4	66.4	66.4
BB Height (mm)	313	313	313	313
BB Drop (mm)	57	57	57	57
Trail (mm)	114	114	114	114
Fork Length (full) (mm)	516	516	516	516
Fork Rake/Offset (mm)	44	44	44	44
Front Center (mm)	709	736	761	787
Chainstay Length (mm)	470.4	470.4	470.4	470.4
Wheelbase (mm)	1173	1200	1226	1252
Toptube Length (horizontal) (mm)	589	620	650	680
Bike Standover Height (mm)	658	655	655	664
Seat Tube Length (mm)	400	450	460	500
Seat Tube Angle (Virtual) (°)	73.9	73.4	72.9	72.4
Crank Length (mm)	170	170	170	170
Handlebar Width (mm)	720	750	750	750
Stem Length (mm)	60	60	70	70
Saddle Width (mm)	155	155	155	155
Seatpost Length (mm)	300	400	400	400

SPECS	Specifications subject to change without notice.
Frame	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount
Fork	SR Suntour XCM32, 110mm travel, lockout
Stem	Stout 3D-forged alloy, 31.8mm, 6-degree rise
Handlebars	Specialized Trail, 6061 alloy, 8-degree backsweep, 6-degree upsweep, 27mm rise, 31.8mm clamp, S 720mm, M-XL 750mm,
Front Brake	Shimano BR-MT200, hydraulic disc, 180mm
Rear Brake	Shimano BR-MT200, hydraulic disc, 180mm
Rear Derailleur	Shimano Acera, RapidFire Plus, 9-speed
Shift Levers	Shimano Alivio, 9-speed w/ Optical Gear Display
Cassette	Shimano CS-HG400, 9-speed, 11-36t
Chain	KMC e9T, 9-speed w/ Missing Link™
Crankset	Custom alloy forged crankarms
Chainrings	40T
Rims	Stout XC 29, 25mm internal width, disc-specific
Front Hub	Shimano MT400, Centerlock 32h, 15x100mm
Rear Hub	Shimano MT400-B, Centerlock 32h, 12x148 Boost
Spokes	DT Swiss Industry
Front Tire	GROUND CONTROL CONTROL 2BR, 29x2.35
Rear Tire	GROUND CONTROL CONTROL 2BR, 29x2.35
Inner Tubes	TUBES, STANDARD 48MM PV LOW LEAD 29x1.75/2.4
Saddle	Bridge Sport, Steel rails, 155mm
SeatPost	Specialized, 6061 alloy, 2-bolt clamp, 0mm setback, 30.9mm
Seat Binder	Alloy, bolt-type, 34.9mm
Motor	TBD
UI/Remote	TBD
Battery	SPECIALIZED U2-530, INTEGRATED BATTERY, 530WH
Charger	Custom charger, 42V4A w/ Rosenberger plug, 230V
Wiring Harness	Custom wire harness
Bell	Simple bell

PART NO.	DESCRIPTION	COLOR	SIZE
95122-8202	TERO 3.0 STEP THROUGH NB	Oak Green Metallic / Smoke	S
95122-8203			M
95122-8204			L
95122-8205			XL
95122-8302	TERO 3.0 STEP THROUGH NB	White Mountains / Gunmetal	S
95122-8303			M
95122-8304			L
95122-8305			XL

VADO

TURBO VADO 5.0 IGH



Cast Black / Silver Reflective



Red Tint / Silver Reflective



White Mountains / Black Reflective

Vado is the vehicle for everything from daily commutes to fast workouts to longer-than-planned adventures—an electric bike for life. The smoothest-riding e-Bike experience yet, Vado is designed to boldly take on the ever-changing landscape you'll encounter as a daily rider, carry whatever you need it to, and keep you riding more often.

- Turbo Full Power 2.2 motor and 710Wh battery offer an unparalleled riding experience, providing a smooth, seamless, and shockingly quiet amplification of your efforts, up to 25 kph. The integrated controller responds to your pedal inputs resulting in intuitive amplification of your efforts with an incredibly natural feel.
- MasterMind and Mission Control - The MasterMind display reveals all relevant info about your ride, allows real-time tuning of support levels, and enables over-the-air updates so that your bike gets better over time. MasterMind seamlessly integrates with the Mission Control app for range optimization tools, advanced tuning, on-ride diagnostics, and more.
- The enviolo AUTOMATIQ Internal Gear Hub (IGH) stepless shifting technology automatically shifts gears based on a rider's pedal pace, taking changes in the surroundings into account. By selecting a preferred cadence or pedal pace, it allows riders to "set it and forget it", adding an extra layer of safety and comfort for riders.
- Proven Smooth Efficiency - We designed a custom testing mechanism to analyze bumps at even the smallest frequency to increase comfort and vision. That precision, paired with a suspended seatpost, higher volume tires, and an 80 mm suspension fork, will flatten roads before your eyes.
- Turbo System Lock - Use the Mission Control app to disable your bike's motor and activate the motion sensor alarm. Once locked, the motor cannot be enabled again except by the owner.
- Garmin Radar - An integrated Garmin Radar sensor lets you know when traffic is coming up behind you. Garmin's Radar technology can detect cars up to 140 meters away. MasterMind will give riders a visual, audible, and haptic alert of an approaching vehicle's relative distance and rate of speed.
- Fully Integrated Removable and Lockable Downtube Battery - Easy to charge, easy to secure.
- Equipped with DRYTECH Fenders, LED front and rear lights, and 27kg capacity rear HD Rack. The rear rack is compatible with child bike seats, and the bike is also rated to pull a thru-axle trailer.

TURBO VADO 5.0 IGH	S	M	L	XL
Stack (mm)	625	639	652	676
Reach (mm)	423	444	464	481
Headtube Length (mm)	135	150	165	190
Headtube Angle (°)	68	68	68	68
BB Height (mm)	285	285	285	285
BB Drop (mm)	70	70	70	70
Trail (mm)	96	96	96	96
Fork Length (full) (mm)	480	480	480	480
Fork Rake/Offset (mm)	44	44	44	44
Front Center (mm)	699	724	750	777
Chainstay Length (mm)	470	470	470	470
Wheelbase (mm)	1160	1186	1212	1239
Toptube Length (horizontal) (mm)	585	615	645	675
Bike Standover Height (mm)	735	771	771	805
Seat Tube Length (mm)	400	450	460	500
Seat Tube Angle (Virtual) (°)	75.5	75	74.5	74
Crank Length (mm)	170	170	170	170
Handlebar Width (mm)	680	680	680	680
Stem Length (mm)	60	60	75	75
Saddle Width (mm)	155	155	155	155
Seatpost Length (mm)	350	350	400	400

SPECS	Specifications subject to change without notice.
Frame	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount, sliding dropout
Fork	Rockshox Recon Silver RL, 80mm travel, Motion-Control, fender-mounts
Stem	Specialized Flowset, 3D-forged alloy, 20-degree rise, 31.8mm clamp
Handlebars	Specialized, alloy, 15-degree backsweep, 46mm rise, 31.8mm
Grips	Ergon GA30
Front Brake	SRAM G2 RS, 4-piston caliper, hydraulic disc, 180mm 6-bolt
Rear Brake	SRAM G2 RS, 4-piston caliper, hydraulic disc, 180mm 6-bolt
Cassette	Gates Carbon Drive CDX 24t sprocket, silver
Chain	Gates Carbon Drive CDX 122t belt, black
Crankset	Custom alloy forged crankarms
Chainrings	Gates Carbon Drive CDX 50T chainring, black
Pedals	Specialized Commuter w/ grip tape & reflectors
Rims	650b disc, double-wall alloy, pinned, 32h
Front Hub	Specialized alloy front hub disc, sealed cartridge bearings, 6-bolt, 15x110mm thru-axle, 32h
Rear Hub	enviolo Heavy Duty, 380% range, 6-bolt, 10x135mm, 32h
Spokes	DT Swiss Industry
Front Tire	Pathfinder Sport Reflect, 650Bx2.3
Rear Tire	Pathfinder Sport Reflect, 650Bx2.3
Inner Tubes	Schrader, 40mm valve
Saddle	Rivo Sport, steel rails, 155mm
SeatPost	Spring suspension, alloy, 40mm travel, 30.9mm, 2-bolt clamp, 34.9mm sleeve
Seat Binder	Specialized Alloy, 34.9mm
Motor	Specialized 2.2, 90Nm torque, custom tuned motor, 250W nominal
UI/Remote	MasterMind TCD, w/handlebar remote, built-in anti-theft feature, Bluetooth* connectivity, customizable display pages
Battery	Specialized U2-710, alloy casing, state of charge display, 710Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Wiring Harness	Custom wire harness
Headlight	Lezyne Ebike Power E115, 310 Lumen, 12V
Taillight	Spanninga Commuter Glow XE, 12V
Chaincase	Custom chaincover
Kickstand	Specialized kickstand, 40mm mount
Rack	Specialized rack, MIK HD interface, built-in pannier mounts, 27kg max load
Fenders	Specialized DRYTECH fenders, 65mm width, aluminum fenderstay
Bell	Specialized brass bell

PART NO.	DESCRIPTION	COLOR	SIZE
95322-3402	VADO 5.0 IGH NB	Cast Black / Silver Reflective	S
95322-3403			M
95322-3404			L
95322-3405			XL
95322-3302	VADO 5.0 IGH NB	Red Tint / Silver Reflective	S
95322-3303			M
95322-3304			L
95322-3305			XL
95322-3502	VADO 5.0 IGH NB	White Mountains / Black Reflective	S
95322-3503			M
95322-3504			L
95322-3505			XL

TURBO VADO 5.0 IGH STEP-THROUGH



Cast Black / Silver Reflective



Red Tint / Silver Reflective



White Mountains / Black Reflective

Vado is the vehicle for everything from daily commutes to fast workouts to longer-than-planned adventures—an electric bike for life. The smoothest-riding e-Bike experience yet, Vado is designed to boldly take on the ever-changing landscape you'll encounter as a daily rider, carry whatever you need it to, and keep you riding more often.

- Turbo Full Power 2.2 motor and 710Wh battery offer an unparalleled riding experience, providing a smooth, seamless, and shockingly quiet amplification of your efforts, up to 25 kph. The integrated controller responds to your pedal inputs resulting in intuitive amplification of your efforts with an incredibly natural feel.
- MasterMind and Mission Control - The MasterMind display reveals all relevant info about your ride, allows real-time tuning of support levels, and enables over-the-air updates so that your bike gets better over time. MasterMind seamlessly integrates with the Mission Control app for range optimization tools, advanced tuning, on-ride diagnostics, and more.
- The enviolo AUTOMATIQ Internal Gear Hub (IGH) stepless shifting technology automatically shifts gears based on a rider's pedal pace, taking changes in the surroundings into account. By selecting a preferred cadence or pedal pace, it allows riders to "set it and forget it", adding an extra layer of safety and comfort for riders.
- Proven Smooth Efficiency - We designed a custom testing mechanism to analyze bumps at even the smallest frequency to increase comfort and vision. That precision, paired with a suspended seatpost, higher volume tires, and an 80 mm suspension fork, will flatten roads before your eyes.
- Turbo System Lock - Use the Mission Control app to disable your bike's motor and activate the motion sensor alarm. Once locked, the motor cannot be enabled again except by the owner.
- Garmin Radar - An integrated Garmin Radar sensor lets you know when traffic is coming up behind you. Garmin's Radar technology can detect cars up to 140 meters away. MasterMind will give riders a visual, audible, and haptic alert of an approaching vehicle's relative distance and rate of speed.
- Fully Integrated Removable and Lockable Downtube Battery - Easy to charge, easy to secure.
- Equipped with DRYTECH Fenders, LED front and rear lights, and 27kg capacity rear HD Rack. The rear rack is compatible with child bike seats, and the bike is also rated to pull a thru-axle trailer.

TURBO VADO 5.0 IGH STEP-THROUGH

	S	M	L	XL
Stack (mm)	625	639	652	676
Reach (mm)	423	444	464	481
Headtube Length (mm)	135	150	165	190
Headtube Angle (°)	68	68	68	68
BB Height (mm)	285	285	285	285
BB Drop (mm)	70	70	70	70
Trail (mm)	96	96	96	96
Fork Length (full) (mm)	480	480	480	480
Fork Rake/Offset (mm)	44	44	44	44
Front Center (mm)	699	724	750	777
Chainstay Length (mm)	470	470	470	470
Wheelbase (mm)	1160	1186	1212	1239
Toptube Length (horizontal) (mm)	585	615	645	675
Bike Standover Height (mm)	618	617	617	626
Seat Tube Length (mm)	400	450	460	500
Seat Tube Angle (Virtual) (°)	75.5	75	74.5	74
Crank Length (mm)	170	170	170	170
Handlebar Width (mm)	680	680	680	680
Stem Length (mm)	60	60	75	75
Saddle Width (mm)	155	155	155	155
Seatpost Length (mm)	350	350	400	400

SPECS

Specifications subject to change without notice.

Frame	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount, sliding dropout
Fork	Rockshox Recon Silver RL, 80mm travel, Motion-Control, fender-mounts
Stem	Specialized Flowset, 3D-forged alloy, 20-degree rise, 31.8mm clamp
Handlebars	Specialized, alloy, 15-degree backsweep, 46mm rise, 31.8mm
Grips	Ergon GA30
Front Brake	SRAM G2 RS, 4-piston caliper, hydraulic disc, 180mm 6-bolt
Rear Brake	SRAM G2 RS, 4-piston caliper, hydraulic disc, 180mm 6-bolt
Cassette	Gates Carbon Drive CDX 24t sprocket, silver
Chain	Gates Carbon Drive CDX 122t belt, black
Crankset	Custom alloy forged crankarms
Chainrings	Gates Carbon Drive CDX 50T chainring, black
Pedals	Specialized Commuter w/ grip tape & reflectors
Rims	650b disc, double-wall alloy, pinned, 32h
Front Hub	Specialized alloy front hub disc, sealed cartridge bearings, 6-bolt, 15x110mm thru-axle, 32h
Rear Hub	enviolo Heavy Duty, 380% range, 6-bolt, 10x135mm, 32h
Spokes	DT Swiss Industry
Front Tire	Pathfinder Sport Reflect, 650Bx2.3
Rear Tire	Pathfinder Sport Reflect, 650Bx2.3
Inner Tubes	Schrader, 40mm valve
Saddle	Rivo Sport, steel rails, 155mm
SeatPost	Spring suspension, alloy, 40mm travel, 30.9mm, 2-bolt clamp, 34.9mm sleeve
Seat Binder	Specialized Alloy, 34.9mm
Motor	Specialized 2.2, 90Nm torque, custom tuned motor, 250W nominal
UI/Remote	MasterMind TCD, w/handlebar remote, built-in anti-theft feature, Bluetooth® connectivity, customizable display pages
Battery	Specialized U2-710, alloy casing, state of charge display, 710Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Wiring Harness	Custom wire harness
SWAT	Handlebar rear view mirror, aluminum
Headlight	Lezyne Ebike Power E115, 310 Lumen, 12V
Taillight	Spanninga Commuter Glow XE, 12V
Chaincase	Custom chaincover
Kickstand	Specialized kickstand, 40mm mount
Rack	Specialized rack, MIK HD interface, built-in pannier mounts, 27kg max load
Fenders	Specialized DRYTECH fenders, 65mm width, aluminum fenderstay
Bell	Specialized brass bell

PART NO.	DESCRIPTION	COLOR	SIZE
95322-2402	VADO 5.0 IGH ST	Cast Black / Silver Reflective	S
95322-2403			M
95322-2404			L
95322-2405			XL
95322-2302	VADO 5.0 IGH ST	Red Tint / Silver Reflective	S
95322-2303			M
95322-2304			L
95322-2305			XL
95322-2502	VADO 5.0 IGH ST	White Mountains / Black Reflective	S
95322-2503			M
95322-2504			L
95322-2505			XL

TURBO VADO 5.0



Cast Black / Silver Reflective



Red Tint / Silver Reflective



White Mountains / Black Reflective

Vado is the vehicle for everything from daily commutes to fast workouts to longer-than-planned adventures—an electric bike for life. The smoothest-riding e-Bike experience yet, Vado is designed to boldly take on the ever-changing landscape you'll encounter as a daily rider, carry whatever you need it to, and keep you riding more often.

- Turbo Full Power 2.2 motor and 710Wh battery offer an unparalleled riding experience, providing a smooth, seamless, and shockingly quiet amplification of your efforts, up to 25 kph. The integrated controller responds to your pedal inputs resulting in intuitive amplification of your efforts with an incredibly natural feel.
- MasterMind and Mission Control - The MasterMind display reveals all relevant info about your ride, allows real-time tuning of support levels, and enables over-the-air updates so that your bike gets better over time. MasterMind seamlessly integrates with the Mission Control app for range optimization tools, advanced tuning, on-ride diagnostics, and more.
- Proven Smooth Efficiency - We designed a custom testing mechanism to analyze bumps at even the smallest frequency to increase comfort and vision. That precision, paired with a suspended seatpost, higher volume tires, and an 80 mm suspension fork, will flatten roads before your eyes.
- Turbo System Lock - Use the Mission Control app to disable your bike's motor and activate the motion sensor alarm. Once locked, the motor cannot be enabled again except by the owner.
- Garmin Radar - An integrated Garmin Radar sensor lets you know when traffic is coming up behind you. Garmin's Radar technology can detect cars up to 140 meters away. MasterMind will give riders a visual, audible, and haptic alert of an approaching vehicle's relative distance and rate of speed.
- Fully Integrated Removable and Lockable Downtube Battery - Easy to charge, easy to secure.
- Equipped with DRYTECH Fenders, LED front and rear lights, and 27kg capacity rear HD Rack. The rear rack is compatible with child bike seats, and the bike is also rated to pull a thru-axle trailer.

TURBO VADO 5.0	S	M	L	XL
Stack (mm)	625	639	652	676
Reach (mm)	423	444	464	481
Headtube Length (mm)	135	150	165	190
Headtube Angle (°)	68	68	68	68
BB Height (mm)	285	285	285	285
BB Drop (mm)	70	70	70	70
Trail (mm)	96	96	96	96
Fork Length (full) (mm)	480	480	480	480
Fork Rake/Offset (mm)	44	44	44	44
Front Center (mm)	699	724	750	777
Chainstay Length (mm)	470	470	470	470
Wheelbase (mm)	1160	1186	1212	1239
Toptube Length (horizontal) (mm)	585	615	645	675
Bike Standover Height (mm)	735	771	771	805
Seat Tube Length (mm)	400	450	460	500
Seat Tube Angle (Virtual) (°)	75.5	75	74.5	74
Crank Length (mm)	170	170	170	170
Handlebar Width (mm)	680	680	680	680
Stem Length (mm)	60	60	75	75
Saddle Width (mm)	155	155	155	155
Seatpost Length (mm)	350	350	400	400

SPECS	Specifications subject to change without notice.
Frame	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount
Fork	Rockshox Recon Silver RL, 80mm travel, Motion-Control, fender-mounts
Stem	Specialized Flowset, 3D-forged alloy, 20-degree rise, 31.8mm clamp
Handlebars	Specialized, alloy, 15-degree backsweep, 46mm rise, 31.8mm
Grips	ERGON GA30
Front Brake	SRAM G2 RS, 4-piston caliper, hydraulic disc, 180mm 6-bolt
Rear Brake	SRAM G2 RS, 4-piston caliper, hydraulic disc, 180mm 6-bolt
Rear Derailleur	SRAM GX, long cage, 11-speed
Shift Levers	SRAM S700, single-click lever
Cassette	SRAM PG-1130, 11-speed, 11-42t
Chain	KMC e11T, 11-speed w/ Missing Link™
Crankset	Custom alloy forged crankarms
Chainrings	Praxis, 48T, 104BCD
Pedals	Specialized Commuter w/ grip tape & reflectors
Rims	650b disc, double-wall alloy, pinned, 32h
Front Hub	Specialized alloy front hub disc, sealed cartridge bearings, 6-bolt, 15x110mm thru-axle, 32h
Rear Hub	Specialized alloy rear hub disc, sealed cartridge bearings, 6-bolt, 12x148mm thru-axle, 32h
Spokes	DT Swiss Industry
Front Tire	Pathfinder Sport Reflect, 650Bx2.3
Rear Tire	Pathfinder Sport Reflect, 650Bx2.3
Inner Tubes	Schrader, 40mm valve
Saddle	Rivo Sport, steel rails, 155mm
SeatPost	Spring suspension, alloy, 40mm travel, 30.9mm, 2-bolt clamp, 34.9mm sleeve
Seat Binder	Specialized Alloy, 34.9mm
Motor	Specialized 2.2, 90Nm torque, custom tuned motor, 250W nominal
UI/Remote	MasterMind TCD, w/handlebar remote, built-in anti-theft feature, Bluetooth® connectivity, customizable display pages
Battery	Specialized U2-710, alloy casing, state of charge display, 710Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug, 230V
Wiring Harness	Custom wire harness
Headlight	Lezyne Ebike Power E115, 310 Lumen, 12V
Taillight	Spanninga Commuter Glow XE, 12V
Chaincase	custom chaincover
Kickstand	Specialized kickstand, 40mm mount
Rack	Specialized rack, MIK HD interface, built-in pannier mounts, 27kg max load
Fenders	Specialized DRYTECH fenders, 65mm width, aluminum fenderstay
Bell	Specialized brass bell

PART NO.	DESCRIPTION	COLOR	SIZE
95022-3302	VADO 5.0 NB	Cast Black / Silver Reflective	S
95022-3303			M
95022-3304			L
95022-3305			XL
95022-3202	VADO 5.0 NB	Red Tint / Silver Reflective	S
95022-3203			M
95022-3204			L
95022-3205			XL
95022-3902	VADO 5.0 NB	White Mountains / Black Reflective	S
95022-3903			M
95022-3904			L
95022-3905			XL

TURBO VADO 5.0 STEP-THROUGH



Cast Black / Silver Reflective



Red Tint / Silver Reflective



White Mountains / Black Reflective

Vado is the vehicle for everything from daily commutes to fast workouts to longer-than-planned adventures—an electric bike for life. The smoothest-riding e-Bike experience yet, Vado is designed to boldly take on the ever-changing landscape you'll encounter as a daily rider, carry whatever you need it to, and keep you riding more often.

- Turbo Full Power 2.2 motor and 710Wh battery offer an unparalleled riding experience, providing a smooth, seamless, and shockingly quiet amplification of your efforts, up to 25 kph. The integrated controller responds to your pedal inputs resulting in intuitive amplification of your efforts with an incredibly natural feel.
- MasterMind and Mission Control - The MasterMind display reveals all relevant info about your ride, allows real-time tuning of support levels, and enables over-the-air updates so that your bike gets better over time. MasterMind seamlessly integrates with the Mission Control app for range optimization tools, advanced tuning, on-ride diagnostics, and more.
- Proven Smooth Efficiency - We designed a custom testing mechanism to analyze bumps at even the smallest frequency to increase comfort and vision. That precision, paired with a suspended seatpost, higher volume tires, and an 80 mm suspension fork, will flatten roads before your eyes.
- Turbo System Lock - Use the Mission Control app to disable your bike's motor and activate the motion sensor alarm. Once locked, the motor cannot be enabled again except by the owner.
- Garmin Radar - An integrated Garmin Radar sensor lets you know when traffic is coming up behind you. Garmin's Radar technology can detect cars up to 140 meters away. MasterMind will give riders a visual, audible, and haptic alert of an approaching vehicle's relative distance and rate of speed.
- Fully Integrated Removable and Lockable Downtube Battery - Easy to charge, easy to secure.
- Equipped with DRYTECH Fenders, LED front and rear lights, and 27kg capacity rear HD Rack. The rear rack is compatible with child bike seats, and the bike is also rated to pull a thru-axle trailer.

TURBO VADO 5.0 STEP-THROUGH

	S	M	L	XL
Stack (mm)	625	639	652	676
Reach (mm)	423	444	464	481
Headtube Length (mm)	135	150	165	190
Headtube Angle (°)	68	68	68	68
BB Height (mm)	285	285	285	285
BB Drop (mm)	70	70	70	70
Trail (mm)	96	96	96	96
Fork Length (full) (mm)	480	480	480	480
Fork Rake/Offset (mm)	44	44	44	44
Front Center (mm)	699	724	750	777
Chainstay Length (mm)	470	470	470	470
Wheelbase (mm)	1160	1186	1212	1239
Toptube Length (horizontal) (mm)	585	615	645	675
Bike Standover Height (mm)	618	617	617	626
Seat Tube Length (mm)	400	450	460	500
Seat Tube Angle (Virtual) (°)	75.5	75	74.5	74
Crank Length (mm)	170	170	170	170
Handlebar Width (mm)	680	680	680	680
Stem Length (mm)	60	60	75	75
Saddle Width (mm)	155	155	155	155
Seatpost Length (mm)	350	350	400	400

SPECS

Specifications subject to change without notice.

Frame	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount
Fork	Rockshox Recon Silver RL, 80mm travel, Motion-Control, fender-mounts
Stem	Specialized Flowset, 3D-forged alloy, 20-degree rise, 31.8mm clamp
Handlebars	Specialized, alloy, 15-degree backsweep, 46mm rise, 31.8mm
Grips	ERGON GA30
Front Brake	SRAM G2 RS, 4-piston caliper, hydraulic disc, 180mm 6-bolt
Rear Brake	SRAM G2 RS, 4-piston caliper, hydraulic disc, 180mm 6-bolt
Rear Derailleur	SRAM GX, long cage, 11-speed
Shift Levers	SRAM S700, single-click lever
Cassette	SRAM PG-1130, 11-speed, 11-42t
Chain	KMC e11T, 11-speed w/ Missing Link™
Crankset	Custom alloy forged crankarms
Chainrings	Praxis, 48T, 104BCD
Pedals	Specialized Commuter w/ grip tape & reflectors
Rims	650b disc, double-wall alloy, pinned, 32h
Front Hub	Specialized alloy front hub disc, sealed cartridge bearings, 6-bolt, 15x110mm thru-axle, 32h
Rear Hub	Specialized alloy front hub disc, sealed cartridge bearings, 6-bolt, 12x148mm thru-axle, 32h
Spokes	DT Swiss Industry
Front Tire	Pathfinder Sport Reflect, 650Bx2.3
Rear Tire	Pathfinder Sport Reflect, 650Bx2.3
Inner Tubes	Schrader, 40mm valve
Saddle	Rivo Sport, steel rails, 155mm
SeatPost	Spring suspension, alloy, 40mm travel, 30.9mm, 2-bolt clamp, 34.9mm sleeve
Seat Binder	Specialized Alloy, 34.9mm
Motor	Specialized 2.2, 90Nm torque, custom tuned motor, 250W nominal
UI/Remote	MasterMind TCD, w/handlebar remote, built-in anti-theft feature, Bluetooth® connectivity, customizable display pages
Battery	Specialized U2-710, alloy casing, state of charge display, 710Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug, 230V
Wiring Harness	Custom wire harness
Headlight	Lezyne Ebike Power E115, 310 Lumen, 12V
Taillight	Spanninga Commuter Glow XE, 12V
Chaincase	custom chaincover
Kickstand	Specialized kickstand, 40mm mount
Rack	Specialized rack, MIK HD interface, built-in pannier mounts, 27kg max load
Fenders	Specialized DRYTECH fenders, 65mm width, aluminum fenderstay
Bell	Specialized brass bell

PART NO.	DESCRIPTION	COLOR	SIZE
95022-3702	VADO 5.0 STEP THROUGH	Cast Black / Silver Reflective	S
95022-3703			M
95022-3704			L
95022-3705			XL
95022-3602	VADO 5.0 STEP THROUGH	Red Tint / Silver Reflective	S
95022-3603			M
95022-3604			L
95022-3605			XL
95022-2102	VADO 5.0 STEP THROUGH	White Mountains / Black Reflective	S
95022-2103			M
95022-2104			L
95022-2105			XL

TURBO VADO 4.0



Red Tint / Silver Reflective



Cast Black / Silver Reflective



White Mountains / Black Reflective

Vado is the vehicle for everything from daily commutes to fast workouts to longer-than-planned adventures—an electric bike for life. The smoothest-riding e-Bike experience yet, Vado is designed to boldly take on the ever-changing landscape you'll encounter as a daily rider, carry whatever you need it to, and keep you riding more often.

- Turbo Full Power 2.0 motor and 710Wh battery offer an unparalleled riding experience, providing a smooth, seamless, and shockingly quiet amplification of your efforts, up to 25 kph. The integrated controller responds to your pedal inputs resulting in intuitive amplification of your efforts with an incredibly natural feel.
- MasterMind and Mission Control - The MasterMind display reveals all relevant info about your ride, allows real-time tuning of support levels, and enables over-the-air updates so that your bike gets better over time. MasterMind seamlessly integrates with the Mission Control app for range optimization tools, advanced tuning, on-ride diagnostics, and more.
- Proven Smooth Efficiency - We designed a custom testing mechanism to analyze bumps at even the smallest frequency to increase comfort and vision. That precision, paired with a suspended seatpost, higher volume tires, and an 80 mm suspension fork, will flatten roads before your eyes.
- Turbo System Lock - Use the Mission Control app to disable your bike's motor and activate the motion sensor alarm. Once locked, the motor cannot be enabled again except by the owner.
- Fully Integrated Removable and Lockable Downtube Battery - Easy to charge, easy to secure.
- Equipped with DRYTECH Fenders, LED front and rear lights, and 27kg capacity rear HD Rack. The rear rack is compatible with child bike seats, and the bike is also rated to pull a thru-axle trailer.

TURBO VADO 4.0	S	M	L	XL
Stack (mm)	625	639	652	676
Reach (mm)	423	444	464	481
Headtube Length (mm)	135	150	165	190
Headtube Angle (°)	68	68	68	68
BB Height (mm)	285	285	285	285
BB Drop (mm)	70	70	70	70
Trail (mm)	96	96	96	96
Fork Length (full) (mm)	480	480	480	480
Fork Rake/Offset (mm)	44	44	44	44
Front Center (mm)	699	724	750	777
Chainstay Length (mm)	470	470	470	470
Wheelbase (mm)	1160	1186	1212	1239
Toptube Length (horizontal) (mm)	585	615	645	675
Bike Standover Height (mm)	735	771	771	805
Seat Tube Length (mm)	400	450	460	500
Seat Tube Angle (Virtual) (°)	75.5	75	74.5	74
Crank Length (mm)	170	170	170	170
Handlebar Width (mm)	680	680	680	680
Stem Length (mm)	60	60	75	75
Saddle Width (mm)	155	155	155	155
Seatpost Length (mm)	350	350	400	400

SPECS	Specifications subject to change without notice.
Frame	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount
Fork	SR Suntour MobieA32, 80mm travel, lockout, fender-mounts, integrated light mount
Stem	Specialized Flowset, 3D-forged alloy, 20-degree rise, 31.8mm clamp
Handlebars	Specialized, alloy, 15-degree backsweep, 46mm rise, 31.8mm
Grips	Specialized Body Geometry Contour, lock-on
Front Brake	SRAM Level, 2-piston caliper, hydraulic disc, 180mm 6-bolt
Rear Brake	SRAM Level, 2-piston caliper, hydraulic disc, 180mm 6-bolt
Rear Derailleur	SRAM NX, 11-speed
Shift Levers	SRAM NX, 11-speed
Cassette	SRAM PG-1130, 11-speed, 11-42t
Chain	KMC e11S, 11-speed w/ Missing Link™
Crankset	Custom alloy forged crankarms
Chainrings	Praxis, 48T, 104BCD
Pedals	Specialized Commuter w/ grip tape & reflectors
Rims	650b disc, double-wall alloy, pinned, 32h
Front Hub	Specialized alloy front hub disc, sealed cartridge bearings, 6-bolt, 15x100mm thru-axle, 32h
Rear Hub	Specialized alloy front hub disc, sealed cartridge bearings, 6-bolt, 12x148mm thru-axle, 32h
Spokes	DT Swiss Industry
Front Tire	Pathfinder Sport Reflect, 650Bx2.3
Rear Tire	Pathfinder Sport Reflect, 650Bx2.3
Inner Tubes	Schrader, 40mm valve
Saddle	Rivo Sport, steel rails, 155mm
SeatPost	Spring suspension, alloy, 40mm travel, 30.9mm, 2-bolt clamp, 34.9mm sleeve
Seat Binder	Alloy, bolt-type, 34.9mm
Motor	Specialized 2.0, 70Nm torque, custom tuned motor, 250W nominal
UI/Remote	MasterMind TCD, w/handlebar remote, built-in anti-theft feature, Bluetooth® connectivity, customizable display pages
Battery	Specialized U2-710, alloy casing, state of charge display, 710Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Wiring Harness	Custom wire harness
Headlight	Lezyne Ebike Hecto E65, 210 Lumen, 12V
Taillight	Spanninga Commuter Glow XE, 12V
Chaincase	Custom chaincover
Kickstand	Specialized kickstand, 40mm mount
Rack	Specialized rack, MIK HD interface, built-in pannier mounts, 27kg max load
Fenders	Specialized DRYTECH fenders, 65mm width, aluminum fenderstay
Bell	Simple bell

PART NO.	DESCRIPTION	COLOR	SIZE
95022-5402	VADO 4.0 NB	Cast Black / Silver Reflective	S
95022-5403			M
95022-5404			L
95022-5405			XL
95022-5702	VADO 4.0 NB	Red Tint / Silver Reflective	S
95022-5703			M
95022-5704			L
95022-5705			XL
95022-5502	VADO 4.0 NB	White Mountains / Black Reflective	S
95022-5503			M
95022-5504			L
95022-5505			XL

TURBO VADO 4.0 STEP-THROUGH



Cast Black / Silver Reflective



Red Tint / Silver Reflective



White Mountains / Black Reflective

Vado is the vehicle for everything from daily commutes to fast workouts to longer-than-planned adventures—an electric bike for life. The smoothest-riding e-Bike experience yet, Vado is designed to boldly take on the ever-changing landscape you'll encounter as a daily rider, carry whatever you need it to, and keep you riding more often.

- Turbo Full Power 2.0 motor and 710Wh battery offer an unparalleled riding experience, providing a smooth, seamless, and shockingly quiet amplification of your efforts, up to 25 kph. The integrated controller responds to your pedal inputs resulting in intuitive amplification of your efforts with an incredibly natural feel.
- MasterMind and Mission Control - The MasterMind display reveals all relevant info about your ride, allows real-time tuning of support levels, and enables over-the-air updates so that your bike gets better over time. MasterMind seamlessly integrates with the Mission Control app for range optimization tools, advanced tuning, on-ride diagnostics, and more.
- Proven Smooth Efficiency - We designed a custom testing mechanism to analyze bumps at even the smallest frequency to increase comfort and vision. That precision, paired with a suspended seatpost, higher volume tires, and an 80 mm suspension fork, will flatten roads before your eyes.
- Turbo System Lock - Use the Mission Control app to disable your bike's motor and activate the motion sensor alarm. Once locked, the motor cannot be enabled again except by the owner.
- Fully Integrated Removable and Lockable Downtube Battery - Easy to charge, easy to secure.
- Equipped with DRYTECH Fenders, LED front and rear lights, and 27kg capacity rear HD Rack. The rear rack is compatible with child bike seats, and the bike is also rated to pull a thru-axle trailer.

TURBO VADO 4.0 STEP-THROUGH

	S	M	L	XL
Stack (mm)	625	639	652	676
Reach (mm)	423	444	464	481
Headtube Length (mm)	135	150	165	190
Headtube Angle (°)	68	68	68	68
BB Height (mm)	285	285	285	285
BB Drop (mm)	70	70	70	70
Trail (mm)	96	96	96	96
Fork Length (full) (mm)	480	480	480	480
Fork Rake/Offset (mm)	44	44	44	44
Front Center (mm)	699	724	750	777
Chainstay Length (mm)	470	470	470	470
Wheelbase (mm)	1160	1186	1212	1239
Toptube Length (horizontal) (mm)	585	615	645	675
Bike Standover Height (mm)	618	617	617	626
Seat Tube Length (mm)	400	450	460	500
Seat Tube Angle (Virtual) (°)	75.5	75	74.5	74
Crank Length (mm)	170	170	170	170
Handlebar Width (mm)	680	680	680	680
Stem Length (mm)	60	60	75	75
Saddle Width (mm)	155	155	155	155
Seatpost Length (mm)	350	350	400	400

SPECS

Specifications subject to change without notice.

Frame	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount
Fork	SR Suntour MobieA32, 80mm travel, lockout, fender-mounts, integrated light mount
Stem	Specialized Flowset, 3D-forged alloy, 20-degree rise, 31.8mm clamp
Handlebars	Specialized, alloy, 15-degree backsweep, 46mm rise, 31.8mm
Grips	Body Geometry Women's Contour
Front Brake	SRAM Level, 2-piston caliper, hydraulic disc, 180mm 6-bolt
Rear Brake	SRAM Level, 2-piston caliper, hydraulic disc, 180mm 6-bolt
Rear Derailleur	SRAM NX, 11-speed
Shift Levers	SRAM NX, 11-speed
Cassette	SRAM PG-1130, 11-speed, 11-42t
Chain	KMC e11S, 11-speed w/ Missing Link™
Crankset	Custom alloy forged crankarms
Chainrings	Praxis, 48T, 104BCD
Pedals	Specialized Commuter w/ grip tape & reflectors
Rims	650b disc, double-wall alloy, pinned, 32h
Front Hub	Specialized alloy front hub disc, sealed cartridge bearings, 6-bolt, 15x100mm thru-axle, 32h
Rear Hub	Specialized alloy rear hub disc, sealed cartridge bearings, 6-bolt, 12x148mm thru-axle, 32h
Spokes	DT Swiss Industry
Front Tire	Pathfinder Sport Reflect, 650Bx2.3
Rear Tire	Pathfinder Sport Reflect, 650Bx2.3
Inner Tubes	Schrader, 40mm valve
Saddle	Rivo Sport, steel rails, 155mm
SeatPost	Spring suspension, alloy, 40mm travel, 30.9mm, 2-bolt clamp, 34.9mm sleeve
Seat Binder	Alloy, bolt-type, 34.9mm
Motor	Specialized 2.0, 70Nm torque, custom tuned motor, 250W nominal
UI/Remote	MasterMind TCD, w/handlebar remote, built-in anti-theft feature, Bluetooth® connectivity, customizable display pages
Battery	Specialized U2-710, alloy casing, state of charge display, 710Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Wiring Harness	Custom wire harness
Headlight	Lezyne Ebike Hecto E65, 210 Lumen, 12V
Taillight	Spanninga Commuter Glow XE, 12V
Chaincase	Custom chaincover
Kickstand	Specialized kickstand, 40mm mount
Rack	Specialized rack, MIK HD interface, built-in pannier mounts, 27kg max load
Fenders	Specialized DRYTECH fenders, 65mm width, aluminum fenderstay
Bell	Simple bell

PART NO.	DESCRIPTION	COLOR	SIZE
95022-4102	VADO 4.0 STEP THROUGH	Cast Black / Silver Reflective	S
95022-4103			M
95022-4104			L
95022-4105			XL
95022-4002	VADO 4.0 STEP THROUGH	Red Tint / Silver Reflective	S
95022-4003			M
95022-4004			L
95022-4005			XL
95022-5102	VADO 4.0 STEP THROUGH	White Mountains / Black Reflective	S
95022-5103			M
95022-5104			L
95022-5105			XL

TURBO VADO 3.0 IGH



Cast Black / Silver Reflective



Red Tint / Silver Reflective



White Mountains / Black Reflective

Vado is the vehicle for everything from daily commutes to fast workouts to longer-than-planned adventures—an electric bike for life. The smoothest-riding e-Bike experience yet, Vado is designed to boldly take on the ever-changing landscape you'll encounter as a daily rider, carry whatever you need it to, and keep you riding more often.

- Turbo Full Power 2.0E motor and 530Wh battery offer an unparalleled riding experience, providing a smooth, seamless, and shockingly quiet amplification of your efforts, up to 25 kph. The integrated controller responds to your pedal inputs resulting in intuitive amplification of your efforts with an incredibly natural feel.
- MasterMind and Mission Control - The MasterMind display reveals all relevant info about your ride, allows real-time tuning of support levels, and enables over-the-air updates so that your bike gets better over time. MasterMind seamlessly integrates with the Mission Control app for range optimization tools, advanced tuning, on-ride diagnostics, and more.
- The stepless shifting enviolo City Internal Gear Hub (IGH) features a specifically designed internal gear hub and matching controller. The manual stepless technology is as simple as adjusting the volume on a radio. This allows riders to focus on the important aspects of a bike ride such as traffic or scenery.
- Proven Smooth Efficiency - We designed a custom testing mechanism to analyze bumps at even the smallest frequency to increase comfort and vision. That precision, paired with a suspended seatpost, higher volume tires, and an 80 mm suspension fork, will flatten roads before your eyes.
- Turbo System Lock - Use the Mission Control app to disable your bike's motor and activate the motion sensor alarm. Once locked, the motor cannot be enabled again except by the owner.
- Fully Integrated Removable and Lockable Downtube Battery - Easy to charge, easy to secure.
- Equipped with DRYTECH Fenders, LED front and rear lights, and 27kg capacity rear HD Rack. The rear rack is compatible with child bike seats, and the bike is also rated to pull a thru-axle trailer.

TURBO VADO 3.0 IGH	S	M	L	XL
Stack (mm)	625	639	652	676
Reach (mm)	423	444	464	481
Headtube Length (mm)	135	150	165	190
Headtube Angle (°)	68	68	68	68
BB Height (mm)	285	285	285	285
BB Drop (mm)	70	70	70	70
Trail (mm)	96	96	96	96
Fork Length (full) (mm)	480	480	480	480
Fork Rake/Offset (mm)	44	44	44	44
Front Center (mm)	699	724	750	777
Chainstay Length (mm)	470	470	470	470
Wheelbase (mm)	1160	1186	1212	1239
Toptube Length (horizontal) (mm)	585	615	645	675
Bike Standover Height (mm)	735	771	771	805
Seat Tube Length (mm)	400	450	460	500
Seat Tube Angle (Virtual) (°)	75.5	75	74.5	74
Crank Length (mm)	170	170	170	170
Handlebar Width (mm)	680	680	680	680
Stem Length (mm)	60	60	75	75
Saddle Width (mm)	155	155	155	155
Seatpost Length (mm)	300	400	400	400

SPECS	Specifications subject to change without notice.
Frame	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount, sliding dropout
Fork	SR Suntour MobieA32, 80mm travel, lockout, fender-mounts, integrated light mount
Stem	Specialized Flowset, 3D-forged alloy, 20-degree rise, 31.8mm clamp
Handlebars	Specialized, alloy, 15-degree backsweep, 46mm rise, 31.8mm
Grips	Specialized Body Geometry Contour, lock-on
Front Brake	Shimano BR-MT200, hydraulic disc, 180mm Centerlock
Rear Brake	Shimano BR-MT200, hydraulic disc, 180mm 6-bolt
Shift Levers	enviolo Twist Display Pure
Cassette	Gates Carbon Drive CDC 24t sprocket, silver
Chain	Gates Carbon Drive CDX 122t belt, black
Crankset	Custom alloy forged crankarms
Chainrings	Gates Carbon Drive CDC 50T chainring, black
Pedals	Specialized Commuter w/ grip tape & reflectors
Rims	650b disc, double-wall alloy, pinned, 32h
Front Hub	Shimano MT400, Centerlock, 15x100mm, 32h
Rear Hub	enviolo CITY, 310% range, 6-bolt, 10x135mm, 32h
Spokes	DT Swiss Industry
Front Tire	Pathfinder Sport Reflect, 650Bx2.3
Rear Tire	Pathfinder Sport Reflect, 650Bx2.3
Inner Tubes	Schrader, 40mm valve
Saddle	Rivo Sport, steel rails, 155mm
SeatPost	Specialized, 6061 alloy, 2-bolt clamp, 0mm setback, 30.9mm
Seat Binder	Alloy, bolt-type, 34.9mm
Motor	Specialized 2.0E, 50Nm torque, custom tuned motor, 250W nominal
UI/Remote	MasterMind TCD, w/handlebar remote, built-in anti-theft feature, Bluetooth® connectivity, customizable display pages
Battery	Specialized U2-530, alloy casing, state of charge display, 530Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Wiring Harness	Custom wire harness
Headlight	Lezyne EBIKE MINI STVZO E65, 210 Lumen, 12V
Taillight	Spanninga Commuter Glow XE, 12V
Chaincase	Custom chaincover
Kickstand	Specialized kickstand, 40mm mount
Rack	Specialized rack, MIK HD interface, built-in pannier mounts, 27kg max load
Fenders	Specialized DRYTECH fenders, 65mm width, aluminum fenderstay
Bell	Simple bell

PART NO.	DESCRIPTION	COLOR	SIZE
95322-7402	VADO 3.0 IGH NB	Cast Black / Silver Reflective	S
95322-7403			M
95322-7404			L
95322-7405			XL
95322-7302	VADO 3.0 IGH NB	Red Tint / Silver Reflective	S
95322-7303			M
95322-7304			L
95322-7305			XL
95322-7502	VADO 3.0 IGH NB	White Mountains / Black Reflective	S
95322-7503			M
95322-7504			L
95322-7505			XL

TURBO VADO 3.0 IGH STEP-THROUGH



Cast Black / Silver Reflective



Red Tint / Silver Reflective



White Mountains / Black Reflective

Vado is the vehicle for everything from daily commutes to fast workouts to longer-than-planned adventures—an electric bike for life. The smoothest-riding e-Bike experience yet, Vado is designed to boldly take on the ever-changing landscape you'll encounter as a daily rider, carry whatever you need it to, and keep you riding more often.

- Turbo Full Power 2.0E motor and 530Wh battery offer an unparalleled riding experience, providing a smooth, seamless, and shockingly quiet amplification of your efforts, up to 25 kph. The integrated controller responds to your pedal inputs resulting in intuitive amplification of your efforts with an incredibly natural feel.
- MasterMind and Mission Control - The MasterMind display reveals all relevant info about your ride, allows real-time tuning of support levels, and enables over-the-air updates so that your bike gets better over time. MasterMind seamlessly integrates with the Mission Control app for range optimization tools, advanced tuning, on-ride diagnostics, and more.
- The stepless shifting enviolo City Internal Gear Hub (IGH) features a specifically designed internal gear hub and matching controller. The manual stepless technology is as simple as adjusting the volume on a radio. This allows riders to focus on the important aspects of a bike ride such as traffic or scenery.
- Proven Smooth Efficiency - We designed a custom testing mechanism to analyze bumps at even the smallest frequency to increase comfort and vision. That precision, paired with a suspended seatpost, higher volume tires, and an 80 mm suspension fork, will flatten roads before your eyes.
- Turbo System Lock - Use the Mission Control app to disable your bike's motor and activate the motion sensor alarm. Once locked, the motor cannot be enabled again except by the owner.
- Fully Integrated Removable and Lockable Downtube Battery - Easy to charge, easy to secure.
- Equipped with DRYTECH Fenders, LED front and rear lights, and 27kg capacity rear HD Rack. The rear rack is compatible with child bike seats, and the bike is also rated to pull a thru-axle trailer.

TURBO VADO 3.0 IGH STEP-THROUGH

	S	M	L	XL
Stack (mm)	625	639	652	676
Reach (mm)	423	444	464	481
Headtube Length (mm)	135	150	165	190
Headtube Angle (°)	68	68	68	68
BB Height (mm)	285	285	285	285
BB Drop (mm)	70	70	70	70
Trail (mm)	96	96	96	96
Fork Length (full) (mm)	480	480	480	480
Fork Rake/Offset (mm)	44	44	44	44
Front Center (mm)	699	724	750	777
Chainstay Length (mm)	470	470	470	470
Wheelbase (mm)	1160	1186	1212	1239
Toptube Length (horizontal) (mm)	585	615	645	675
Bike Standover Height (mm)	618	617	617	626
Seat Tube Length (mm)	400	450	460	500
Seat Tube Angle (Virtual) (°)	75.5	75	74.5	74
Crank Length (mm)	170	170	170	170
Handlebar Width (mm)	680	680	680	680
Stem Length (mm)	60	60	75	75
Saddle Width (mm)	155	155	155	155
Seatpost Length (mm)	300	400	400	400

SPECS

Specifications subject to change without notice.

Frame	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount, sliding dropout
Fork	SR Suntour MobieA32, 80mm travel, lockout, fender-mounts, integrated light mount
Stem	Specialized Flowset, 3D-forged alloy, 20-degree rise, 31.8mm clamp
Handlebars	Specialized, alloy, 15-degree backsweep, 46mm rise, 31.8mm
Grips	Specialized Body Geometry Contour, lock-on
Front Brake	Shimano BR-MT200, hydraulic disc, 180mm Centerlock
Rear Brake	Shimano BR-MT200, hydraulic disc, 180mm 6-bolt
Shift Levers	enviolo Twist Display Pure
Cassette	Gates Carbon Drive CDC 24t sprocket, silver
Chain	Gates Carbon Drive CDX 122t belt, black
Crankset	Custom alloy forged crankarms
Chainrings	Gates Carbon Drive CDC 50T chainring, black
Pedals	Specialized Commuter w/ grip tape & reflectors
Rims	650b disc, double-wall alloy, pinned, 32h
Front Hub	Shimano MT400, Centerlock, 15x100mm, 32h
Rear Hub	enviolo CITY, 310% range, 6-bolt, 10x135mm, 32h
Spokes	DT Swiss Industry
Front Tire	Pathfinder Sport Reflect, 650Bx2.3
Rear Tire	Pathfinder Sport Reflect, 650Bx2.3
Inner Tubes	Schrader, 40mm valve
Saddle	Rivo Sport, steel rails, 155mm
SeatPost	Specialized, 6061 alloy, 2-bolt clamp, 0mm setback, 30.9mm
Seat Binder	Alloy, bolt-type, 34.9mm
Motor	Specialized 2.0E, 50Nm torque, custom tuned motor, 250W nominal
UI/Remote	MasterMind TCD, w/handlebar remote, built-in anti-theft feature, Bluetooth* connectivity, customizable display pages
Battery	Specialized U2-530, alloy casing, state of charge display, 530Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Wiring Harness	Custom wire harness
Headlight	Lezyne EBIKE MINI STVZO E65, 210 Lumen, 12V
Taillight	Spanninga Commuter Glow XE, 12V
Chaincase	Custom chaincover
Kickstand	Specialized kickstand, 40mm mount
Rack	Specialized rack, MIK HD interface, built-in pannier mounts, 27kg max load
Fenders	Specialized DRYTECH fenders, 65mm width, aluminum fenderstay
Bell	Simple bell

PART NO.	DESCRIPTION	COLOR	SIZE
95322-6402	VADO 3.0 IGH ST	Cast Black / Silver Reflective	S
95322-6403			M
95322-6404			L
95322-6405			XL
95322-6302	VADO 3.0 IGH ST	Red Tint / Silver Reflective	S
95322-6303			M
95322-6304			L
95322-6305			XL
95322-6502	VADO 3.0 IGH ST	White Mountains / Black Reflective	S
95322-6503			M
95322-6504			L
95322-6505			XL

TURBO VADO 3.0



Cast Black / Silver Reflective



Red Tint / Silver Reflective



White Mountains / Black Reflective

Vado is the vehicle for everything from daily commutes to fast workouts to longer-than-planned adventures—an electric bike for life. The smoothest-riding e-Bike experience yet, Vado is designed to boldly take on the ever-changing landscape you'll encounter as a daily rider, carry whatever you need it to, and keep you riding more often.

- Turbo Full Power 2.0E motor and 530Wh battery offer an unparalleled riding experience, providing a smooth, seamless, and shockingly quiet amplification of your efforts, up to 25 kph. The integrated controller responds to your pedal inputs resulting in intuitive amplification of your efforts with an incredibly natural feel.
- MasterMind and Mission Control - The MasterMind display reveals all relevant info about your ride, allows real-time tuning of support levels, and enables over-the-air updates so that your bike gets better over time. MasterMind seamlessly integrates with the Mission Control app for range optimization tools, advanced tuning, on-ride diagnostics, and more.
- Proven Smooth Efficiency - We designed a custom testing mechanism to analyze bumps at even the smallest frequency to increase comfort and vision. That precision, paired with higher volume tires, and an 80 mm suspension fork, will flatten roads before your eyes.
- Turbo System Lock - Use the Mission Control app to disable your bike's motor and activate the motion sensor alarm. Once locked, the motor cannot be enabled again except by the owner.
- Fully Integrated Removable and Lockable Downtube Battery - Easy to charge, easy to secure.
- Equipped with DRYTECH Fenders, LED front and rear lights, and 27kg capacity rear HD Rack. The rear rack is compatible with child bike seats, and the bike is also rated to pull a thru-axle trailer.

TURBO VADO 3.0	S	M	L	XL
Stack (mm)	625	639	652	676
Reach (mm)	423	444	464	481
Headtube Length (mm)	135	150	165	190
Headtube Angle (°)	68	68	68	68
BB Height (mm)	285	285	285	285
BB Drop (mm)	70	70	70	70
Trail (mm)	96	96	96	96
Fork Length (full) (mm)	480	480	480	480
Fork Rake/Offset (mm)	44	44	44	44
Front Center (mm)	699	724	750	777
Chainstay Length (mm)	470	470	470	470
Wheelbase (mm)	1160	1186	1212	1239
Toptube Length (horizontal) (mm)	585	615	645	675
Bike Standover Height (mm)	735	771	771	805
Seat Tube Length (mm)	400	450	460	500
Seat Tube Angle (Virtual) (°)	75.5	75	74.5	74
Crank Length (mm)	170	170	170	170
Handlebar Width (mm)	680	680	680	680
Stem Length (mm)	60	60	75	75
Saddle Width (mm)	155	155	155	155
Seatpost Length (mm)	300	400	400	400

SPECS	Specifications subject to change without notice.
Frame	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount
Fork	SR Suntour MobieA32, 80mm travel, lockout, fender-mounts, integrated light mount
Stem	Specialized Flowset, 3D-forged alloy, 20-degree rise, 31.8mm clamp
Handlebars	Specialized, alloy, 15-degree backsweep, 46mm rise, 31.8mm
Grips	Specialized Body Geometry Contour, lock-on
Front Brake	Shimano BR-MT200, hydraulic disc, 180mm Centerlock
Rear Brake	Shimano BR-MT200, hydraulic disc, 180mm Centerlock
Rear Derailleur	Shimano Alivio, SGS, 9-speed
Shift Levers	Shimano Alivio, 9-speed w/ Optical Gear Display
Cassette	Shimano CS-HG400, 9-speed, 11-36t
Chain	KMC e9T, 9-speed w/ Missing Link™
Crankset	Custom alloy forged crankarms
Chainrings	Praxis, 48T, 104BCD
Pedals	Specialized Commuter w/ grip tape & reflectors
Rims	650b disc, double-wall alloy, pinned, 32h
Front Hub	Shimano MT400, Centerlock, 15x100mm, 32h
Rear Hub	Shimano MT400-B, Centerlock, 12x148 Boost, 32h
Spokes	DT Swiss Industry
Front Tire	Pathfinder Sport Reflect, 650Bx2.3
Rear Tire	Pathfinder Sport Reflect, 650Bx2.3
Inner Tubes	Schrader, 40mm valve
Saddle	Bridge Sport, Steel rails, 155mm
SeatPost	Specialized, 6061 alloy, 2-bolt clamp, 0mm setback, 30.9mm
Seat Binder	Alloy, bolt-type, 34.9mm
Motor	Specialized 2.0E, 50Nm torque, custom tuned motor, 250W nominal
UI/Remote	MasterMind TCD, w/handlebar remote, built-in anti-theft feature, Bluetooth® connectivity, customizable display pages
Battery	Specialized U2-530, alloy casing, state of charge display, 530Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Wiring Harness	Custom wire harness
Headlight	Lezyne EBIKE MINI STVZO E65, 210 Lumen, 12V
Taillight	Spanninga Commuter Glow XE, 12V
Chaincase	Custom chaincover
Kickstand	Specialized kickstand, 40mm mount
Rack	Specialized rack, MIK HD interface, built-in pannier mounts, 27kg max load
Fenders	Specialized DRYTECH fenders, 65mm width, aluminum fenderstay
Bell	Simple bell

PART NO.	DESCRIPTION	COLOR	SIZE
95022-7202	VADO 3.0 NB	Cast Black / Silver Reflective	S
95022-7203			M
95022-7204			L
95022-7205			XL
95022-7902	VADO 3.0 NB	Red Tint / Silver Reflective	S
95022-7903			M
95022-7904			L
95022-7905			XL
95022-7302	VADO 3.0 NB	White Mountains / Black Reflective	S
95022-7303			M
95022-7304			L
95022-7305			XL

TURBO VADO 3.0 STEP-THROUGH



Cast Black / Silver Reflective



Red Tint / Silver Reflective



White Mountains / Black Reflective

Vado is the vehicle for everything from daily commutes to fast workouts to longer-than-planned adventures—an electric bike for life. The smoothest-riding e-Bike experience yet, Vado is designed to boldly take on the ever-changing landscape you'll encounter as a daily rider, carry whatever you need it to, and keep you riding more often.

- Turbo Full Power 2.0E motor and 530Wh battery offer an unparalleled riding experience, providing a smooth, seamless, and shockingly quiet amplification of your efforts, up to 25 kph. The integrated controller responds to your pedal inputs resulting in intuitive amplification of your efforts with an incredibly natural feel.
- MasterMind and Mission Control - The MasterMind display reveals all relevant info about your ride, allows real-time tuning of support levels, and enables over-the-air updates so that your bike gets better over time. MasterMind seamlessly integrates with the Mission Control app for range optimization tools, advanced tuning, on-ride diagnostics, and more.
- Proven Smooth Efficiency - We designed a custom testing mechanism to analyze bumps at even the smallest frequency to increase comfort and vision. That precision, paired with higher volume tires, and an 80 mm suspension fork, will flatten roads before your eyes.
- Turbo System Lock - Use the Mission Control app to disable your bike's motor and activate the motion sensor alarm. Once locked, the motor cannot be enabled again except by the owner.
- Fully Integrated Removable and Lockable Downtube Battery - Easy to charge, easy to secure.
- Equipped with DRYTECH Fenders, LED front and rear lights, and 27kg capacity rear HD Rack. The rear rack is compatible with child bike seats, and the bike is also rated to pull a thru-axle trailer.

TURBO VADO 3.0 STEP-THROUGH

	S	M	L	XL
Stack (mm)	625	639	652	676
Reach (mm)	423	444	464	481
Headtube Length (mm)	135	150	165	190
Headtube Angle (°)	68	68	68	68
BB Height (mm)	285	285	285	285
BB Drop (mm)	70	70	70	70
Trail (mm)	96	96	96	96
Fork Length (full) (mm)	480	480	480	480
Fork Rake/Offset (mm)	44	44	44	44
Front Center (mm)	699	724	750	777
Chainstay Length (mm)	470	470	470	470
Wheelbase (mm)	1160	1186	1212	1239
Toptube Length (horizontal) (mm)	585	615	645	675
Bike Standover Height (mm)	618	617	617	626
Seat Tube Length (mm)	400	450	460	500
Seat Tube Angle (Virtual) (°)	75.5	75	74.5	74
Crank Length (mm)	170	170	170	170
Handlebar Width (mm)	680	680	680	680
Stem Length (mm)	60	60	75	75
Saddle Width (mm)	155	155	155	155
Seatpost Length (mm)	300	400	400	400

SPECS	Specifications subject to change without notice.
Frame	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount
Fork	SR Suntour MobieA32, 80mm travel, lockout, fender-mounts, integrated light mount
Stem	Specialized Flowset, 3D-forged alloy, 20-degree rise, 31.8mm clamp
Handlebars	Specialized, alloy, 15-degree backsweep, 46mm rise, 31.8mm
Grips	Body Geometry Women's Contour
Front Brake	Shimano BR-MT200, hydraulic disc, 180mm Centerlock
Rear Brake	Shimano BR-MT200, hydraulic disc, 180mm Centerlock
Rear Derailleur	Shimano Alivio, SGS, 9-speed
Shift Levers	Shimano Alivio, 9-speed w/ Optical Gear Display
Cassette	Shimano CS-HG400, 9-speed, 11-36t
Chain	KMC e9T, 9-speed w/ Missing Link™
Crankset	Custom alloy forged crankarms
Chainrings	Praxis, 48T, 104BCD
Pedals	Specialized Commuter w/ grip tape & reflectors
Rims	650b disc, double-wall alloy, pinned, 32h
Front Hub	Shimano MT400, Centerlock, 15x100mm, 32h
Rear Hub	Shimano MT400-B, Centerlock, 12x148 Boost, 32h
Spokes	DT Swiss Industry
Front Tire	Pathfinder Sport Reflect, 650Bx2.3
Rear Tire	Pathfinder Sport Reflect, 650Bx2.3
Inner Tubes	Schrader, 40mm valve
Saddle	Rivo Sport, steel rails, 155mm
SeatPost	Specialized, 6061 alloy, 2-bolt clamp, 0mm setback, 30.9mm
Seat Binder	Alloy, bolt-type, 34.9mm
Motor	Specialized 2.0E, 50Nm torque, custom tuned motor, 250W nominal
UI/Remote	MasterMind TCD, w/handlebar remote, built-in anti-theft feature, Bluetooth® connectivity, customizable display pages
Battery	Specialized U2-530, alloy casing, state of charge display, 530Wh
Charger	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Wiring Harness	Custom wire harness
Headlight	Lezyne EBIKE MINI STVZO E65, 210 Lumen, 12V
Taillight	Spanninga Commuter Glow XE, 12V
Chaincase	Custom chaincover
Kickstand	Specialized kickstand, 40mm mount
Rack	Specialized rack, MIK HD interface, built-in pannier mounts, 27kg max load
Fenders	Specialized DRYTECH fenders, 65mm width, aluminum fenderstay
Bell	Simple bell

PART NO.	DESCRIPTION	COLOR	SIZE
95022-7602	VADO 3.0 STEP THROUGH	Cast Black / Silver Reflective	S
95022-7603			M
95022-7604			L
95022-7605			XL
95022-6102	VADO 3.0 STEP THROUGH	Red Tint / Silver Reflective	S
95022-6103			M
95022-6104			L
95022-6105			XL
95022-7702	VADO 3.0 STEP THROUGH	White Mountains / Black Reflective	S
95022-7703			M
95022-7704			L
95022-7705			XL

VADO SL

TURBO VADO SL 5.0 EQ



Brassy Yellow / Black Reflective



Brushed Aluminum / Black Reflective

There's no other e-bike out there with ride quality, range, and power like this, at a weight that's light enough to carry. The Turbo Vado SL 5.0 EQ is best for your daily commute, quick errands and getting around town. Extra-bright, built-in lights in front and back mean you'll see and be seen. DRYTECH fenders keep water and road spray away, and a standard rear rack is always ready for your bags and panniers. This is your go-to for local transportation.

- Integrated Turbo Connect Display to view key ride data quickly and safely.
- Fully integrated and secure Specialized 320Wh downtube battery w/optional Range Extender compatibility for up to 120 miles of range.
- Specialized SL 1.1 custom lightweight motor, peak 240W / 35Nm, 2x you rider amplification (180% assistance), assist up to 25 kph.
- Lightweight and high-strength premium carbon fork with Boost™ 12x110mm thru-axle.
- Future Shock 1.5 reduces impacts from rough roads and terrain, potholes be gone!
- Premium hydraulic disc brakes for maximum stopping power.
- Extra-bright front and rear lighting to see and be seen.

TURBO VADO SL 5.0 EQ	S	M	L	XL
Stack (mm)	595	626	660	696
Reach (mm)	378	401	415	424
Head-Tube Length (mm)	185	217	250	285
Head-Tube Angle (°)	70	70.5	71	71.5
B-B Height (mm)	270	270	270	270
B-B Drop (mm)	70	70	70	70
Trail (mm)	71	67	64	61
Fork Length (full) (mm)	390	390	390	390
Fork Rake/Offset (mm)	50	50	50	50
Front-Center (mm)	626	655	675	690
Chain-Stay Length (mm)	445	445	445	445
Wheelbase (mm)	1062	1091	1110	1126
Top-Tube Length (horizontal) (mm)	554	587	610	630
Bike Stand-Over Height (mm)	770	790	815	840
Seat-Tube Length (mm)	415	446.5	494.5	535
Seat-Tube Angle (°)	73.5	73.5	73.5	73.5
Crank Length (mm)	170	172.5	172.5	175
Handlebar Width (mm)	680	680	680	680
Stem Length (mm)	60	75	75	90
Saddle Width (mm)	155	155	155	155
Seatpost Length (mm)	350	350	350	350

SPECS	Specifications subject to change without notice.
Frame	E5 Aluminum, bottom bracket motor mount, fully integrated downtube battery, internal cable routing, fender and front rack mounts, Smooth Welds
Fork	Rigid carbon fork, Boost™ 12x110mm thru-axle, flat mount disc
Stem	Specialized Stealth Stem, alloy, 14 deg, 31.8mm, integrated TCD mount
Handlebars	Specialized, alloy, 9-degree backsweep, 15mm rise, 31.8mm
Grips	Specialized Body Geometry Contour, lock-on
Front Brake	Tekro HD-R510, hydraulic disc, 160mm
Rear Brake	Tekro HD-R510, hydraulic disc, 160mm
Rear Derailleur	Shimano XT, Shadow Plus, SGS Cage, 12-speed
Shift Levers	Shimano SLX, Rapidfire Plus, 12-speed, w/o OGD
Cassette	Shimano SLX, Hyperglide+, 12-speed, 10-45t
Chain	Shimano SLX, 12-speed, w/Quick Link
Crankset	Praxis, Forged alloy M30, custom offset
Chainrings	Praxis, 44T, 104BCD
Pedals	Specialized Commuter w/ grip tape & reflectors
Rims	DT Swiss R500 disc, 22mm internal width, 23mm internal depth
Front Hub	Specialized alloy front hub disc, sealed cartridge bearings, 12x110mm, Center Lock™, 24h
Rear Hub	Specialized alloy rear hub disc, Center Lock™, sealed cartridge bearings, 12x148mm, 28h
Spokes	DT Swiss Industry
Front Tire	Nimbus II Sport Reflect, 700x38mm
Rear Tire	Nimbus II Sport Reflect, 700x38mm
Inner Tubes	Standard 40mm PV 700x32-50
Saddle	Bridge Sport, hollow cr-mo rails, 155mm
SeatPost	Specialized, alloy, 2-bolt, 12.5mm offset, 27.2mm
Seat Binder	Integrated w/ frame
Motor	Specialized SL 1.1, custom lightweight motor
UI/Remote	Specialized MasterMind TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®, w/Handlebar remote
Battery	Specialized SL1-320, fully integrated, 320Wh
Charger	Custom charger, 48V System w/ SL system charger plug
Wiring Harness	Custom Specialized wiring harness w/ chargeport
Headlight	Lezyne Ebike Power STVZO E115, 310Lumens, 12V
Taillight	Lezyne Ebike Rear Fender STVZO, 11Lumens, 12V
Kickstand	Specialized kickstand, 40mm mount
Rack	Turbo SL Rack, Closed Platform, direct fender mount, Racktime-compatible, 15kg
Fenders	Specialized DryTech, Aluminum
Bell	Simple bell

PART NO.	DESCRIPTION	COLOR	SIZE
93922-3002	VADO SL 5.0 EQ	Brassy Yellow / Black Reflective	S
93922-3003			M
93922-3004			L
93922-3005			XL
93922-3202	VADO SL 5.0 EQ	Brushed Aluminum / Black Reflective	S
93922-3203			M
93922-3204			L
93922-3205			XL

TURBO VADO SL 5.0 STEP-THROUGH EQ



Brushed / Black Reflective

There's no other e-bike out there with ride quality, range, and power like this, at a weight that's light enough to carry. The Turbo Vado Super Light 5.0 EQ is best for your daily commute, quick errands and getting around town. Extra-bright, built-in lights in front and back mean you'll see and be seen. DRYTECH fenders keep water and road spray away, and a standard rear rack is always ready for your bags and panniers. This is your go-to for local transportation.

- Integrated Turbo Connect Display to view key ride data quickly and safely.
- Fully integrated and secure Specialized 320Wh downtube battery w/optional Range Extender compatibility for up to 120 miles of range.
- Specialized SL 1.1 custom lightweight motor, peak 240W / 35Nm, 2x you rider amplification (180% assistance), assist up to 25 kph depending on your country
- Lightweight and high-strength premium carbon fork with Boost™ 12x110mm thru-axle.
- Future Shock 1.5 reduces impacts from rough roads and terrain.
- Step-through frame for easier on/off and managing commuter traffic.
- Premium hydraulic disc brakes for maximum stopping power.
- Extra-bright front and rear lighting to see and be seen.
- Turbo SL mounted rear rack, Racktime-compatible for your favorite bags and panniers, and DRYTECH fenders to keep the spray away.
- 12-speed Sram GX derailleur and shifter for lightweight, precise performance for the long haul.

TURBO VADO SL 5.0 STEP-THROUGH EQ

	S	M	L	XL
Stack (mm)	595	626	660	696
Reach (mm)	378	401	415	424
Head-Tube Length (mm)	185.5	217	250	285.5
Head-Tube Angle (°)	70	70.5	71	71.5
B-B Height (mm)	291	291	291	291
B-B Drop (mm)	70	70	70	70
Trail (mm)	71	67	64	61
Fork Length (full) (mm)	390	390	390	390
Fork Rake/Offset (mm)	50	50	50	50
Front-Center (mm)	626	655	675	690
Chain-Stay Length (mm)	445	445	445	445
Wheelbase (mm)	1062	1091	1110	1126
Top-Tube Length (horizontal) (mm)	554	587	610	630
Bike Stand-Over Height (mm)	616	631	655	688
Seat-Tube Length (mm)	405	431.5	469.5	510
Seat-Tube Angle (°)	73.5	73.5	73.5	73.5
Crank Length (mm)	170	172.5	172.5	175
Handlebar Width (mm)	680	680	680	680
Stem Length (mm)	60	75	75	90
Saddle Width (mm)	155	155	155	155
Seatpost Length (mm)	350	350	350	350

SPECS

Specifications subject to change without notice.

Frame	E5 Aluminum, bottom bracket motor mount, fully integrated downtube battery, internal cable routing, fender and front rack mounts, Smooth Welds
Fork	Rigid carbon fork, Boost™ 12x110mm thru-axle, flat mount disc
Stem	Specialized Stealth Stem, alloy, 14 deg, 31.8mm, integrated TCD mount
Handlebars	Specialized, alloy, 9-degree backsweep, 15mm rise, 31.8mm
Grips	Body Geometry Women's Contour
Front Brake	Tekro HD-R510, hydraulic disc, 160mm
Rear Brake	Tekro HD-R510, hydraulic disc, 160mm
Rear Derailleur	SRAM GX Eagle, 12-speed
Shift Levers	SRAM GX Eagle, 12-speed
Cassette	SRAM NX Eagle PG-1230, 12-speed, 11-50t
Chain	SRAM NX Eagle, 12-speed
Crankset	Praxis, Forged alloy M30, custom offset
Chainrings	Praxis, 44T, 110BCD
Pedals	Specialized Commuter w/ grip tape & reflectors
Rims	DT Swiss R500 disc, 22mm internal width, 23mm internal depth
Front Hub	Specialized alloy front hub disc, sealed cartridge bearings, 12x110mm, Center Lock™, 24h
Rear Hub	Specialized alloy rear hub disc, Center Lock™, sealed cartridge bearings, 12x148mm, 28h
Spokes	DT Swiss Industry
Front Tire	Nimbus II Sport Reflect, 700x38mm
Rear Tire	Nimbus II Sport Reflect, 700x38mm
Inner Tubes	Standard 40mm PV 700x32-50
Saddle	Bridge Sport, hollow cr-mo rails, 155mm
SeatPost	Specialized, alloy, 2-bolt, 12.5mm offset, 27.2mm
Seat Binder	Specialized Alloy, 30.8mm
Motor	Specialized SL 1.1, custom lightweight motor
UI/Remote	Specialized Mastermind TCU, TFT-screen, fully custom steup, ANT+/Bluetooth®, w/Handlebar remote
Battery	Specialized SL1-320, fully integrated, 320Wh
Charger	Custom charger, 48V System w/ SL system charger plug
Wiring Harness	Custom Specialized wiring harness w/ chargeport
Headlight	Lezyne Ebike Power STVZO E115, 310Lumens, 12V
Taillight	Lezyne Ebike Rear Fender STVZO, 11Lumens, 12V
Kickstand	Specialized kickstand, 40mm mount
Rack	Turbo SL Rack, Closed Platform, direct fender mount, Racktime-compatible, 15kg
Fenders	Specialized DryTech, Aluminum
Bell	Simple bell

PART NO.	DESCRIPTION	COLOR	SIZE
93922-3302	VADO SL 5.0 STEP THROUGH EQ	Brushed / Black Reflective	S
93922-3303			M
93922-3304			L
93922-3305			XL
93923-3002	VADO SL 5.0 STEP THROUGH EQ	Brushed Aluminum / Black Reflective	S
93923-3003			M
93923-3004			L
93923-3005			XL

TURBO VADO SL 5.0



Brushed Aluminum / Black Reflective

There's no other e-bike out there with ride quality, range, and power like this, at a weight that's light enough to carry. The Turbo Vado SL 5.0 is best for workouts, riding beyond the beaten path and last-minute adventures. All you need to do is get on and go. Extra-bright, built-in lights in front and back mean you'll see and be seen. A Turbo Connect display makes it easy to view ride info. Plus, Pathfinder tires roll fast on or off the pavement with plenty of grip.

- Integrated Turbo Connect Display to view key ride data quickly and safely.
- Fully integrated and secure Specialized 320Wh downtube battery w/optional Range Extender compatibility for up to 120 miles of range.
- Specialized SL 1.1 custom lightweight motor, peak 240W / 35Nm, 2x you rider amplification (180% assistance), assist up to 25 kph.
- Lightweight and high-strength premium carbon fork with Boost™ 12x110mm thru-axle.
- Future Shock 1.5 reduces impacts from rough roads and terrain, potholes be gone!
- Premium hydraulic disc brakes for maximum stopping power.
- Extra-bright front and rear lighting to see and be seen.

TURBO VADO SL 5.0	S	M	L	XL
Stack (mm)	595	626	660	696
Reach (mm)	378	401	415	424
Head-Tube Length (mm)	185	217	250	285
Head-Tube Angle (°)	70	70.5	71	71.5
B-B Height (mm)	270	270	270	270
B-B Drop (mm)	70	70	70	70
Trail (mm)	71	67	64	61
Fork Length (full) (mm)	390	390	390	390
Fork Rake/Offset (mm)	50	50	50	50
Front-Center (mm)	626	655	675	690
Chain-Stay Length (mm)	445	445	445	445
Wheelbase (mm)	1062	1091	1110	1126
Top-Tube Length (horizontal) (mm)	554	587	610	630
Bike Stand-Over Height (mm)	770	790	815	840
Seat-Tube Length (mm)	415	446.5	494.5	535
Seat-Tube Angle (°)	73.5	73.5	73.5	73.5
Crank Length (mm)	170	172.5	172.5	175
Handlebar Width (mm)	680	680	680	680
Stem Length (mm)	60	75	75	90
Saddle Width (mm)	155	155	155	155
Seatpost Length (mm)	350	350	350	350

SPECS	Specifications subject to change without notice.
Frame	E5 Aluminum, bottom bracket motor mount, fully integrated downtube battery, internal cable routing, fender and front rack mounts, Smooth Welds
Fork	Rigid carbon fork, Boost™ 12x110mm thru-axle, flat mount disc
Stem	Specialized Stealth Stem, alloy, 14 deg, 31.8mm, integrated TCD mount
Handlebars	Specialized, alloy, 9-degree backsweep, 15mm rise, 31.8mm
Grips	Specialized Body Geometry Contour, lock-on
Front Brake	Tektro HD-R510, hydraulic disc, 160mm
Rear Brake	Tektro HD-R510, hydraulic disc, 160mm
Rear Derailleur	Shimano XT, Shadow Plus, SGS Cage, 12-speed
Shift Levers	Shimano SLX, Rapidfire Plus, 12-speed, w/o OGD
Cassette	Shimano SLX, Hyperglide+, 12-speed, 10-45t
Chain	Shimano SLX, 12-speed, w/Quick Link
Crankset	Praxis, Forged alloy M30, custom offset
Chainrings	Praxis, 44T, 104BCD
Pedals	Specialized Commuter w/ grip tape & reflectors
Rims	DT Swiss R500 disc, 22mm internal width, 23mm internal depth
Front Hub	Specialized alloy front hub disc, sealed cartridge bearings, 12x110mm, Center Lock™, 24h
Rear Hub	Specialized alloy rear hub disc, Center Lock™, sealed cartridge bearings, 12x148mm, 28h
Spokes	DT Swiss Industry
Front Tire	Specialized Pathfinder Sport, 700x38c
Rear Tire	Specialized Pathfinder Sport, 700x38c
Inner Tubes	Standard 40mm PV 700x32-50
Saddle	Bridge Sport, hollow cr-mo rails, 155mm
SeatPost	Specialized, alloy, single bolt, 21mm offset, 27.2mm
Seat Binder	Integrated w/ frame
Motor	Specialized SL 1.1, custom lightweight motor
UI/Remote	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®, w/Handlebar remote
Battery	Specialized SL1-320, fully integrated, 320Wh
Charger	Custom charger, 48V System w/ SL system charger plug
Wiring Harness	Custom Specialized wiring harness w/ chargeport
Headlight	Lezyne Ebike Power STVZO E115, 310Lumens, 12V
Taillight	Specialized integrated saddle mount, LED Technology, 12V
Bell	Simple bell

PART NO.	DESCRIPTION	COLOR	SIZE
93922-3102	VADO SL 5.0	Brushed Aluminum / Black Reflective	S
93922-3103			M
93922-3104			L
93922-3105			XL

TURBO VADO SL 4.0 EQ



Smoke / Black Reflective



White Sage / Black Reflective

There's no other e-bike out there with ride quality, range, and power like this, at a weight that's light enough to carry. The Turbo Vado SL 4.0 EQ is best for your daily commute, quick errands and getting around town. Extra-bright, built-in lights in front and back mean you'll see and be seen. DRYTECH fenders keep water and road spray away, and a standard rear rack is always ready for your bags and panniers. This is your go-to for local transportation.

- Fully integrated and secure Specialized 320Wh downtube battery w/optional Range Extender compatibility for up to 120 miles of range.
- Specialized SL 1.1 custom lightweight motor, peak 240W / 35Nm, 2x you rider amplification (180% assistance), assist up to 25 kph.
- Turbo SL mounted rear rack, Racktime-compatible for your favorite bags and panniers, and DRYTECH fenders to keep the spray away.
- Premium lightweight E5 Aluminum frame.
- Clean internal cable routing, fender/rack mounts, and reflective graphics.
- Premium hydraulic disc brakes for maximum stopping power.
- Bright, integrated front and rear lighting to see and be seen.

TURBO VADO SL 4.0 EQ	S	M	L	XL
Stack (mm)	542	574	607	643
Reach (mm)	397	419	433	442
Head-Tube Length (mm)	130	161.5	194.5	230
Head-Tube Angle (°)	70	70.5	71	71.5
B-B Height (mm)	291	291	291	291
B-B Drop (mm)	70	70	70	70
Trail (mm)	78	75	71	68
Fork Length (full) (mm)	390	390	390	390
Fork Rake/Offset (mm)	50	50	50	50
Front-Center (mm)	626	655	675	690
Chain-Stay Length (mm)	445	445	445	445
Wheelbase (mm)	1062	1091	1110	1126
Top-Tube Length (horizontal) (mm)	558	589	613	632
Bike Stand-Over Height (mm)	791	811	836	861
Seat-Tube Length (mm)	415	446.5	494.5	535
Seat-Tube Angle (°)	73.5	73.5	73.5	73.5
Crank Length (mm)	170	172.5	172.5	175
Handlebar Width (mm)	680	680	680	680
Stem Length (mm)	60	75	75	90
Saddle Width (mm)	155	155	155	155
Seatpost Length (mm)	350	350	350	350

SPECS	Specifications subject to change without notice.
Frame	E5 Aluminum, bottom bracket motor mount, fully integrated downtube battery, internal cable routing, fender and front rack mounts, Smooth Welds
Fork	Rigid full aluminum disc, Boost™ 12x110mm, front-rack-compatible
Stem	Specialized Stealth Stem, alloy, 14 deg, 31.8mm, integrated TCD mount
Handlebars	Specialized, alloy, 9-degree backsweep, 15mm rise, 31.8mm
Grips	Specialized Body Geometry Contour, lock-on
Front Brake	Tektro HD-R290, hydraulic disc, 160mm
Rear Brake	Tektro HD-R290, hydraulic disc, 160mm
Rear Derailleur	Shimano Deore, Shadow Plus, GS cage, 10-speed
Shift Levers	Shimano Deore, RapidFire Plus, 10-speed w/ Optical Gear Display
Cassette	Shimano Deore, 10spd, 11-42t
Chain	KMC e11S, 11-speed w/ Missing Link™
Crankset	Praxis, Forged alloy M30, custom offset
Chainrings	Praxis, 44T, 104BCD
Pedals	Specialized Commuter w/ grip tape & reflectors
Rims	700C disc, 22mm rim depth, 21mm internal width
Front Hub	Specialized alloy front hub disc, sealed cartridge bearings, 12x110mm, Center Lock™, 24h
Rear Hub	Specialized alloy rear hub disc, Center Lock™, sealed cartridge bearings, 12x148mm, 28h
Spokes	DT Swiss Industry
Front Tire	Nimbus II Sport Reflect, 700x38mm
Rear Tire	Nimbus II Sport Reflect, 700x38mm
Inner Tubes	Standard 40mm PV 700x32-50
Saddle	Bridge Sport, hollow cr-mo rails, 155mm
SeatPost	Specialized, alloy, dual-bolt, 25mm offset, 27.2mm
Seat Binder	Integrated w/ frame
Motor	Specialized SL 1.1, custom lightweight motor
UI/Remote	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®, w/Handlebar remote
Battery	Specialized SL1-320, fully integrated, 320Wh
Charger	Custom charger, 48V System w/ SL system charger plug
Wiring Harness	Custom Specialized wiring harness w/ chargeport
Headlight	Lezyne Ebike Hecto STVZO E65, 210Lumens, 12V
Taillight	Lezyne Ebike Rear Fender STVZO, 11Lumens, 12V
Kickstand	Specialized kickstand, 40mm mount
Rack	Turbo SL Rack, Closed Platform, direct fender mount, Racktime-compatible, 15kg
Fenders	Specialized DryTech, Aluminum
Bell	Simple bell

PART NO.	DESCRIPTION	COLOR	SIZE
93922-5302	VADO SL 4.0 EQ	Smoke / Black Reflective	S
93922-5303			M
93922-5304			L
93922-5305			XL
93922-5202	VADO SL 4.0 EQ	White Sage / Black Reflective	S
93922-5203			M
93922-5204			L
93922-5205			XL

TURBO VADO SL 4.0 STEP-THROUGH EQ



Raspberry / Black Reflective



White Sage / Black Reflective

There's no other e-bike out there with ride quality, range, and power like this, at a weight that's light enough to carry. The Turbo Vado Super Light 4.0 EQ is best for your daily commute, quick errands and getting around town. Extra-bright, built-in lights in front and back mean you'll see and be seen. DRYTECH fenders keep water and road spray away, and a standard rear rack is always ready for your bags and panniers. This is your go-to for local transportation.

- Fully integrated and secure Specialized 320Wh downtube battery w/optional Range Extender compatibility for up to 120 miles of range.
- Specialized SL 1.1 custom lightweight motor, peak 240W / 35Nm, 2x you rider amplification (180% assistance), assist up to 25 kph.
- Turbo SL mounted rear rack, Racktime-compatible for your favorite bags and panniers, and DRYTECH fenders to keep the spray away.
- Premium lightweight E5 Aluminum frame.
- Clean internal cable routing, fender/rack mounts, and reflective graphics.
- Step-through frame for easier on/off and managing commuter traffic.
- Premium hydraulic disc brakes for maximum stopping power.
- Bright, integrated front and rear lighting to see and be seen.
- 11-speed Sram NX shifting for reliable performance for the long haul.
- Durable, lightweight alloy wheels paired with fast-rolling, high-grip, Nimbus II Sport Reflect 700 tires with BlackBelt flat protection and reflective accents to increase visibility.

TURBO VADO SL 4.0 STEP-THROUGH EQ

	S	M	L	XL
Stack (mm)	542	574	607	643
Reach (mm)	397	419	433	442
Head-Tube Length (mm)	130	161.5	194.5	230
Head-Tube Angle (°)	70	70.5	71	71.5
B-B Height (mm)	291	291	291	291
B-B Drop (mm)	70	70	70	70
Trail (mm)	71	67	64	61
Fork Length (full) (mm)	390	390	390	390
Fork Rake/Offset (mm)	50	50	50	50
Front-Center (mm)	626	655	675	690
Chain-Stay Length (mm)	445	445	445	445
Wheelbase (mm)	1062	1091	1110	1126
Top-Tube Length (horizontal) (mm)	558	587	610	630
Bike Stand-Over Height (mm)	616	631	655	688
Seat-Tube Length (mm)	405	431.5	469.5	510
Seat-Tube Angle (°)	73.5	73.5	73.5	73.5
Crank Length (mm)	170	172.5	172.5	175
Handlebar Width (mm)	680	680	680	680
Stem Length (mm)	60	75	75	90
Saddle Width (mm)	155	155	155	155
Seatpost Length (mm)	350	350	350	350

SPECS

Specifications subject to change without notice.

Frame	E5 Aluminum, bottom bracket motor mount, fully integrated downtube battery, internal cable routing, fender and front rack mounts, Smooth Welds
Fork	Rigid full aluminum disc, Boost™ 12x110mm, front-rack-compatible
Stem	Specialized Stealth Stem, alloy, 14 deg, 31.8mm, integrated TCD mount
Handlebars	Specialized, alloy, 9-degree backsweep, 15mm rise, 31.8mm
Grips	Body Geometry Women's Contour
Front Brake	Tektro HD-R290, hydraulic disc, 160mm
Rear Brake	Tektro HD-R290, hydraulic disc, 160mm
Rear Derailleur	SRAM NX, 11-speed
Shift Levers	Sram NX, 11-speed, multi-shift
Cassette	SUNRACE, CSMS7, 11-42t, 11-speed
Chain	KMC X11eT, 11-speed
Crankset	Praxis, Forged alloy M30, custom offset
Chainrings	Praxis, 44T, 110BCD
Pedals	Specialized Commuter w/ grip tape & reflectors
Rims	700C disc, 22mm rim depth, 21mm internal width
Front Hub	Specialized alloy front hub disc, sealed cartridge bearings, Center Lock™, 12x110mm, 24h
Rear Hub	Specialized alloy rear hub disc, sealed cartridge bearings, Center Lock™, 12x148mm, 28h
Spokes	DT Swiss Industry
Front Tire	Nimbus II Sport Reflect, 700x38mm
Rear Tire	Nimbus II Sport Reflect, 700x38mm
Inner Tubes	Standard 40mm PV 700x32-50
Saddle	Bridge Sport, hollow cr-mo rails, 155mm
SeatPost	Specialized, alloy, dual-bolt, 25mm offset, 27.2mm
Seat Binder	Specialized Alloy, 30.8mm
Motor	Specialized SL 1.1, custom lightweight motor
UI/Remote	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®, w/Handlebar remote
Battery	Specialized SL1-320, fully integrated, 320Wh
Charger	Custom charger, 48V System w/ SL system charger plug
Wiring Harness	Custom Specialized wiring harness w/ chargeport
Headlight	Lezyne Ebike Hecto STVZO E65, 210Lumens, 12V
Taillight	Lezyne Ebike Rear Fender STVZO, 11Lumens, 12V
Kickstand	Specialized kickstand, 40mm mount
Rack	Turbo SL Rack, Closed Platform, direct fender mount, Racktime-compatible, 15kg
Fenders	Specialized DryTech, Aluminum
Bell	Simple bell

PART NO.	DESCRIPTION	COLOR	SIZE
93921-5302	VADO SL 4.0 ST EQ	Raspberry / Black Reflective	S
93921-5303			M
93921-5304			L
93921-5305			XL
93921-5202	VADO SL 4.0 ST EQ	White Sage / Black Reflective	S
93921-5203			M
93921-5204			L
93921-5205			XL
93923-5302	VADO SL 4.0 ST EQ	Raspberry / Black Reflective	S
93923-5303			M
93923-5304			L
93923-5305			XL
93923-5202	VADO SL 4.0 ST EQ	White Sage / Black Reflective	S
93923-5203			M
93923-5204			L
93923-5205			XL

TURBO VADO SL 4.0



Limestone / Black Reflective



Smoke / Black Reflective

There's no other e-bike out there with ride quality, range, and power like this, at a weight that's light enough to carry. The Turbo Vado SL 4.0 is best for workouts, riding beyond the beaten path and last-minute adventures. All you need to do is get on and go. Extra-bright, built-in lights in front and back mean you'll see and be seen. Plus, Pathfinder tires roll fast on or off the pavement with plenty of grip.

- Fully integrated and secure Specialized 320Wh downtube battery w/optional Range Extender compatibility for up to 120 miles of range.
- Specialized SL 1.1 custom lightweight motor, peak 240W / 35Nm, 2x you rider amplification (180% assistance), assist up to 25 kph.
- Premium lightweight E5 Aluminum frame.
- Clean internal cable routing, fender/rack mounts, and reflective graphics.
- Premium hydraulic disc brakes for maximum stopping power.
- Bright, integrated front and rear lighting to see and be seen.
- 10-speed Shimano Deore shifting for reliable performance for the long haul.

TURBO VADO SL 4.0	S	M	L	XL
Stack (mm)	542	574	607	643
Reach (mm)	397	419	433	442
Head-Tube Length (mm)	130	161.5	194.5	230
Head-Tube Angle (°)	70	70.5	71	71.5
B-B Height (mm)	291	291	291	291
B-B Drop (mm)	70	70	70	70
Trail (mm)	78	75	71	68
Fork Length (full) (mm)	390	390	390	390
Fork Rake/Offset (mm)	50	50	50	50
Front-Center (mm)	626	655	675	690
Chain-Stay Length (mm)	445	445	445	445
Wheelbase (mm)	1062	1091	1110	1126
Top-Tube Length (horizontal) (mm)	558	589	613	632
Bike Stand-Over Height (mm)	791	811	836	861
Seat-Tube Length (mm)	415	446.5	494.5	535
Seat-Tube Angle (°)	73.5	73.5	73.5	73.5
Crank Length (mm)	170	172.5	172.5	175
Handlebar Width (mm)	680	680	680	680
Stem Length (mm)	60	75	75	90
Saddle Width (mm)	155	155	155	155
Seatpost Length (mm)	350	350	350	350

SPECS	Specifications subject to change without notice.
Frame	E5 Aluminum, bottom bracket motor mount, fully integrated downtube battery, internal cable routing, fender and front rack mounts, Smooth Welds
Fork	Rigid full aluminum disc, Boost™ 12x110mm, front-rack-compatible
Stem	Specialized Stealth Stem, alloy, 14 deg, 31.8mm, integrated TCD mount
Handlebars	Specialized, alloy, 9-degree backsweep, 15mm rise, 31.8mm
Front Brake	Tektro HD-R290, hydraulic disc, 160mm
Rear Brake	Tektro HD-R290, hydraulic disc, 160mm
Rear Derailleur	Shimano Deore, Shadow Plus, GS cage, 10-speed
Shift Levers	Shimano Deore, RapidFire Plus, 10-speed w/ Optical Gear Display
Cassette	Shimano Deore, 10spd, 11-42t
Chain	KMC e11S, 11-speed w/ Missing Link™
Crankset	Praxis, Forged alloy M30, custom offset
Chainrings	Praxis, 44T, 104BCD
Pedals	Specialized Commuter w/ grip tape & reflectors
Rims	700C disc, 22mm rim depth, 21mm internal width
Front Hub	Specialized alloy front hub disc, sealed cartridge bearings, 12x110mm, Center Lock™, 24h
Rear Hub	Specialized alloy rear hub disc, Center Lock™, sealed cartridge bearings, 12x148mm, 28h
Spokes	DT Swiss Industry
Front Tire	Specialized Pathfinder Sport, 700x38c
Rear Tire	Specialized Pathfinder Sport, 700x38c
Inner Tubes	Standard 40mm PV 700x32-50
Saddle	Bridge Sport, Steel rails, 155mm
SeatPost	Specialized, alloy, dual-bolt, 25mm offset, 27.2mm
Seat Binder	Integrated w/ frame
Motor	Specialized SL 1.1, custom lightweight motor
UI/Remote	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®, w/Handlebar remote
Battery	Specialized SL1-320, fully integrated, 320Wh
Charger	Custom charger, 48V System w/ SL system charger plug
Wiring Harness	Custom Specialized wiring harness w/ chargeport
Headlight	Lezyne Ebike Hecto STVZO E65, 210Lumens, 12V
Taillight	Specialized integrated saddle mount, LED Technology, 12V
Bell	Simple bell

PART NO.	DESCRIPTION	COLOR	SIZE
93922-5002	VADO SL 4.0	Limestone / Black Reflective	S
93922-5003			M
93922-5004			L
93922-5005			XL
93922-5102	VADO SL 4.0	Smoke / Black Reflective	S
93922-5103			M
93922-5104			L
93922-5105			XL

TURBO VADO SL 4.0 STEP-THROUGH



Cast Umber / Silver Reflective



Limestone / Black Reflective

There's no other e-bike out there with ride quality, range, and power like this, at a weight that's light enough to carry. The Turbo Vado Super Light 4.0 is best for workouts, riding beyond the beaten path and last-minute adventures. All you need to do is get on and go. Extra-bright, built-in lights in front and back mean you'll see and be seen. Plus, Pathfinder tires roll fast on or off the pavement with plenty of grip.

- Fully integrated and secure Specialized 320Wh downtube battery w/optional Range Extender compatibility for up to 120 miles of range.
- Specialized SL 1.1 custom lightweight motor, peak 240W / 35Nm, 2x you rider amplification (180% assistance), assist up to 25 kph depending on your country
- Premium lightweight E5 Aluminum frame.
- Clean internal cable routing, fender/rack mounts, and reflective graphics.
- Step-through frame for easier on/off and managing commuter traffic.
- Premium hydraulic disc brakes for maximum stopping power.
- Bright, integrated front and rear lighting to see and be seen.
- 11-speed Sram NX shifting for reliable performance for the long haul.
- Durable, lightweight alloy wheels paired with fast-rolling, high-grip, Specialized Pathfinder 38c tires, featuring proprietary Gripton rubber compound, are as good on gravel as they are on pavement.

TURBO VADO SL 4.0 STEP-THROUGH

	S	M	L	XL
Stack (mm)	542	574	607	643
Reach (mm)	397	419	433	442
Head-Tube Length (mm)	130	161.5	194.5	230
Head-Tube Angle (°)	70	70.5	71	71.5
B-B Height (mm)	291	291	291	291
B-B Drop (mm)	70	70	70	70
Trail (mm)	71	67	64	61
Fork Length (full) (mm)	390	390	390	390
Fork Rake/Offset (mm)	50	50	50	50
Front-Center (mm)	626	655	675	690
Chain-Stay Length (mm)	445	445	445	445
Wheelbase (mm)	1062	1091	1110	1126
Top-Tube Length (horizontal) (mm)	558	587	610	630
Bike Stand-Over Height (mm)	616	631	655	688
Seat-Tube Length (mm)	405	431.5	469.5	510
Seat-Tube Angle (°)	73.5	73.5	73.5	73.5
Crank Length (mm)	170	172.5	172.5	175
Handlebar Width (mm)	680	680	680	680
Stem Length (mm)	60	75	75	90
Saddle Width (mm)	155	155	155	155
Seatpost Length (mm)	350	350	350	350

SPECS	Specifications subject to change without notice.
Frame	E5 Aluminum, bottom bracket motor mount, fully integrated downtube battery, internal cable routing, fender and front rack mounts, Smooth Welds
Fork	Rigid full aluminum disc, Boost™ 12x110mm, front-rack-compatible
Stem	Specialized Stealth Stem, alloy, 14 deg, 31.8mm, integrated TCD mount
Handlebars	Specialized, alloy, 9-degree backsweep, 15mm rise, 31.8mm
Grips	Body Geometry Women's Contour
Front Brake	Tektro HD-R290, hydraulic disc, 160mm
Rear Brake	Tektro HD-R290, hydraulic disc, 160mm
Rear Derailleur	SRAM NX, 11-speed
Shift Levers	Sram NX, 11-speed, multi-shift
Cassette	SUNRACE, CSMS7, 11-42t, 11-speed
Chain	KMC X11eT, 11spd
Crankset	Praxis, Forged alloy M30, custom offset
Chainrings	Praxis, 44T, 110BCD
Pedals	Specialized Commuter w/ grip tape & reflectors
Rims	700C disc, 22mm rim depth, 21mm internal width
Front Hub	Specialized alloy front hub disc, sealed cartridge bearings, Center Lock™, 12x110mm, 24h
Rear Hub	Specialized alloy rear hub disc, sealed cartridge bearings, Center Lock™, 12x148mm, 28h
Spokes	DT Swiss Industry
Front Tire	Specialized Pathfinder Sport, 700x38c
Rear Tire	Specialized Pathfinder Sport, 700x38c
Inner Tubes	Standard 40mm PV 700x32-50
Saddle	Bridge Sport, Steel rails, 155mm
SeatPost	Specialized, alloy, 2-bolt, 12.5mm offset, 27.2mm
Seat Binder	Specialized Alloy, 30.8mm
Motor	Specialized SL 1.1, custom lightweight motor
UI/Remote	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®, w/Handlebar remote
Battery	Specialized SL1-320, fully integrated, 320Wh
Charger	Custom charger, 48V System w/ SL system charger plug
Wiring Harness	Custom Specialized wiring harness w/ chargeport
Headlight	Lezyne Ebike Hecto STVZO E65, 210Lumens, 12V
Taillight	Specialized integrated saddle mount, LED Technology, 12V
Bell	Simple bell

PART NO.	DESCRIPTION	COLOR	SIZE
93921-5102	VADO SL 4.0 ST	Cast Umber / Silver Reflective	S
93921-5103			M
93921-5104			L
93921-5105			XL
93921-5002	VADO SL 4.0 ST	Limestone / Black Reflective	S
93921-5003			M
93921-5004			L
93921-5005			XL
93923-5002	VADO SL 4.0 ST	Cast Umber / Silver Reflective	S
93923-5003			M
93923-5004			L
93923-5005			XL
93923-5102	VADO SL 4.0 ST	Limestone / Black Reflective	S
93923-5103			M
93923-5104			L
93923-5105			XL

COMO

TURBO COMO 5.0 IGH



Cast Black / Silver Reflective



Limestone / Black Reflective



Red Tint / Silver Reflective



Sand / Black Reflective

Como is a laid-back, comfortable e-Bike with the power of a confident ride. Como lets you go with the flow by giving you a full-power, confidence-inspiring, utterly delightful experience on a bike that feels effortless to ride.

- Turbo Full Power 2.2 motor and 710Wh battery offer an unparalleled riding experience, providing a smooth, seamless, and shockingly quiet amplification of your efforts, up to 25 km/h. The integrated controller responds to your pedal inputs resulting in intuitive amplification of your efforts with an incredibly natural feel.
- MasterMind and Mission Control - The MasterMind display reveals all relevant info about your ride, allows real-time tuning of support levels, and enables over-the-air updates so that your bike gets better over time. MasterMind seamlessly integrates with the Mission Control app for range optimization tools, advanced tuning, on-ride diagnostics, and more.
- The Enviolo AUTOMATIQ Internal Gear Hub (IGH) stepless shifting technology automatically shifts gears based on a rider's pedal pace, taking changes in the surroundings into account. By selecting a preferred cadence or pedal pace, it allows riders to "set it and forget it", adding an extra layer of safety and comfort for riders.
- Proven Smooth Efficiency - We designed a custom testing mechanism to analyze bumps at even the smallest frequency to increase comfort and vision. That precision, paired with a suspended seatpost, higher volume tires, and an 80 mm suspension fork, will flatten roads before your eyes.
- Turbo System Lock - Use the Mission Control app to disable your bike's motor and activate the motion sensor alarm. Once locked, the motor cannot be enabled again except by the owner.
- Garmin Radar - An integrated Garmin Radar sensor lets you know when traffic is coming up behind you. Garmin's Radar technology can detect cars up to 140 meters away. MasterMind will give riders a visual, audible, and haptic alert of an approaching vehicle's relative distance and rate of speed.
- Fully Integrated Removable and Lockable Downtube Battery - Easy to charge, easy to secure.
- Equipped with DRYTECH Fenders, LED front and rear lights, and 27kg capacity rear HD Rack. The rear rack is compatible with child bike seats, and the bike is also rated to pull a thru-axle trailer.

	S	M	L
Stack (mm)	650	671	682
Reach (mm)	441	465	486
Headtube Length (mm)	150	170	180
Headtube Angle (°)	67	67.5	68
BB Height (mm)	275	275	275
BB Drop (mm)	80	80	80
Trail (mm)	103	99	96
Fork Length (full) (mm)	487	487	487
Fork Rake/Offset (mm)	44	44	44
Front Center (mm)	735	762	781
Chainstay Length (mm)	470.4	470.4	470.4
Wheelbase (mm)	1194	1221	1241
Toptube Length (horizontal) (mm)	630	666	695
Bike Standover Height (mm)	355	355	355
Seat Tube Length (mm)	450	450	460
Seat Tube Angle (Virtual) (°)	73.8	73.3	73
Crank Length (mm)	170	170	170
Handlebar Width (mm)	680	680	680
Saddle Width (mm)	200	200	200
Seatpost Length (mm)	350	400	400

SPECS	Specifications subject to change without notice.
Frame	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount, sliding dropout
Fork	Rockshox Recon Silver RL, 80mm travel, Motion-Control, fender-mounts
Handlebars	Specialized handlebar/stem combo, integrated cable routing
Grips	Ergon GP-10s
Front Brake	SRAM G2 RS, 4-piston caliper, hydraulic disc, 180mm
Rear Brake	SRAM G2 RS, 4-piston caliper, hydraulic disc, 180mm
Rear Derailleur	Enviolo Automatiq Pro
Cassette	Gates Carbon Drive CDX 24t sprocket, silver
Chain	Gates Carbon Drive CDX 122t belt, black
Crankset	Custom alloy forged crankarms
Chainrings	Gates Carbon Drive CDX 50T chainring, black
Pedals	Specialized Commuter w/ grip tape & reflectors
Rims	650b disc, double-wall alloy, pinned, 24/32h
Front Hub	Alloy, sealed cartridge bearings, 15x110mm thru-axle, 32h
Rear Hub	Enviolo HD, 32h, 135mm, 6-bolt
Spokes	DT Swiss Industry
Front Tire	Pathfinder Sport Reflect, 650Bx2.3
Rear Tire	Pathfinder Sport Reflect, 650Bx2.3
Inner Tubes	Schrader, 40mm valve
Saddle	Body Geometry Comfort Gel, 200mm w/ SWAT™ Mount
SeatPost	Spring suspension, alloy, 30.9mm, 2-bolt
Seat Binder	Specialized bolt-type, alloy, 42.9mm
Motor	TBD
UI/Remote	TBD
Battery	SPECIALIZED U2-710, INTEGRATED BATTERY, 710WH
Charger	Custom charger, 42V4A w/ Rosenberger plug, 230V
Wiring Harness	Custom wire harness
Headlight	LEZYNE, EBIKE POWER STVZO E115, 115LUX 310LUMEN
Taillight	Spanninga Commuter Glow
Chaincase	Integrated Chaincover
Kickstand	Specialized kickstand, 40mm mount
Rack	Specialized rack, MIK HD interface, built-in pannier mounts, 27kg max load
Fenders	Specialized DRYTECH fenders, 65mm width, aluminum fenderstay
Bell	Specialized brass bell

PART NO.	DESCRIPTION	COLOR	SIZE
90422-2402	COMO 5.0 IGH NB	Cast Black / Silver Reflective	S
90422-2403			M
90422-2404			L
90422-2502	COMO 5.0 IGH NB	Limestone / Black Reflective	S
90422-2503			M
90422-2504			L
90422-2602	COMO 5.0 IGH NB	Red Tint / Silver Reflective	S
90422-2603			M
90422-2604			L
90422-2702	COMO 5.0 IGH NB	Sand / Black Reflective	S
90422-2703			M
90422-2704			L

TURBO COMO 5.0



Cast Black / Silver Reflective



Limestone / Black Reflective



Red Tint / Silver Reflective



Sand / Black Reflective

Como is a laid-back, comfortable e-Bike with the power of a confident ride. Como lets you go with the flow by giving you a full-power, confidence-inspiring, utterly delightful experience on a bike that feels effortless to ride.

- Turbo Full Power 2.2 motor and 710Wh battery offer an unparalleled riding experience, providing a smooth, seamless, and shockingly quiet amplification of your efforts, up to 25 km/h. The integrated controller responds to your pedal inputs resulting in intuitive amplification of your efforts with an incredibly natural feel.
- MasterMind and Mission Control - The MasterMind display reveals all relevant info about your ride, allows real-time tuning of support levels, and enables over-the-air updates so that your bike gets better over time. MasterMind seamlessly integrates with the Mission Control app for range optimization tools, advanced tuning, on-ride diagnostics, and more.
- Proven Smooth Efficiency - We designed a custom testing mechanism to analyze bumps at even the smallest frequency to increase comfort and vision. That precision, paired with a suspended seatpost, higher volume tires, and an 80 mm suspension fork, will flatten roads before your eyes.
- Turbo System Lock - Use the Mission Control app to disable your bike's motor and activate the motion sensor alarm. Once locked, the motor cannot be enabled again except by the owner.
- Garmin Radar - An integrated Garmin Radar sensor lets you know when traffic is coming up behind you. Garmin's Radar technology can detect cars up to 140 meters away. MasterMind will give riders a visual, audible, and haptic alert of an approaching vehicle's relative distance and rate of speed.
- Fully Integrated Removable and Lockable Downtube Battery - Easy to charge, easy to secure.
- Equipped with DRYTECH Fenders, LED front and rear lights, and 27kg capacity rear HD Rack. The rear rack is compatible with child bike seats, and the bike is also rated to pull a thru-axle trailer.

SPECS Specifications subject to change without notice.

Frame	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount
Fork	Rockshox Recon Silver RL, 80mm travel, Motion-Control, fender-mounts
Handlebars	Specialized handlebar/stem combo, integrated cable routing
Grips	Ergon GP-10s
Front Brake	SRAM G2 RS, 4-piston caliper, hydraulic disc, 180mm
Rear Brake	SRAM G2 RS, 4-piston caliper, hydraulic disc, 180mm
Rear Derailleur	SRAM GX, long cage, 11-speed
Shift Levers	SRAM S700, single-click lever
Cassette	SRAM PG-1130, 11-speed, 11-42t
Chain	KMC e11T, 11-speed w/ Missing Link™
Crankset	Custom alloy forged crankarms
Chainrings	40T
Pedals	Specialized Commuter w/ grip tape & reflectors
Rims	650b disc, double-wall alloy, pinned, 24/32h
Front Hub	Alloy, sealed cartridge bearings, 15x110mm thru-axle, 32h
Rear Hub	Alloy, sealed cartridge bearings, 12x148mm thru-axle, 32h
Spokes	DT Swiss Industry
Front Tire	Pathfinder Sport Reflect, 650Bx2.3
Rear Tire	Pathfinder Sport Reflect, 650Bx2.3
Inner Tubes	Schrader, 40mm valve
Saddle	Body Geometry Comfort Gel, 200mm w/ SWAT™ Mount
SeatPost	Spring suspension, alloy, 30.9mm, 2-bolt
Seat Binder	Specialized bolt-type, alloy, 42.9mm
Motor	TBD
UI/Remote	TBD
Battery	SPECIALIZED U2-710, INTEGRATED BATTERY, 710WH
Charger	Custom charger, 42V4A w/ Rosenberger plug, 230V
Wiring Harness	Custom wire harness
Headlight	LEZYNE, EBIKE POWER STVZO E115, 115LUX 310LUMEN
Taillight	Spanninga Commuter Glow
Chaincase	Integrated Chaincover
Kickstand	Specialized kickstand, 40mm mount
Rack	Specialized rack, MIK HD interface, built-in pannier mounts, 27kg max load
Fenders	Specialized DRYTECH fenders, 65mm width, aluminum fenderstay
Bell	Specialized brass bell

	S	M	L
Stack (mm)	650	671	682
Reach (mm)	441	465	486
Headtube Length (mm)	150	170	180
Headtube Angle (°)	67	67.5	68
BB Height (mm)	275	275	275
BB Drop (mm)	80	80	80
Trail (mm)	103	99	96
Fork Length (full) (mm)	487	487	487
Fork Rake/Offset (mm)	44	44	44
Front Center (mm)	735	762	781
Chainstay Length (mm)	470.4	470.4	470.4
Wheelbase (mm)	1194	1221	1241
Toptube Length (horizontal) (mm)	630	666	695
Bike Standover Height (mm)	355	355	355
Seat Tube Length (mm)	450	450	460
Seat Tube Angle (Virtual) (°)	73.8	73.3	73
Crank Length (mm)	170	170	170
Handlebar Width (mm)	680	680	680
Saddle Width (mm)	200	200	200
Seatpost Length (mm)	350	400	400

PART NO.	DESCRIPTION	COLOR	SIZE
90422-3402	COMO 5.0 NB	Cast Black / Silver Reflective	S
90422-3403			M
90422-3404			L
90422-3502	COMO 5.0 NB	Limestone / Black Reflective	S
90422-3503			M
90422-3504			L
90422-3602	COMO 5.0 NB	Red Tint / Silver Reflective	S
90422-3603			M
90422-3604			L
90422-3702	COMO 5.0 NB	Sand / Black Reflective	S
90422-3703			M
90422-3704			L

TURBO COMO 4.0 IGH



Cast Black / Silver Reflective



Red Tint / Silver Reflective



Sand / Black Reflective



Limestone / Black Reflective

Como is a laid-back, comfortable e-Bike with the power of a confident ride. Como lets you go with the flow by giving you a full-power, confidence-inspiring, utterly delightful experience on a bike that feels effortless to ride.

- Turbo Full Power 2.0 motor and 710Wh battery offer an unparalleled riding experience, providing a smooth, seamless, and shockingly quiet amplification of your efforts, up to 25 km/h. The integrated controller responds to your pedal inputs resulting in intuitive amplification of your efforts with an incredibly natural feel.
- The stepless shifting enviolo TR Internal Gear Hub (IGH) features a specifically designed internal gear hub and matching controller. The manual stepless technology is as simple as adjusting the volume on a radio. This allows riders to focus on the important aspects of a bike ride such as traffic or scenery.
- MasterMind and Mission Control - The MasterMind display reveals all relevant info about your ride, allows real-time tuning of support levels, and enables over-the-air updates so that your bike gets better over time. MasterMind seamlessly integrates with the Mission Control app for range optimization tools, advanced tuning, on-ride diagnostics, and more.
- Proven Smooth Efficiency - We designed a custom testing mechanism to analyze bumps at even the smallest frequency to increase comfort and vision. That precision, paired with a suspended seatpost, higher volume tires, and an 80 mm suspension fork, will flatten roads before your eyes.
- Turbo System Lock - Use the Mission Control app to disable your bike's motor and activate the motion sensor alarm. Once locked, the motor cannot be enabled again except by the owner.
- Fully Integrated Removable and Lockable Downtube Battery - Easy to charge, easy to secure.
- Equipped with DRYTECH Fenders, LED front and rear lights, and 27kg capacity rear HD Rack. The rear rack is compatible with child bike seats, and the bike is also rated to pull a thru-axle trailer.

	S	M	L
Stack (mm)	650	671	682
Reach (mm)	441	465	486
Headtube Length (mm)	150	170	180
Headtube Angle (°)	67	67.5	68
BB Height (mm)	275	275	275
BB Drop (mm)	80	80	80
Trail (mm)	103	99	96
Fork Length (full) (mm)	487	487	487
Fork Rake/Offset (mm)	44	44	44
Front Center (mm)	735	762	781
Chainstay Length (mm)	470.4	470.4	470.4
Wheelbase (mm)	1194	1221	1241
Toptube Length (horizontal) (mm)	630	666	695
Bike Standover Height (mm)	355	355	355
Seat Tube Length (mm)	450	450	460
Seat Tube Angle (Virtual) (°)	73.8	73.3	73
Crank Length (mm)	170	170	170
Handlebar Width (mm)	680	680	680
Saddle Width (mm)	200	200	200
Seatpost Length (mm)	350	400	400

SPECS	Specifications subject to change without notice.
Frame	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount, sliding dropout
Fork	SR Suntour MobieA32, 80mm travel, lockout, fender-mounts, integrated light mount
Handlebars	Specialized handlebar/stem combo, integrated cable routing
Grips	Body Geometry Contour
Front Brake	SRAM Level, 2-piston caliper, hydraulic disc, 180mm
Rear Brake	SRAM Level, hydraulic disc, 160mm
Rear Derailleur	Enviolo CVP Multi-Turn
Shift Levers	Enviolo Twist Display Pure
Cassette	Gates Carbon Drive CDX 24t sprocket, silver
Chain	Gates Carbon Drive CDX 122t belt, black
Crankset	Custom alloy forged crankarms
Chainrings	Gates Carbon Drive CDX 50T chainring, black
Pedals	Specialized Commuter w/ grip tape & reflectors
Rims	650b disc, double-wall alloy, pinned, 24/32h
Front Hub	Alloy, sealed cartridge bearings, 15x100mm thru-axle, 32h
Rear Hub	Enviolo TR, 32h, 135mm, 6-bolt
Spokes	DT Swiss Industry
Front Tire	Pathfinder Sport Reflect, 650Bx2.3
Rear Tire	Pathfinder Sport Reflect, 650Bx2.3
Inner Tubes	Schrader, 40mm valve
Saddle	Body Geometry Comfort Gel, 200mm w/ SWAT™ Mount
SeatPost	Spring suspension, alloy, 30.9mm, 2-bolt
Seat Binder	Specialized bolt-type, alloy, 42.9mm
Motor	TBD
UI/Remote	TBD
Battery	SPECIALIZED U2-710, INTEGRATED BATTERY, 710WH
Charger	Custom charger, 42V4A w/ Rosenberger plug, 230V
Wiring Harness	Custom wire harness
Headlight	LEZYNE, EBIKE HECTO STVZO E65, 65LUX 210LUMEN
Taillight	Spanninga Commuter Glow
Chaincase	Integrated Chaincover
Kickstand	Specialized kickstand, 40mm mount
Rack	Specialized rack, MIK HD interface, built-in pannier mounts, 27kg max load
Fenders	Specialized DRYTECH fenders, 65mm width, aluminum fenderstay
Bell	Simple bell

PART NO.	DESCRIPTION	COLOR	SIZE
90422-4402	COMO 4.0 IGH NB	Cast Black / Silver Reflective	S
90422-4403			M
90422-4404			L
90422-4502	COMO 4.0 IGH NB	Limestone / Black Reflective	S
90422-4503			M
90422-4504			L
90422-4602	COMO 4.0 IGH NB	Red Tint / Silver Reflective	S
90422-4603			M
90422-4604			L
90422-4702	COMO 4.0 IGH NB	Sand / Black Reflective	S
90422-4703			M
90422-4704			L

TURBO COMO 4.0



Cast Black / Silver Reflective



Limestone / Black Reflective



Red Tint / Silver Reflective



Sand / Black Reflective

Como is a laid-back, comfortable e-Bike with the power of a confident ride. Como lets you go with the flow by giving you a full-power, confidence-inspiring, utterly delightful experience on a bike that feels effortless to ride.

- Turbo Full Power 2.0 motor and 710Wh battery offer an unparalleled riding experience, providing a smooth, seamless, and shockingly quiet amplification of your efforts, up to 25 km/h. The integrated controller responds to your pedal inputs resulting in intuitive amplification of your efforts with an incredibly natural feel.
- MasterMind and Mission Control - The MasterMind display reveals all relevant info about your ride, allows real-time tuning of support levels, and enables over-the-air updates so that your bike gets better over time. MasterMind seamlessly integrates with the Mission Control app for range optimization tools, advanced tuning, on-ride diagnostics, and more.
- Proven Smooth Efficiency - We designed a custom testing mechanism to analyze bumps at even the smallest frequency to increase comfort and vision. That precision, paired with a suspended seatpost, higher volume tires, and an 80 mm suspension fork, will flatten roads before your eyes.
- Turbo System Lock - Use the Mission Control app to disable your bike's motor and activate the motion sensor alarm. Once locked, the motor cannot be enabled again except by the owner.
- Fully Integrated Removable and Lockable Downtube Battery - Easy to charge, easy to secure.
- Equipped with DRYTECH Fenders, LED front and rear lights, and 27kg capacity rear HD Rack. The rear rack is compatible with child bike seats, and the bike is also rated to pull a thru-axle trailer.

	S	M	L
Stack (mm)	650	671	682
Reach (mm)	441	465	486
Headtube Length (mm)	150	170	180
Headtube Angle (°)	67	67.5	68
BB Height (mm)	275	275	275
BB Drop (mm)	80	80	80
Trail (mm)	103	99	96
Fork Length (full) (mm)	487	487	487
Fork Rake/Offset (mm)	44	44	44
Front Center (mm)	735	762	781
Chainstay Length (mm)	470.4	470.4	470.4
Wheelbase (mm)	1194	1221	1241
Toptube Length (horizontal) (mm)	630	666	695
Bike Standover Height (mm)	355	355	355
Seat Tube Length (mm)	450	450	460
Seat Tube Angle (Virtual) (°)	73.8	73.3	73
Crank Length (mm)	170	170	170
Handlebar Width (mm)	680	680	680
Saddle Width (mm)	200	200	200
Seatpost Length (mm)	350	400	400

SPECS	Specifications subject to change without notice.
Frame	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount
Fork	SR Suntour MobieA32, 80mm travel, lockout, fender-mounts, integrated light mount
Handlebars	Specialized handlebar/stem combo, integrated cable routing
Grips	Body Geometry Contour
Front Brake	SRAM Level, 2-piston caliper, hydraulic disc, 180mm
Rear Brake	SRAM Level, hydraulic disc, 160mm
Rear Derailleur	SRAM NX, 11-speed
Shift Levers	SRAM NX, 11-speed
Cassette	SRAM PG-1130, 11-speed, 11-42t
Chain	KMC e11S, 11-speed w/ Missing Link™
Crankset	Custom alloy forged crankarms
Chainrings	40T
Pedals	Specialized Commuter w/ grip tape & reflectors
Rims	650b disc, double-wall alloy, pinned, 24/32h
Front Hub	Alloy, sealed cartridge bearings, 15x100mm thru-axle, 32h
Rear Hub	Alloy, sealed cartridge bearings, 12x148mm thru-axle, 32h
Spokes	DT Swiss Industry
Front Tire	Pathfinder Sport Reflect, 650Bx2.3
Rear Tire	Pathfinder Sport Reflect, 650Bx2.3
Inner Tubes	Schrader, 40mm valve
Saddle	Body Geometry Comfort Gel, 200mm w/ SWAT™ Mount
SeatPost	Spring suspension, alloy, 30.9mm, 2-bolt
Seat Binder	Specialized bolt-type, alloy, 42.9mm
Motor	TBD
UI/Remote	TBD
Battery	SPECIALIZED U2-710, INTEGRATED BATTERY, 710WH
Charger	Custom charger, 42V4A w/ Rosenberger plug, 230V
Wiring Harness	Custom wire harness
Headlight	LEZYNE, EBIKE HECTO STVZO E65, 65LUX 210LUMEN
Taillight	Spanninga Commuter Glow
Chaincase	Integrated Chaincover
Kickstand	Specialized kickstand, 40mm mount
Rack	Specialized rack, MIK HD interface, built-in pannier mounts, 27kg max load
Fenders	Specialized DRYTECH fenders, 65mm width, aluminum fenderstay
Bell	Simple bell

PART NO.	DESCRIPTION	COLOR	SIZE
90422-5402	COMO 4.0 NB	Cast Black / Silver Reflective	S
90422-5403			M
90422-5404			L
90422-5502	COMO 4.0 NB	Limestone / Black Reflective	S
90422-5503			M
90422-5504			L
90422-5602	COMO 4.0 NB	Red Tint / Silver Reflective	S
90422-5603			M
90422-5604			L
90422-5702	COMO 4.0 NB	Sand / Black Reflective	S
90422-5703			M
90422-5704			L

TURBO COMO 3.0 IGH



Cast Black / Silver Reflective



Limestone / Black Reflective



Red Tint / Silver Reflective



Sand / Black Reflective

Como is a laid-back, comfortable e-Bike with the power of a confident ride. Como lets you go with the flow by giving you a full-power, confidence-inspiring, utterly delightful experience on a bike that feels effortless to ride.

- Turbo Full Power 2.0E motor and 530Wh battery offer an unparalleled riding experience, providing a smooth, seamless, and shockingly quiet amplification of your efforts, up to 25 km/h. The integrated controller responds to your pedal inputs resulting in intuitive amplification of your efforts with an incredibly natural feel.
- MasterMind and Mission Control - The MasterMind display reveals all relevant info about your ride, allows real-time tuning of support levels, and enables over-the-air updates so that your bike gets better over time. MasterMind seamlessly integrates with the Mission Control app for range optimization tools, advanced tuning, on-ride diagnostics, and more.
- The stepless shifting Enviolo City Internal Gear Hub (IGH) features a specifically designed internal gear hub and matching controller. The manual stepless technology is as simple as adjusting the volume on a radio. This allows riders to focus on the important aspects of a bike ride such as traffic or scenery.
- Proven Smooth Efficiency - We designed a custom testing mechanism to analyze bumps at even the smallest frequency to increase comfort and vision. That precision, paired with a suspended seatpost, higher volume tires, and an 80 mm suspension fork, will flatten roads before your eyes.
- Turbo System Lock - Use the Mission Control app to disable your bike's motor and activate the motion sensor alarm. Once locked, the motor cannot be enabled again except by the owner.
- Fully Integrated Removable and Lockable Downtube Battery - Easy to charge, easy to secure.
- Equipped with DRYTECH Fenders, LED front and rear lights, and 27kg capacity rear HD Rack. The rear rack is compatible with child bike seats, and the bike is also rated to pull a thru-axle trailer.

	S	M	L
Stack (mm)	650	671	682
Reach (mm)	441	465	486
Headtube Length (mm)	150	170	180
Headtube Angle (°)	67	67.5	68
BB Height (mm)	275	275	275
BB Drop (mm)	80	80	80
Trail (mm)	103	99	96
Fork Length (full) (mm)	487	487	487
Fork Rake/Offset (mm)	44	44	44
Front Center (mm)	735	762	781
Chainstay Length (mm)	470.4	470.4	470.4
Wheelbase (mm)	1194	1221	1241
Toptube Length (horizontal) (mm)	630	666	695
Bike Standover Height (mm)	355	355	355
Seat Tube Length (mm)	450	450	460
Seat Tube Angle (Virtual) (°)	73.8	73.3	73
Crank Length (mm)	170	170	170
Handlebar Width (mm)	680	680	680
Saddle Width (mm)	200	200	200
Seatpost Length (mm)	375	435	500

SPECS	Specifications subject to change without notice.
Frame	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount, sliding dropout
Fork	SR Suntour MobieA32, 80mm travel, lockout, fender-mounts, integrated light mount
Handlebars	Specialized handlebar/stem combo, integrated cable routing
Grips	Body Geometry Contour
Front Brake	Shimano BR-MT200, hydraulic disc, 180mm
Rear Brake	Shimano BR-MT200, hydraulic disc, 160mm
Rear Derailleur	Enviolo CVP Multi-Turn
Shift Levers	Enviolo Twist Display Pure
Cassette	Gates Carbon Drive CDC 24t sprocket, silver
Chain	Gates Carbon Drive CDX 122t belt, black
Crankset	Custom alloy forged crankarms
Chainrings	Gates Carbon Drive CDC 50T chainring, black
Pedals	Specialized Commuter w/ grip tape & reflectors
Rims	650b disc, double-wall alloy, pinned, 24/32h
Front Hub	Shimano MT400, Centerlock 32h, 15x100mm
Rear Hub	Enviolo CT, 32h, 135mm, 6-bolt
Spokes	DT Swiss Industry
Front Tire	Pathfinder Sport Reflect, 650Bx2.3
Rear Tire	Pathfinder Sport Reflect, 650Bx2.3
Inner Tubes	Schrader, 40mm valve
Saddle	Body Geometry Comfort Gel, 200mm w/ SWAT™ Mount
SeatPost	Specialized 2-bolt head, forged alloy, 5mm offset, micro-adjust, 34.9mm
Seat Binder	Specialized bolt-type, alloy, 42.9mm
Motor	TBD
UI/Remote	TBD
Battery	SPECIALIZED U2-530, INTEGRATED BATTERY, 530WH
Charger	Custom charger, 42V4A w/ Rosenberger plug, 230V
Wiring Harness	Custom wire harness
SWAT	RETAINING WIRE RING, HW-RING-OE, ENVILOLO, FOR IGH
Headlight	LEZYNE, EBIKE MINI STVZO E65, 65LUX 210LUMEN
Taillight	Spanninga Commuter Glow
Chaincase	Integrated Chaincover
Kickstand	Specialized kickstand, 40mm mount
Rack	Specialized rack, MIK HD interface, built-in pannier mounts, 27kg max load
Fenders	Specialized DRYTECH fenders, 65mm width, aluminum fenderstay
Bell	Simple bell

PART NO.	DESCRIPTION	COLOR	SIZE
90422-6402	COMO 3.0 IGH NB	Cast Black / Silver Reflective	S
90422-6403			M
90422-6404			L
90422-6502	COMO 3.0 IGH NB	Limestone / Black Reflective	S
90422-6503			M
90422-6504			L
90422-6602	COMO 3.0 IGH NB	Red Tint / Silver Reflective	S
90422-6603			M
90422-6604			L
90422-6702	COMO 3.0 IGH NB	Sand / Black Reflective	S
90422-6703			M
90422-6704			L

TURBO COMO 3.0



Cast Black / Silver Reflective



Limestone / Black Reflective



Red Tint / Silver Reflective



Sand / Black Reflective

Como is a laid-back, comfortable e-Bike with the power of a confident ride. Como lets you go with the flow by giving you a full-power, confidence-inspiring, utterly delightful experience on a bike that feels effortless to ride.

- Turbo Full Power 2.0E motor and 530Wh battery offer an unparalleled riding experience, providing a smooth, seamless, and shockingly quiet amplification of your efforts, up to 25 km/h. The integrated controller responds to your pedal inputs resulting in intuitive amplification of your efforts with an incredibly natural feel.
- MasterMind and Mission Control - The MasterMind display reveals all relevant info about your ride, allows real-time tuning of support levels, and enables over-the-air updates so that your bike gets better over time. MasterMind seamlessly integrates with the Mission Control app for range optimization tools, advanced tuning, on-ride diagnostics, and more.
- Proven Smooth Efficiency - We designed a custom testing mechanism to analyze bumps at even the smallest frequency to increase comfort and vision. That precision, paired with a suspended seatpost, higher volume tires, and an 80 mm suspension fork, will flatten roads before your eyes.
- Turbo System Lock - Use the Mission Control app to disable your bike's motor and activate the motion sensor alarm. Once locked, the motor cannot be enabled again except by the owner.
- Fully Integrated Removable and Lockable Downtube Battery - Easy to charge, easy to secure.
- Equipped with DRYTECH Fenders, LED front and rear lights, and 27kg capacity rear HD Rack. The rear rack is compatible with child bike seats, and the bike is also rated to pull a thru-axle trailer.

	S	M	L
Stack (mm)	650	671	682
Reach (mm)	441	465	486
Headtube Length (mm)	150	170	180
Headtube Angle (°)	67	67.5	68
BB Height (mm)	275	275	275
BB Drop (mm)	80	80	80
Trail (mm)	103	99	96
Fork Length (full) (mm)	487	487	487
Fork Rake/Offset (mm)	44	44	44
Front Center (mm)	735	762	781
Chainstay Length (mm)	470.4	470.4	470.4
Wheelbase (mm)	1194	1221	1241
Toptube Length (horizontal) (mm)	630	666	695
Bike Standover Height (mm)	355	355	355
Seat Tube Length (mm)	450	450	460
Seat Tube Angle (Virtual) (°)	73.8	73.3	73
Crank Length (mm)	170	170	170
Handlebar Width (mm)	680	680	680
Saddle Width (mm)	200	200	200
Seatpost Length (mm)	375	435	500

SPECS	Specifications subject to change without notice.
Frame	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount
Fork	SR Suntour MobieA32, 80mm travel, lockout, fender-mounts, integrated light mount
Handlebars	Specialized handlebar/stem combo, integrated cable routing
Grips	Body Geometry Contour
Front Brake	Shimano BR-MT200, hydraulic disc, 180mm
Rear Brake	Shimano BR-MT200, hydraulic disc, 160mm
Rear Derailleur	Shimano Acera, RapidFire Plus, 9-speed
Shift Levers	Shimano Alivio, 9-speed w/ Optical Gear Display
Cassette	Shimano CS-HG400, 9-speed, 11-36t
Chain	KMC e9T, 9-speed w/ Missing Link™
Crankset	Custom alloy forged crankarms
Chainrings	40T
Pedals	Specialized Commuter w/ grip tape & reflectors
Rims	650b disc, double-wall alloy, pinned, 24/32h
Front Hub	Shimano MT400, Centerlock 32h, 15x100mm
Rear Hub	Shimano MT400-B, Centerlock 32h, 12x148 Boost
Spokes	DT Swiss Industry
Front Tire	Pathfinder Sport Reflect, 650Bx2.3
Rear Tire	Pathfinder Sport Reflect, 650Bx2.3
Inner Tubes	Schrader, 40mm valve
Saddle	Body Geometry Comfort Gel, 200mm w/ SWAT™ Mount
SeatPost	Specialized 2-bolt head, forged alloy, 5mm offset, micro-adjust, 34.9mm
Seat Binder	Specialized bolt-type, alloy, 42.9mm
Motor	TBD
UI/Remote	TBD
Battery	SPECIALIZED U2-530, INTEGRATED BATTERY, 530WH
Charger	Custom charger, 42V4A w/ Rosenberger plug, 230V
Wiring Harness	Custom wire harness
Headlight	LEZYNE, EBIKE MINI STVZO E65, 65LUX 210LUMEN
Taillight	Spanninga Commuter Glow
Chaincase	Integrated Chaincover
Kickstand	Specialized kickstand, 40mm mount
Rack	Specialized rack, MIK HD interface, built-in pannier mounts, 27kg max load
Fenders	Specialized DRYTECH fenders, 65mm width, aluminum fenderstay
Bell	Simple bell

PART NO.	DESCRIPTION	COLOR	SIZE
90422-7402	COMO 3.0 NB	Cast Black / Silver Reflective	S
90422-7403			M
90422-7404			L
90422-7502	COMO 3.0 NB	Limestone / Black Reflective	S
90422-7503			M
90422-7504			L
90422-7602	COMO 3.0 NB	Red Tint / Silver Reflective	S
90422-7603			M
90422-7604			L
90422-7702	COMO 3.0 NB	Sand / Black Reflective	S
90422-7703			M
90422-7704			L

COMO SL

TURBO COMO SL 5.0



Brassy Yellow / Transparent



Brushed Silver / Transparent



Smoke / Transparent

What happened when we brought our perfectly balanced Super Light system to our popular Turbo Como E-bike? The best combination of power, range, and usability in a comfort e-bike. The Turbo Como Super Light (SL) is designed for running around town and beyond. Able to carry twice its weight in cargo, it's a surprising errand bike that's as exciting to ride as it is easy to own.

- 8-speed Alfine Internal Gear Hub and Gates Belt Drive for shifting when stopped, extended bike performance, and minimal at-home bike maintenance.
- Fully integrated Specialized 320Wh downtube battery w/optional Range Extender compatibility for up to 93 miles of range.
- Specialized SL 1.1 custom lightweight motor, peak 240W / 35Nm, 2x you rider amplification (180% assistance), assist up to 28mph.
- Bright, integrated front and rear lighting to see and be seen.
- Frame-mounted front porteur rack with a basket and top net.
- Turbo Super Light mounted pannier-compatible rear rack and DRYTECH fenders.
- Turbo Connect Display included and centrally located on the handlebars.
- Clean internal cable routing and reflective graphics.
- TRP Flow Set hydraulic disc brakes for maximum stopping power.
- Durable 650b wheels paired with Nimbus 2.3 tires smooth out rough roads, while providing BlackBelt flat protection and reflective accents to increase visibility

SPECS	Specifications subject to change without notice.
Frame	E5 Aluminum, bottom bracket motor mount, fully integrated downtube battery, internal cable routing, fender and front rack mounts, Smooth Welds
Fork	Turbo Como SL one-piece-design aluminum fork, 12x110mm thru-axle
Handlebars	Specialized handlebar/stem combo, integrated cable routing
Grips	Body Geometry XC Contour
Front Brake	TRP Flow Set Control, hydraulic disc w/ 160mm CL-rotor
Rear Brake	TRP Flow Set Control, hydraulic disc w/ 160mm CL-rotor
Shift Levers	Microshift SL-SCN08, 8-speed Alfine compatible
Cassette	Gates Carbon Drive CDX 22t sprocket, silver
Chain	Gates Carbon Drive CDX 122t belt, black
Crankset	Custom alloy forged crankarms
Chainrings	Gates Carbon Drive CDX 46T chainring, black
Pedals	Specialized Commuter w/ grip tape & reflectors
Rims	650b disc, double-wall alloy, pinned, 24/32h
Front Hub	Specialized alloy front hub disc, sealed cartridge bearings, 12x110mm, Center Lock™, 24h
Rear Hub	Shimano Alfine, 8-speed internal gear hub, SG-S7001-8, 32H, Black
Spokes	DT Swiss Industry
Front Tire	Nimbus 2 Sport Reflect, 650Bx2.3
Rear Tire	Nimbus 2 Sport Reflect, 650Bx2.3
Inner Tubes	Schrader, 40mm valve
Saddle	Body Geometry Comfort Gel, 200mm w/ SWAT™ Mount
SeatPost	Specialized 2-bolt head, forged alloy, 5mm offset, micro-adjust, 34.9mm
Seat Binder	Specialized bolt-type, alloy, 38.6mm
Motor	Specialized SL 1.1, custom lightweight motor
UI/Remote	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth*
Battery	Specialized SL1-320, fully integrated, 320Wh
Charger	Custom charger, 48V System w/ SL system charger plug
Wiring Harness	Custom Specialized wiring harness w/ chargeport
SWAT	Specialized Como SL front-rack, max. 15kg load, incl. Como SL basket w/cargo-net
Headlight	Supernova Mini2, 235lm, 12V, alloy housing
Taillight	Supernova E3, alloy housing, 3-LED, 250-degree visibility, fender mount, 12V
Chaincase	Integrated Chaincover
Kickstand	Specialized Center-Mount, 255mm
Rack	Specialized Pannier-rack, alloy tubing, max. 20kg load
Fenders	Specialized DRYTECH fenders, 65mm width, stainless steel fenderstays
Bell	Simple bell

TURBO COMO SL 5.0	S	M	L
Stack (mm)	623	641	697
Reach (mm)	401	426	433
Front Center (mm)	680	713	742
Seat Tube Length, Center to Top (mm)	380	390	420
Top Tube Length, Horizontal (mm)	634	666	694
Chainstay Length (mm)	484	484	484
Wheelbase (mm)	1154	1187	1216
Standover Height (mm)	575	575	600
Head Tube Length (mm)	190	210	270
BB Drop (mm)	75	75	75
BB Height (mm)	280	280	280
Head Tube Angle (°)	68	68	68
Seat Tube Angle, Actual (°)	69.5	69.5	69.5

PART NO.	DESCRIPTION	COLOR	SIZE
90121-3102	COMO SL 5.0	Brassy Yellow / Transparent	S
90121-3103			M
90121-3104			L
90121-3302	COMO SL 5.0	Brushed Silver / Transparent	S
90121-3303			M
90121-3304			L
90121-3002	COMO SL 5.0	Smoke / Transparent	S
90121-3003			M
90121-3004			L

TURBO COMO SL 4.0



Cast Umber / Transparent



Dove Grey / Transparent



Raspberry / Transparent

What happened when we brought our perfectly balanced Super Light system to our popular Turbo Como E-bike? The best combination of power, range, and usability in a comfort e-bike. The Turbo Como Super Light (SL) is designed for running around town and beyond. Able to carry twice its weight in cargo, it's a surprising errand bike that's as exciting to ride as it is easy to own.

- 5-speed Nexus Internal Gear Hub and chain drive for shifting when stopped, extended bike performance, and reduced at-home bike maintenance.
- Fully integrated Specialized 320Wh downtube battery w/optional Range Extender compatibility for up to 93 miles of range.
- Specialized SL 1.1 custom lightweight motor, peak 240W / 35Nm, 2x you rider amplification (180% assistance), assist up to 28mph.
- Bright, integrated front and rear lighting to see and be seen.
- Frame-mounted front porteur rack with a basket and top net.
- Turbo Super Light mounted pannier-compatible rear rack and DRYTECH fenders.
- Aftermarket Turbo Connect Display compatibility.
- Clean internal cable routing and reflective graphics.
- TRP Flow Set hydraulic disc brakes for maximum stopping power.
- Durable 650b wheels paired with Nimbus 2.3 tires smooth out rough roads, while providing BlackBelt flat protection and reflective accents to increase visibility

SPECS	Specifications subject to change without notice.
Frame	E5 Aluminum, bottom bracket motor mount, fully integrated downtube battery, internal cable routing, fender and front rack mounts, Smooth Welds
Fork	Turbo Como SL one-piece-design aluminum fork, 12x110mm thru-axle
Handlebars	Specialized handlebar/stem combo, integrated cable routing
Grips	Body Geometry XC Contour
Front Brake	TRP Flow Set Control, hydraulic disc w/ 160mm CL-rotor
Rear Brake	TRP Flow Set Control, hydraulic disc w/ 160mm CL-rotor
Shift Levers	Microshift SL-SCN05, 5-speed Nexus compatible
Cassette	Shimano 30t sprocket
Chain	KMC CN-HG71
Crankset	Custom alloy forged crankarms
Chainrings	40T, custom-alloy
Pedals	Specialized Commuter w/ grip tape & reflectors
Rims	650b disc, double-wall alloy, pinned, 24/32h
Front Hub	Specialized alloy front hub disc, sealed cartridge bearings, 12x110mm, Center Lock™, 24h
Rear Hub	Shimano Nexus, 5-speed internal gear hub, SG-C7000-5D, 32H, BLACK
Spokes	DT Swiss Industry
Front Tire	Nimbus 2 Sport Reflect, 650Bx2.3
Rear Tire	Nimbus 2 Sport Reflect, 650Bx2.3
Inner Tubes	Schrader, 40mm valve
Saddle	Body Geometry Comfort Gel, 200mm w/ SWAT™ Mount
SeatPost	Specialized 2-bolt head, forged alloy, 5mm offset, micro-adjust, 34.9mm
Seat Binder	Specialized bolt-type, alloy, 38.6mm
Motor	Specialized SL 1.1, custom lightweight motor
UI/Remote	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®
Battery	Specialized SL1-320, fully integrated, 320Wh
Charger	Custom charger, 48V System w/ SL system charger plug
Wiring Harness	Custom Specialized wiring harness w/ chargeport
SWAT	Specialized Como SL front-rack, max. 15kg load, incl. Como SL basket w/cargo-net
Headlight	Supernova Mini2, 235lm, 12V, alloy housing
Taillight	Supernova E3, alloy housing, 3-LED, 250-degree visibility, fender mount, 12V
Chaincase	Integrated Chaincover
Kickstand	Specialized Center-Mount, 255mm
Rack	Specialized Pannier-rack, alloy tubing, max. 20kg load
Fenders	Specialized DRYTECH fenders, 65mm width, stainless steel fenderstays
Bell	Simple bell

TURBO COMO SL 4.0	S	M	L
Stack (mm)	623	641	697
Reach (mm)	401	426	433
Front Center (mm)	680	713	742
Seat Tube Length, Center to Top (mm)	380	390	420
Top Tube Length, Horizontal (mm)	634	666	694
Chainstay Length (mm)	484	484	484
Wheelbase (mm)	1154	1187	1216
Standover Height (mm)	575	575	600
Head Tube Length (mm)	190	210	270
BB Drop (mm)	75	75	75
BB Height (mm)	280	280	280
Head Tube Angle (°)	68	68	68
Seat Tube Angle, Actual (°)	69.5	69.5	69.5

PART NO.	DESCRIPTION	COLOR	SIZE
90121-5002	COMO SL 4.0	Cast Umber / Transparent	S
90121-5003			M
90121-5004			L
90121-5102	COMO SL 4.0	Dove Grey / Transparent	S
90121-5103			M
90121-5104			L
90121-5202	COMO SL 4.0	Raspberry / Transparent	S
90121-5203			M
90121-5204			L



SPECIALIZED